


## Schottky Rectifier Surface-Mount

### eSMP® Series



SMF (DO-219AB)



### FEATURES

- For surface mounted applications
- Ideal for automated placement
- Low power loss, high efficiency
- Oxide planar chip junction
- Meets MSL level 1, per J-STD-020, LF maximum peak of 260 °C
- Meets JESD 201 class 2 whisker test
- Wave and reflow solderable
- AEC-Q101 qualified
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)



**RoHS**  
COMPLIANT

### DESIGN SUPPORT TOOLS



[click logo to get started](#)

### MECHANICAL DATA

**Case:** SMF (DO-219AB)

**Polarity:** color band denotes cathode end

**Weight:** approx. 15 mg

**Packaging codes / options:**

GS18/10K per 13" reel (8 mm tape), 50K/box

GS08/3K per 7" reel (8 mm tape), 30K/box

**Circuit configuration:** single

### PARTS TABLE

| PART | ORDERING CODE          | MARKING | REMARKS       |
|------|------------------------|---------|---------------|
| SL02 | SL02-GS18 or SL02-GS08 | S2      | Tape and reel |
| SL03 | SL03-GS18 or SL03-GS08 | S3      | Tape and reel |

### ABSOLUTE MAXIMUM RATINGS ( $T_{amb} = 25\text{ °C}$ , unless otherwise specified)

| PARAMETER                                               | TEST CONDITION        | PART | SYMBOL      | VALUE | UNIT |
|---------------------------------------------------------|-----------------------|------|-------------|-------|------|
| Maximum repetitive peak reverse voltage                 |                       | SL02 | $V_{RRM}$   | 20    | V    |
|                                                         |                       | SL03 | $V_{RRM}$   | 30    | V    |
| Maximum RMS voltage                                     |                       | SL02 | $V_{RMS}$   | 14    | V    |
|                                                         |                       | SL03 | $V_{RMS}$   | 21    | V    |
| Maximum DC blocking voltage                             |                       | SL02 | $V_{DC}$    | 20    | V    |
|                                                         |                       | SL03 | $V_{DC}$    | 30    | V    |
| Maximum average forward rectified current               | $T_L = 109\text{ °C}$ |      | $I_{F(AV)}$ | 1.1   | A    |
| Peak forward surge current 8.3 ms single half sine-wave |                       |      | $I_{FSM}$   | 40    | A    |

### THERMAL CHARACTERISTICS ( $T_{amb} = 25\text{ °C}$ , unless otherwise specified)

| PARAMETER                                                 | TEST CONDITION | SYMBOL     | VALUE       | UNIT |
|-----------------------------------------------------------|----------------|------------|-------------|------|
| Thermal resistance junction to ambient air <sup>(1)</sup> |                | $R_{thJA}$ | 180         | K/W  |
| Maximum operating junction temperature                    |                | $T_j$      | 125         | °C   |
| Storage temperature range                                 |                | $T_{stg}$  | -55 to +150 | °C   |

#### Note

<sup>(1)</sup> Mounted on epoxy substrate with 3 mm x 3 mm Cu pads ( $\geq 40\text{ }\mu\text{m}$  thick)

| <b>ELECTRICAL CHARACTERISTICS</b> ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified) |                                     |      |          |      |       |       |               |
|----------------------------------------------------------------------------------------------------------|-------------------------------------|------|----------|------|-------|-------|---------------|
| PARAMETER                                                                                                | TEST CONDITION                      | PART | SYMBOL   | MIN. | TYP.  | MAX.  | UNIT          |
| Instantaneous forward voltage                                                                            | $I_F = 0.5\text{ A}$ <sup>(1)</sup> | SL02 | $V_F$    |      | 0.360 | 0.385 | V             |
|                                                                                                          |                                     | SL03 | $V_F$    |      | 0.395 | 0.43  | V             |
| Typical instantaneous forward voltage                                                                    | $I_F = 1.1\text{ A}$                | SL02 | $V_F$    |      | 0.420 |       | V             |
|                                                                                                          |                                     | SL03 | $V_F$    |      | 0.450 |       | V             |
| Maximum DC reverse current at rated DC blocking voltage                                                  | $T_A = 25\text{ }^{\circ}\text{C}$  | SL02 | $I_R$    |      |       | 250   | $\mu\text{A}$ |
|                                                                                                          | $T_A = 100\text{ }^{\circ}\text{C}$ | SL02 | $I_R$    |      |       | 8     | mA            |
|                                                                                                          | $T_A = 25\text{ }^{\circ}\text{C}$  | SL03 | $I_R$    |      |       | 130   | $\mu\text{A}$ |
|                                                                                                          | $T_A = 100\text{ }^{\circ}\text{C}$ | SL03 | $I_R$    |      |       | 6     | mA            |
| Reverse recovery time                                                                                    |                                     | SL02 | $t_{rr}$ |      |       | < 10  | ns            |
|                                                                                                          |                                     | SL03 | $t_{rr}$ |      |       | < 10  | ns            |

**Note**

(1) Pulse test: 300  $\mu\text{s}$  pulse width, 1 % duty cycle


**TYPICAL CHARACTERISTICS** ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)


Fig. 1 - Forward Current Derating Curve




Fig. 3 - Typical Instantaneous Forward Characteristics - SL02




Fig. 2 - Typical Junction Capacitance




Fig. 4 - Typical Reverse Current Characteristics - SL02




Fig. 5 - Typical Instantaneous Forward Characteristics - SL03






Fig. 6 - Typical Reverse Current Characteristics - SL03

**PACKAGE DIMENSIONS** in millimeters (inches): **SMF (DO-219AB)**


Foot print recommendation:

Created - Date: 15. February 2005  
Rev. 3 - Date: 13. March 2007  
Document no.: S8-V-3915.01-001 (4)  
17247

**BLISTERTAPE DIMENSION** in millimeters: **SMF (DO-219AB)**



| Mat: | A0  | B0  | K0  | W   | T     | P0  | P2  | P1  | D0  | D1 | E    | F   |
|------|-----|-----|-----|-----|-------|-----|-----|-----|-----|----|------|-----|
| PS   | 1.9 | 4.0 | 1.5 | 8.0 | 0.235 | 4.0 | 2.0 | 4.0 | 1.5 | 1  | 1.75 | 3.5 |

Document-No.: S8-V-3717.02-001 (3)

18513



**ORIENTATION IN CARRIER TAPE - SMF (DO-219AB)**



Document no.: S8-V-3717.02-003 (4)  
Created - Date: 09. Feb. 2010  
22670



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.