


## Green Thick Film Chip Resistors



### FEATURES

- Green resistor - does not use RoHS exemptions
- Stability  $\Delta R/R = 1\%$  for 1000 h at 70 °C
- 2 mm pitch packaging option for 0603 size
- Material categorization:  
for definitions of compliance please see  
[www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)



**RoHS**  
COMPLIANT  
HALOGEN  
**FREE**  
**GREEN**  
(5-2008)

### STANDARD ELECTRICAL SPECIFICATIONS

| TYPE    | CASE SIZE<br>IMPERIAL | CASE SIZE<br>METRIC | POWER RATING<br>$P_{70}$<br>W | LIMITING<br>ELEMENT<br>VOLTAGE<br>$U_{max.}$<br>$AC_{RMS}/DC$<br>V | TEMPERATURE<br>COEFFICIENT<br>$\pm$ ppm/K                                     | TOLERANCE<br>$\pm$ % | RESISTANCE<br>RANGE<br>$\Omega$ | SERIES   |
|---------|-----------------------|---------------------|-------------------------------|--------------------------------------------------------------------|-------------------------------------------------------------------------------|----------------------|---------------------------------|----------|
| RCG0402 | 0402                  | RR1005M             | 0.063                         | 50                                                                 | 100                                                                           | 0.5, 1               | 150 to 10M                      | E24; E96 |
|         |                       |                     |                               |                                                                    | 150                                                                           |                      | 1.0 to 147                      |          |
|         |                       |                     |                               |                                                                    | 200                                                                           | 5                    | 1.0 to 10M                      | E24      |
|         |                       |                     |                               |                                                                    | Zero-Ohm-Resistor: $R_{max.} = 20\text{ m}\Omega$ , $I_{max.} = 1.5\text{ A}$ |                      |                                 |          |
| RCG0603 | 0603                  | RR1608M             | 0.1                           | 75                                                                 | 100                                                                           | 0.5, 1               | 1.0 to 10M                      | E24; E96 |
|         |                       |                     |                               |                                                                    | 200                                                                           |                      |                                 |          |
|         |                       |                     |                               |                                                                    |                                                                               | 5                    |                                 | E24      |
|         |                       |                     |                               |                                                                    | Zero-Ohm-Resistor: $R_{max.} = 20\text{ m}\Omega$ , $I_{max.} = 2.0\text{ A}$ |                      |                                 |          |
| RCG0805 | 0805                  | RR2012M             | 0.125                         | 150                                                                | 100                                                                           | 0.5, 1               | 1.0 to 10M                      | E24; E96 |
|         |                       |                     |                               |                                                                    | 200                                                                           |                      |                                 |          |
|         |                       |                     |                               |                                                                    |                                                                               | 5                    |                                 | E24      |
|         |                       |                     |                               |                                                                    | Zero-Ohm-Resistor: $R_{max.} = 20\text{ m}\Omega$ , $I_{max.} = 2.5\text{ A}$ |                      |                                 |          |
| RCG1206 | 1206                  | RR3216M             | 0.25                          | 200                                                                | 100                                                                           | 0.5, 1               | 1.0 to 10M                      | E24; E96 |
|         |                       |                     |                               |                                                                    | 200                                                                           |                      |                                 |          |
|         |                       |                     |                               |                                                                    |                                                                               | 5                    |                                 | E24      |
|         |                       |                     |                               |                                                                    | Zero-Ohm-Resistor: $R_{max.} = 20\text{ m}\Omega$ , $I_{max.} = 3.5\text{ A}$ |                      |                                 |          |

### Notes

- These resistors do not feature a limited lifetime when operated within the permissible limits. However, resistance value drift increasing over operating time may result in exceeding a limit acceptable to the specific application, thereby establishing a functional lifetime.
- Marking: See datasheet "Surface Mount Resistor Marking" (document number 20020).
- Power rating depends on the max. temperature at the solder point, the component placement density and the substrate material.

### TECHNICAL SPECIFICATIONS

| PARAMETER                                  | UNIT     | RCG0402       | RCG0603 | RCG0805 | RCG1206 |
|--------------------------------------------|----------|---------------|---------|---------|---------|
| Rated dissipation $P_{70}$ <sup>(1)</sup>  | W        | 0.063         | 0.1     | 0.125   | 0.25    |
| Operating voltage $U_{max.}$ $AC_{RMS}/DC$ | V        | 50            | 75      | 150     | 200     |
| Insulation voltage $U_{ins}$ (1 min)       | V        | 75            | 100     | 200     | 300     |
| Insulation resistance                      | $\Omega$ | $> 10^9$      |         |         |         |
| Operating temperature range                | °C       | - 55 to + 155 |         |         |         |
| Mass                                       | mg       | 0.65          | 2       | 5.5     | 10      |

### Note

- <sup>(1)</sup> The power dissipation on the resistor generates a temperature rise against the local ambient, depending on the heat flow support of the printed-circuit board (thermal resistance). The rated dissipation applies only if the permitted film temperature of 155 °C is not exceeded.

**PART NUMBER AND PRODUCT DESCRIPTION**

PART NUMBER: RCG080510K0FKEA

|   |   |   |   |   |   |   |   |   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| R | C | G | 0 | 8 | 0 | 5 | 1 | 0 | K | 0 | F | K | E | A |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|

| TYPE    |
|---------|
| RCG0402 |
| RCG0603 |
| RCG0805 |
| RCG1206 |

| VALUE                    |
|--------------------------|
| R = Decimal              |
| K = Thousand             |
| M = Million              |
| 0000 = 0 $\Omega$ Jumper |

| TOLERANCE       |
|-----------------|
| D = $\pm 0.5\%$ |
| F = $\pm 1.0\%$ |
| J = $\pm 5.0\%$ |
| Z = Jumper      |

| TCR                 |
|---------------------|
| K = $\pm 100$ ppm/K |
| L = $\pm 150$ ppm/K |
| N = $\pm 200$ ppm/K |
| 0 = Jumper          |

| PACKAGING                           |
|-------------------------------------|
| EA, EB,<br>EC, ED,<br>EE, EI,<br>EL |

PRODUCT DESCRIPTION: RCG0805 100 10K 1 % EA

| RCG0805 |
|---------|
| TYPE    |
| RCG0402 |
| RCG0603 |
| RCG0805 |
| RCG1206 |

| 100             |
|-----------------|
| TCR             |
| $\pm 100$ ppm/K |
| $\pm 150$ ppm/K |
| $\pm 200$ ppm/K |



| 10K                 |
|---------------------|
| RESISTANCE VALUE    |
| 10R = 10 $\Omega$   |
| 10K = 10 k $\Omega$ |
| 1M = 1 M $\Omega$   |
| 0R0 = Jumper        |

| 1 %         |
|-------------|
| TOLERANCE   |
| $\pm 0.5\%$ |
| $\pm 1\%$   |
| $\pm 5\%$   |


| EA                                  |
|-------------------------------------|
| PACKAGING                           |
| EA, EB,<br>EC, ED,<br>EE, EI,<br>EL |

**PACKAGING**

| TYPE    | CODE | QUANTITY | CARRIER TAPE                                 | WIDTH | PITCH | REEL DIAMETER |
|---------|------|----------|----------------------------------------------|-------|-------|---------------|
| RCG0402 | ED   | 10 000   | Paper tape acc.<br>to IEC 60286-3<br>Type 1a | 8 mm  | 2 mm  | 180 mm/7"     |
|         | EE   | 50 000   |                                              |       |       | 330 mm/13"    |
| RCG0603 | EI   | 5000     | Paper tape acc.<br>to IEC 60268-3<br>Type 1a | 8 mm  | 2 mm  | 180 mm/7"     |
|         | ED   | 10 000   |                                              |       |       | 180 mm/7"     |
|         | EL   | 20 000   |                                              |       |       | 285 mm/11.25" |
|         | EE   | 50 000   |                                              |       |       | 330 mm/13"    |
|         | EA   | 5000     | Paper tape acc.<br>to IEC 60268-3<br>Type 1a | 8 mm  | 4 mm  | 180 mm/7"     |
|         | EB   | 10 000   |                                              |       |       | 285 mm/11.25" |
|         | EC   | 20 000   |                                              |       |       | 330 mm/13"    |
| RCG0805 | EA   | 5000     | Paper tape acc.<br>to IEC 60268-3<br>Type 1a | 8 mm  | 4 mm  | 180 mm/7"     |
|         | EB   | 10 000   |                                              |       |       | 285 mm/11.25" |
|         | EC   | 20 000   |                                              |       |       | 330 mm/13"    |
| RCG1206 | EA   | 5000     | Paper tape acc.<br>to IEC 60268-3<br>Type 1a | 8 mm  | 4 mm  | 180 mm/7"     |
|         | EB   | 10 000   |                                              |       |       | 285 mm/11.25" |
|         | EC   | 20 000   |                                              |       |       | 330 mm/13"    |

**DIMENSIONS** in millimeters


| SIZE     |         | DIMENSIONS                             |             |             |                                       |           | SOLDER PAD DIMENSIONS |     |     |                |     |     |
|----------|---------|----------------------------------------|-------------|-------------|---------------------------------------|-----------|-----------------------|-----|-----|----------------|-----|-----|
|          |         |                                        |             |             |                                       |           | REFLOW SOLDERING      |     |     | WAVE SOLDERING |     |     |
| IMPERIAL | METRIC  | L                                      | W           | H           | T1                                    | T2        | a                     | b   | l   | a              | b   | l   |
| 0402     | RR1005M | 1.0 ± 0.05                             | 0.5 ± 0.05  | 0.35 ± 0.05 | 0.25 ± 0.05                           | 0.2 ± 0.1 | 0.4                   | 0.6 | 0.5 |                |     |     |
| 0603     | RR1608M | 1.55 <sup>+0.10</sup> <sub>-0.05</sub> | 0.85 ± 0.1  | 0.45 ± 0.05 | 0.3 ± 0.2                             | 0.3 ± 0.2 | 0.5                   | 0.9 | 1.0 | 0.9            | 0.9 | 1.0 |
| 0805     | RR2012M | 2.0 <sup>+0.20</sup> <sub>-0.10</sub>  | 1.25 ± 0.15 | 0.45 ± 0.05 | 0.3 <sup>+0.20</sup> <sub>-0.10</sub> | 0.3 ± 0.2 | 0.7                   | 1.3 | 1.2 | 0.9            | 1.3 | 1.3 |
| 1206     | RR3216M | 3.2 <sup>+0.10</sup> <sub>-0.20</sub>  | 1.6 ± 0.15  | 0.55 ± 0.05 | 0.45 ± 0.2                            | 0.4 ± 0.2 | 0.9                   | 1.7 | 2.0 | 1.1            | 1.7 | 2.3 |

**FUNCTIONAL PERFORMANCE**

**GREEN REQUIREMENTS**

| SUBSTANCES                           | CONCENTRATION LIMIT |
|--------------------------------------|---------------------|
| Lead (Pb)                            | < 1000 ppm          |
| Mercury (Hg)                         | < 1000 ppm          |
| Cadmium (Cd)                         | < 100 ppm           |
| Hexavalent Chromium                  | < 1000 ppm          |
| Polybrominated Biphenyl (PBB)        | < 1000 ppm          |
| Polybrominated Diphenyl Ether (PBDE) | < 1000 ppm          |
| Bromine (Br)                         | < 900 ppm           |
| Chlorine (Cl)                        | < 900 ppm           |
| Sum of Bromine and Chlorine          | ≤ 1500 ppm max.     |
| Antimony (Sb)                        | < 900 ppm           |
| Red Phosphorous                      | < 100 ppm           |

**Notes**

- No exemptions (e.g. Pb in glass) may be applied to any substances or application for the “Green” category
- All concentration levels are based on homogenous materials

| TEST PROCEDURES AND REQUIREMENTS |                                  |                                                  |                                                                                                                     |                                                           |                                        |
|----------------------------------|----------------------------------|--------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------|----------------------------------------|
| EN 60115-1<br>CLAUSE             | IEC<br>60068-2<br>TEST<br>METHOD | TEST                                             | PROCEDURE                                                                                                           | REQUIREMENTS<br>PERMISSIBLE CHANGE ( $\Delta R$ )         |                                        |
|                                  |                                  |                                                  | Stability for product types:                                                                                        | <b>STABILITY CLASS 1<br/>OR BETTER</b>                    | <b>STABILITY CLASS 2<br/>OR BETTER</b> |
|                                  |                                  |                                                  | <b>RCG e3</b>                                                                                                       | 1 $\Omega$ to 10 M $\Omega$                               | 1 $\Omega$ to 10 M $\Omega$            |
| 4.5                              | -                                | Resistance                                       | -                                                                                                                   | $\pm 0.5 \%$ , $\pm 1 \%$                                 | $\pm 5 \%$                             |
| 4.7                              | -                                | Voltage proof                                    | $U = 1.4 \times U_{ins}$ ; 60 s                                                                                     | No flashover or breakdown                                 |                                        |
| 4.13                             | -                                | Short time overload                              | $U = 2.5 \times \sqrt{P_{70} \times R} \leq 2 \times U_{max.}$ ;<br>Duration acc. to style                          | $\pm (0.25 \% R + 0.05 \Omega)$                           | $\pm (0.5 \% R + 0.05 \Omega)$         |
| 4.17.2                           | 58 (Td)                          | Solderability                                    | Solder bath method;<br>Sn96.5Ag3Cu0.5<br>non-activated flux;<br>(245 $\pm$ 5) $^{\circ}\text{C}$<br>(3 $\pm$ 0.3) s | Good tinning ( $\geq 95 \%$ covered)<br>no visible damage |                                        |
| 4.8.4.2                          | -                                | Temperature<br>coefficient                       | (20/- 55/20) $^{\circ}\text{C}$ and<br>(20/125/20) $^{\circ}\text{C}$                                               | $\pm 100 \text{ ppm/K}$ , $\pm 150 \text{ ppm/K}$         | $\pm 200 \text{ ppm/K}$                |
| 4.32                             | 21 ( $U_{u3}$ )                  | Shear<br>(adhesion)                              | RR 1608 and smaller: 9 N<br>RR 2012 and larger: 45 N                                                                | No visible damage                                         |                                        |
| 4.33                             | 21 ( $U_{u1}$ )                  | Substrate bending                                | Depth 2 mm;<br>3 times                                                                                              | No visible damage, no open circuit in bent position       |                                        |
| 4.23                             | -                                | Climatic sequence:                               | -                                                                                                                   |                                                           |                                        |
| 4.23.2                           | 2 (Ba)                           | Dry heat                                         | 125 $^{\circ}\text{C}$ ; 16 h                                                                                       |                                                           |                                        |
| 4.23.3                           | 30 (Db)                          | Damp heat, cyclic                                | 55 $^{\circ}\text{C}$ ; $\geq 90 \%$ RH;<br>24 h; 1 cycle                                                           |                                                           |                                        |
| 4.23.4                           | 1 (Aa)                           | Cold                                             | - 55 $^{\circ}\text{C}$ ; 2 h                                                                                       | $\pm (1 \% R + 0.05 \Omega)$                              | $\pm (2 \% R + 0.1 \Omega)$            |
| 4.23.5                           | 13 (M)                           | Low air pressure                                 | 1 kPa; (25 $\pm$ 10) $^{\circ}\text{C}$ ; 1 h                                                                       |                                                           |                                        |
| 4.23.6                           | 30 (Db)                          | Damp heat, cyclic                                | 55 $^{\circ}\text{C}$ ; $\geq 90 \%$ RH;<br>24 h; 5 cycles                                                          |                                                           |                                        |
| 4.23.7                           | -                                | DC load                                          | $U = \sqrt{P_{70} \times R}$                                                                                        |                                                           |                                        |
| 4.25.1                           | -                                | Endurance at 70 $^{\circ}\text{C}$               | $U = \sqrt{P_{70} \times R} \leq U_{max.}$ ;<br>1.5 h on; 0.5 h off;<br>70 $^{\circ}\text{C}$ ; 1000 h              | $\pm (1 \% R + 0.05 \Omega)$                              | $\pm (2 \% R + 0.1 \Omega)$            |
| 4.18.2                           | 58 (Td)                          | Resistance to<br>soldering heat                  | Solder bath method<br>(260 $\pm$ 5) $^{\circ}\text{C}$ ;<br>(10 $\pm$ 1) s                                          | $\pm (0.25 \% R + 0.05 \Omega)$                           | $\pm (0.5 \% R + 0.05 \Omega)$         |
| 4.35                             | -                                | Flamability,<br>needle flame test                | IEC 60695-11-5;<br>10 s                                                                                             | No burning after 30 s                                     |                                        |
| 4.24                             | 78 (Cab)                         | Damp heat,<br>steady state                       | (40 $\pm$ 2) $^{\circ}\text{C}$ ;<br>(93 $\pm$ 3) % RH;<br>56 days                                                  | $\pm (1 \% R + 0.05 \Omega)$                              | $\pm (1 \% R + 0.1 \Omega)$            |
| 4.25.3                           | -                                | Endurance at<br>upper category<br>temperature    | 155 $^{\circ}\text{C}$ , 1000 h                                                                                     | $\pm (1 \% R + 0.05 \Omega)$                              | $\pm (2 \% R + 0.1 \Omega)$            |
| 4.40                             | -                                | Electrostatic<br>discharge<br>(human body model) | IEC 61340-3-1;<br>3 pos. + 3 neg. discharges;<br>ESD test voltage acc. to size                                      | $\pm (1 \% R + 0.05 \Omega)$                              |                                        |

| TEST PROCEDURES AND REQUIREMENTS |                                  |                                                               |                                                                                                              |                                                   |                                        |
|----------------------------------|----------------------------------|---------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------|---------------------------------------------------|----------------------------------------|
| EN 60115-1<br>CLAUSE             | IEC<br>60068-2<br>TEST<br>METHOD | TEST                                                          | PROCEDURE                                                                                                    | REQUIREMENTS<br>PERMISSIBLE CHANGE ( $\Delta R$ ) |                                        |
|                                  |                                  |                                                               | Stability for product types:                                                                                 | <b>STABILITY CLASS 1<br/>OR BETTER</b>            | <b>STABILITY CLASS 2<br/>OR BETTER</b> |
|                                  |                                  |                                                               | <b>RCG e3</b>                                                                                                | 1 $\Omega$ to 10 M $\Omega$                       | 1 $\Omega$ to 10 M $\Omega$            |
| 4.29                             | 45 (XA)                          | Component solvent resistance                                  | Isopropyl alcohol;<br>50 °C; method 2                                                                        | No visible damage                                 |                                        |
| 4.30                             | 45 (XA)                          | Solvent resistance of marking                                 | Isopropyl alcohol;<br>50 °C; method 1,<br>toothbrush                                                         | Marking legible,<br>no visible damage             |                                        |
| 4.22                             | 6 (Fc)                           | Vibration, endurance by sweeping                              | f = 10 Hz to 2000 Hz;<br>x, y, z $\leq$ 1.5 mm;<br>A $\leq$ 200 m/s <sup>2</sup> ;<br>10 sweeps per axis     | $\pm (0.25 \% R + 0.05 \Omega)$                   | $\pm (0.5 \% R + 0.05 \Omega)$         |
| 4.37                             | -                                | Periodic electric overload                                    | $U = \sqrt{15 \times P_{70} \times R}$<br>$\leq 2 \times U_{\max.}$ ;<br>0.1 s on; 2.5 s off;<br>1000 cycles | $\pm (1 \% R + 0.05 \Omega)$                      |                                        |
| 4.27                             | -                                | Single pulse high voltage overload,<br>10 $\mu$ s/700 $\mu$ s | $\dot{U} = 10 \times \sqrt{P_{70} \times R}$<br>$\leq 2 \times U_{\max.}$ ;<br>10 pulses                     | $\pm (1 \% R + 0.05 \Omega)$                      |                                        |

All tests are carried out in accordance with the following specifications:

- EN 60115-1, generic specification
- EN 140400, sectional specification
- EN 140401-802, detail specification
- IEC 60068-2, environmental test procedures

Packaging of components is done in paper tapes according to IEC 60286-3.



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.