



## Dual Flat No Lead Molded Precision Thin Film Resistor Surface Mount Network



The DFN series of precision surface mount resistor networks feature isolated thin film precision resistors mounted in a 0.8 mm pitch 4 mm x 4 mm dual flat no lead package. The networks feature 50 % savings in board space over traditional SOIC packages. They are ideally suited for applications of unity gain operational amplifiers that require close TC tracking and tight ratio tolerances over temperature. Custom configurations are available upon request.

### SCHEMATIC



### FEATURES

- 0.8 mm lead pitch
- MSL level 1 per J-STD-020
- Low profile 1 mm seated height
- Small size 4 mm x 4 mm size 50 % board savings over SOIC packages
- Wide resistance range 100  $\Omega$  to 100 k $\Omega$  available
- Custom configurations available
- Low TCR  $\pm 25$  ppm, TCR tracking to  $\pm 3$  ppm
- Ratio tolerances to  $\pm 0.025$  %
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)


**RoHS  
COMPLIANT**

### TYPICAL PERFORMANCE

|      | ABSOLUTE | TRACKING |
|------|----------|----------|
| TCR  | 25       | 3        |
|      | ABSOLUTE | RATIO    |
| TOL. | 0.1      | 0.05     |

### STANDARD RESISTANCE OFFERING ( $R_1 =$ )




|                 |                |
|-----------------|----------------|
| 500 $\Omega$    | 10 k $\Omega$  |
| 1 k $\Omega$    | 20 k $\Omega$  |
| 2 k $\Omega$    | 50 k $\Omega$  |
| 4.99 k $\Omega$ | 100 k $\Omega$ |
| 5 k $\Omega$    |                |

#### Note

- Consult factory for additional R values and schematics

### STANDARD ELECTRICAL SPECIFICATIONS

| TEST                           | SPECIFICATIONS                                    | CONDITIONS                                        |
|--------------------------------|---------------------------------------------------|---------------------------------------------------|
| Material                       | Passivated nichrome                               | -                                                 |
| Pin/Lead Number                | 8                                                 | -                                                 |
| Resistance Range               | 100 $\Omega$ to 100 k $\Omega$ per resistor       | -                                                 |
| TCR: Absolute                  | $\pm 25$ ppm/ $^{\circ}\text{C}$                  | -55 $^{\circ}\text{C}$ to +125 $^{\circ}\text{C}$ |
| TCR: Tracking                  | $\pm 3$ ppm/ $^{\circ}\text{C}$                   | -55 $^{\circ}\text{C}$ to +125 $^{\circ}\text{C}$ |
| Tolerance: Absolute            | $\pm 0.05$ % to $\pm 1.0$ %                       | +25 $^{\circ}\text{C}$                            |
| Tolerance: Ratio               | $\pm 0.025$ % to $\pm 0.5$ %                      | +25 $^{\circ}\text{C}$                            |
| Power Rating: Resistor         | 100 mW                                            | Maximum at +70 $^{\circ}\text{C}$                 |
| Power Rating: Package          | 100 mW x number of resistors                      | Maximum at +70 $^{\circ}\text{C}$                 |
| Stability: Absolute            | $\Delta R \pm 0.05$ %                             | 2000 h at +70 $^{\circ}\text{C}$                  |
| Stability: Ratio               | $\Delta R \pm 0.015$ %                            | 2000 h at +70 $^{\circ}\text{C}$                  |
| Voltage Coefficient            | < 0.1 ppm/V                                       | -                                                 |
| Working Voltage                | 100 V max. not to exceed $\sqrt{P \times R}$      | -                                                 |
| Operating Temperature Range    | -55 $^{\circ}\text{C}$ to +125 $^{\circ}\text{C}$ | -                                                 |
| Storage Temperature Range      | -55 $^{\circ}\text{C}$ to +150 $^{\circ}\text{C}$ | -                                                 |
| Noise                          | < -30 dB                                          | -                                                 |
| Thermal EMF                    | < 0.08 $\mu\text{V}/^{\circ}\text{C}$             | -                                                 |
| Shelf Life Stability: Absolute | $\Delta R \pm 0.01$ %                             | 1 year at +25 $^{\circ}\text{C}$                  |
| Shelf Life Stability: Ratio    | $\Delta R \pm 0.002$ %                            | 1 year at +25 $^{\circ}\text{C}$                  |

**DIMENSIONS AND IMPRINTING** in millimeters


|   |      |       |
|---|------|-------|
| A | Max. | 0.900 |
|   | Nom. | 0.850 |
|   | Min. | 0.800 |

**Note**

- Contact factory for package outlines for higher pin count or custom configurations

**MECHANICAL SPECIFICATIONS**

|                                |                     |
|--------------------------------|---------------------|
| Resistive Element              | Passivated nichrome |
| Substrate Material             | Ceramic             |
| Body                           | Molded epoxy        |
| Terminals                      | Copper alloy        |
| Plating                        | 100 % matte tin     |
| Marking Resistance to Solvents | Per MIL-PRF-914     |

**GLOBAL PART NUMBER INFORMATION**

New Global Part Numbering: DFNA1002AT1

| D                               | F | N                                  | A | 1                                                                                                                                                                         | 0 | 0                                                                                                                                                                                                                          | 2 | A                                                                                                                                                                                                       | T | 1 |
|---------------------------------|---|------------------------------------|---|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---|---|
| GLOBAL MODEL                    |   | SCHEMATIC                          |   | RESISTANCE                                                                                                                                                                |   | TOLERANCE AND RATIO TOLERANCE                                                                                                                                                                                              |   | PACKAGING                                                                                                                                                                                               |   |   |
| DFN<br>(Lead (Pb)-free)<br>(e3) |   | A = Isolated equal value resistors |   | The first 3 digits are significant figures and the last digit specifies the number of zeros to follow.<br><br>Example:<br>1002 = 10 kΩ<br>1003 = 100 kΩ<br>4991 = 4.99 kΩ |   | Z = ± 0.05 % abs. ± 0.025 ratio <sup>(1)</sup><br>A = ± 0.1 % abs. ± 0.05 % ratio<br>B = ± 0.1 % abs. ± 0.1 % ratio<br>C = ± 0.25 % abs. ± 0.1 % ratio<br>D = ± 0.5 % abs. ± 0.1 % ratio<br>F = ± 1.0 % abs. ± 0.5 % ratio |   | TAPE AND REEL<br>T0 = 100 min., 100 mult<br>T1 = 1000 min., 1000 mult <sup>(2)</sup><br>T3 = 300 min., 300 mult<br>T5 = 500 min., 500 mult<br>TF = Full reel<br>TS = 100 min., 1 mult<br><br>UF = TUBED |   |   |

**Notes**

- (1) Tolerance available on 1 kΩ and up
- (2) Preferred packaging code



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.