




## High Performance Schottky Rectifier, 2 x 20 A


**D<sup>2</sup>PAK (TO-263AB)**

**VS-40L15CTS-M3**

**TO-262AA**

**VS-40L15CT-1-M3**

### FEATURES

- 125 °C T<sub>J</sub> operation (V<sub>R</sub> < 5 V)
- Center tap module
- Optimized for OR-ing applications
- Ultralow forward voltage drop
- High frequency operation
- High purity, high temperature epoxy encapsulation for enhanced mechanical strength and moisture resistance
- Guard ring for enhanced ruggedness and long term reliability
- Meets MSL level 1, per J-STD-020, LF maximum peak of 245 °C
- Designed and qualified according to JEDEC®-JESD 47
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)



**RoHS**  
COMPLIANT  
HALOGEN  
**FREE**

### DESCRIPTION

The center tap Schottky rectifier module has been optimized for ultralow forward voltage drop specifically for the OR-ing of parallel power supplies. The proprietary barrier technology allows for reliable operation up to 125 °C junction temperature. Typical applications are in parallel switching power supplies, converters, reverse battery protection, and redundant power subsystems.

### PRIMARY CHARACTERISTICS

|                                  |                                         |
|----------------------------------|-----------------------------------------|
| I <sub>F(AV)</sub>               | 2 x 20 A                                |
| V <sub>R</sub>                   | 15 V                                    |
| V <sub>F</sub> at I <sub>F</sub> | 0.33 V                                  |
| I <sub>RM</sub> max.             | 600 mA at 100 °C                        |
| T <sub>J</sub> max.              | 125 °C                                  |
| E <sub>AS</sub>                  | 10 mJ                                   |
| Package                          | D <sup>2</sup> PAK (TO-263AB), TO-262AA |
| Circuit configuration            | Common cathode                          |

### MAJOR RATINGS AND CHARACTERISTICS

| SYMBOL             | CHARACTERISTICS                                                 | VALUES      | UNITS |
|--------------------|-----------------------------------------------------------------|-------------|-------|
| I <sub>F(AV)</sub> | Rectangular waveform                                            | 40          | A     |
| V <sub>RRM</sub>   |                                                                 | 15          | V     |
| I <sub>FSM</sub>   | t <sub>p</sub> = 5 μs sine                                      | 700         | A     |
| V <sub>F</sub>     | 19 A <sub>pk</sub> , T <sub>J</sub> = 125 °C (per leg, typical) | 0.25        | V     |
| T <sub>J</sub>     |                                                                 | -55 to +125 | °C    |

### VOLTAGE RATINGS

| PARAMETER                            | SYMBOL           | TEST CONDITIONS         | VS-40L15CTS-M3<br>VS-40L15CT-1-M3 | UNITS |
|--------------------------------------|------------------|-------------------------|-----------------------------------|-------|
| Maximum DC reverse voltage           | V <sub>R</sub>   | T <sub>J</sub> = 100 °C | 15                                | V     |
| Maximum working peak reverse voltage | V <sub>RWM</sub> |                         |                                   |       |

**ABSOLUTE MAXIMUM RATINGS**

| PARAMETER                                                               | SYMBOL      | TEST CONDITIONS                                                                                                           | VALUES   | UNITS |
|-------------------------------------------------------------------------|-------------|---------------------------------------------------------------------------------------------------------------------------|----------|-------|
| Maximum average forward current, see fig. 5                             | $I_{F(AV)}$ | 50 % duty cycle at $T_C = 85^\circ\text{C}$ , rectangular waveform                                                        | 20<br>40 | A     |
| Maximum peak one cycle non-repetitive surge current per leg, see fig. 7 | $I_{FSM}$   | 5 $\mu\text{s}$ sine or 3 $\mu\text{s}$ rect. pulse                                                                       | 700      |       |
|                                                                         |             | 10 ms sine or 6 ms rect. pulse                                                                                            | 330      |       |
| Non-repetitive avalanche energy per leg                                 | $E_{AS}$    | $T_J = 25^\circ\text{C}$ , $I_{AS} = 2\text{ A}$ , $L = 6\text{ mH}$                                                      | 10       | mJ    |
| Repetitive avalanche current per leg                                    | $I_{AR}$    | Current decaying linearly to zero in 1 $\mu\text{s}$<br>Frequency limited by $T_J$ maximum $V_A = 1.5 \times V_R$ typical | 2        | A     |

**ELECTRICAL SPECIFICATIONS**

| PARAMETER                                          | SYMBOL         | TEST CONDITIONS                                                                  | TYP.   | MAX. | UNITS            |
|----------------------------------------------------|----------------|----------------------------------------------------------------------------------|--------|------|------------------|
| Maximum forward voltage drop per leg<br>See fig. 1 | $V_{FM}^{(1)}$ | 19 A                                                                             | -      | 0.41 | V                |
|                                                    |                | 40 A                                                                             | -      | 0.52 |                  |
|                                                    |                | 19 A                                                                             | 0.25   | 0.33 |                  |
|                                                    |                | 40 A                                                                             | 0.37   | 0.50 |                  |
| Reverse leakage current per leg<br>See fig. 2      | $I_{RM}^{(1)}$ | $T_J = 25^\circ\text{C}$                                                         | -      | 10   | mA               |
|                                                    |                | $T_J = 100^\circ\text{C}$                                                        | -      | 600  |                  |
| Threshold voltage                                  | $V_{F(TO)}$    | $T_J = T_J$ maximum                                                              | 0.182  |      | V                |
| Forward slope resistance                           | $r_t$          |                                                                                  | 7.6    |      | m $\Omega$       |
| Maximum junction capacitance per leg               | $C_T$          | $V_R = 5\text{ V}_{DC}$ (test signal range 100 kHz to 1 MHz), $25^\circ\text{C}$ | -      | 2000 | pF               |
| Typical series inductance per leg                  | $L_S$          | Measured lead to lead 5 mm from package body                                     | 8      | -    | nH               |
| Maximum voltage rate of change                     | $dV/dt$        | Rated $V_R$                                                                      | 10 000 |      | V/ $\mu\text{s}$ |

**Note**(1) Pulse width < 300  $\mu\text{s}$ , duty cycle < 2 %**THERMAL - MECHANICAL SPECIFICATIONS**

| PARAMETER                                            | SYMBOL            | TEST CONDITIONS                          | VALUES      | UNITS                  |
|------------------------------------------------------|-------------------|------------------------------------------|-------------|------------------------|
| Maximum junction temperature range                   | T <sub>J</sub>    |                                          | -55 to +125 | °C                     |
| Maximum storage temperature range                    | T <sub>Stg</sub>  |                                          | -55 to +150 |                        |
| Maximum thermal resistance, junction to case per leg | R <sub>thJC</sub> | DC operation<br>See fig. 4               | 1.5         | °C/W                   |
| Typical thermal resistance, case to heatsink         | R <sub>thCS</sub> | Mounting surface, smooth and greased     | 0.50        |                        |
| Maximum thermal resistance, junction to ambient      | R <sub>thJA</sub> | DC operation                             | 40          |                        |
| Approximate weight                                   |                   |                                          | 2           | g                      |
|                                                      |                   |                                          | 0.07        | oz.                    |
| Mounting torque                                      | minimum           | Non-lubricated threads                   | 6 (5)       | kgf · cm<br>(lbf · in) |
|                                                      | maximum           |                                          | 12 (10)     |                        |
| Marking device                                       |                   | Case style D <sup>2</sup> PAK (TO-263AB) | 40L15CTS    |                        |
|                                                      |                   | Case style TO-262AA                      | 40L15CT-1   |                        |




Fig. 1 - Maximum Forward Voltage Drop Characteristics




Fig. 2 - Typical Values of Reverse Current vs. Reverse Voltage





Fig. 3 - Typical Junction Capacitance vs. Reverse Voltage


Fig. 4 - Maximum Thermal Impedance  $Z_{thJC}$  Characteristics




Fig. 5 - Maximum Allowable Case Temperature vs. Average Forward Current




Fig. 6 - Forward Power Loss Characteristics




Fig. 7 - Maximum Non-Repetitive Surge Current




Fig. 8 - Unclamped Inductive Test Circuit

#### Note

- (1) Formula used:  $T_C = T_J - (P_d + P_{dREV}) \times R_{thJC}$ ;  
 $P_d$  = forward power loss =  $I_{F(AV)} \times V_{FM}$  at  $(I_{F(AV)}/D)$  (see fig. 6);  
 $P_{dREV}$  = inverse power loss =  $V_{R1} \times I_R (1 - D)$ ;  $I_R$  at  $V_{R1} = 80\%$  rated  $V_R$

**ORDERING INFORMATION TABLE**

|             |                                                                                                                                                                                      |           |          |           |          |          |          |            |            |
|-------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|----------|-----------|----------|----------|----------|------------|------------|
| Device code | <b>VS-</b>                                                                                                                                                                           | <b>40</b> | <b>L</b> | <b>15</b> | <b>C</b> | <b>T</b> | <b>S</b> | <b>TRL</b> | <b>-M3</b> |
|             | 1                                                                                                                                                                                    | 2         | 3        | 4         | 5        | 6        | 7        | 8          | 9          |
| <b>1</b>    | - Vishay Semiconductors product                                                                                                                                                      |           |          |           |          |          |          |            |            |
| <b>2</b>    | - Current rating (40 A)                                                                                                                                                              |           |          |           |          |          |          |            |            |
| <b>3</b>    | - L = Schottky "L" series                                                                                                                                                            |           |          |           |          |          |          |            |            |
| <b>4</b>    | - Voltage rating (15 V)                                                                                                                                                              |           |          |           |          |          |          |            |            |
| <b>5</b>    | - C = common cathode                                                                                                                                                                 |           |          |           |          |          |          |            |            |
| <b>6</b>    | - T = TO-220                                                                                                                                                                         |           |          |           |          |          |          |            |            |
| <b>7</b>    | - • S = D <sup>2</sup> PAK (TO-263AB)<br>• -1 = TO-262AA                                                                                                                             |           |          |           |          |          |          |            |            |
| <b>8</b>    | - • None = tube<br>• TRL = tape and reel (left oriented - for D <sup>2</sup> PAK (TO-263AB) only)<br>• TRR = tape and reel (right oriented - for D <sup>2</sup> PAK (TO-263AB) only) |           |          |           |          |          |          |            |            |
| <b>9</b>    | - -M3 = halogen-free, RoHS-compliant, and termination lead (Pb)-free                                                                                                                 |           |          |           |          |          |          |            |            |

| <b>ORDERING INFORMATION</b> (Example) |                  |                        |                          |
|---------------------------------------|------------------|------------------------|--------------------------|
| PREFERRED P/N                         | QUANTITY PER T/R | MINIMUM ORDER QUANTITY | PACKAGING DESCRIPTION    |
| VS-40L15CTS-M3                        | 50               | 1000                   | Antistatic plastic tubes |
| VS-40L15CTSTRL-M3                     | 800              | 800                    | 13" diameter reel        |
| VS-40L15CTSTRR-M3                     | 800              | 800                    | 13" diameter reel        |
| VS-40L15CT-1-M3                       | 50               | 1000                   | Antistatic plastic tubes |

| <b>LINKS TO RELATED DOCUMENTS</b> |                               |                                                                        |
|-----------------------------------|-------------------------------|------------------------------------------------------------------------|
| Dimensions                        | D <sup>2</sup> PAK (TO-263AB) | <a href="http://www.vishay.com/doc?96164">www.vishay.com/doc?96164</a> |
|                                   | TO-262AA                      | <a href="http://www.vishay.com/doc?96165">www.vishay.com/doc?96165</a> |
| Part marking information          | D <sup>2</sup> PAK (TO-263AB) | <a href="http://www.vishay.com/doc?95444">www.vishay.com/doc?95444</a> |
|                                   | TO-262AA                      | <a href="http://www.vishay.com/doc?95443">www.vishay.com/doc?95443</a> |
| Packaging information             |                               | <a href="http://www.vishay.com/doc?96424">www.vishay.com/doc?96424</a> |



## D<sup>2</sup>PAK

### DIMENSIONS in millimeters and inches

Conforms to JEDEC® outline D<sup>2</sup>PAK (SMD-220)



| SYMBOL | MILLIMETERS |       | INCHES |       | NOTES |
|--------|-------------|-------|--------|-------|-------|
|        | MIN.        | MAX.  | MIN.   | MAX.  |       |
| A      | 4.06        | 4.83  | 0.160  | 0.190 |       |
| A1     | 0.00        | 0.254 | 0.000  | 0.010 |       |
| b      | 0.51        | 0.99  | 0.020  | 0.039 |       |
| b1     | 0.51        | 0.89  | 0.020  | 0.035 | 4     |
| b2     | 1.14        | 1.78  | 0.045  | 0.070 |       |
| b3     | 1.14        | 1.73  | 0.045  | 0.068 | 4     |
| c      | 0.38        | 0.74  | 0.015  | 0.029 |       |
| c1     | 0.38        | 0.58  | 0.015  | 0.023 | 4     |
| c2     | 1.14        | 1.65  | 0.045  | 0.065 |       |
| D      | 8.51        | 9.65  | 0.335  | 0.380 | 2     |

| SYMBOL | MILLIMETERS |       | INCHES    |       | NOTES |
|--------|-------------|-------|-----------|-------|-------|
|        | MIN.        | MAX.  | MIN.      | MAX.  |       |
| D1     | 6.86        | 8.00  | 0.270     | 0.315 | 3     |
| E      | 9.65        | 10.67 | 0.380     | 0.420 | 2, 3  |
| E1     | 7.90        | 8.80  | 0.311     | 0.346 | 3     |
| e      | 2.54 BSC    |       | 0.100 BSC |       |       |
| H      | 14.61       | 15.88 | 0.575     | 0.625 |       |
| L      | 1.78        | 2.79  | 0.070     | 0.110 |       |
| L1     | -           | 1.65  | -         | 0.066 | 3     |
| L2     | 1.27        | 1.78  | 0.050     | 0.070 |       |
| L3     | 0.25 BSC    |       | 0.010 BSC |       |       |
| L4     | 4.78        | 5.28  | 0.188     | 0.208 |       |

#### Notes

- (1) Dimensioning and tolerancing per ASME Y14.5 M-1994
- (2) Dimension D and E do not include mold flash. Mold flash shall not exceed 0.127 mm (0.005") per side. These dimensions are measured at the outmost extremes of the plastic body
- (3) Thermal pad contour optional within dimension E, L1, D1 and E1
- (4) Dimension b1 and c1 apply to base metal only
- (5) Datum A and B to be determined at datum plane H
- (6) Controlling dimension: inch
- (7) Outline conforms to JEDEC® outline TO-263AB

## TO-262

### DIMENSIONS in millimeters and inches

#### Modified JEDEC outline TO-262




$\pm 0.010$  A A B




#### Lead assignments

##### Diodes

1. - Anode (two die)/open (one die)
2. - Cathode
3. - Anode



Section A - A



Section B - B and C - C

Scale: None

| SYMBOL | MILLIMETERS |       | INCHES    |       | NOTES |
|--------|-------------|-------|-----------|-------|-------|
|        | MIN.        | MAX.  | MIN.      | MAX.  |       |
| A      | 4.06        | 4.83  | 0.160     | 0.190 |       |
| A1     | 2.03        | 3.02  | 0.080     | 0.119 |       |
| b      | 0.51        | 0.99  | 0.020     | 0.039 |       |
| b1     | 0.51        | 0.89  | 0.020     | 0.035 | 4     |
| b2     | 1.14        | 1.78  | 0.045     | 0.070 |       |
| b3     | 1.14        | 1.73  | 0.045     | 0.068 | 4     |
| c      | 0.38        | 0.74  | 0.015     | 0.029 |       |
| c1     | 0.38        | 0.58  | 0.015     | 0.023 | 4     |
| c2     | 1.14        | 1.65  | 0.045     | 0.065 |       |
| D      | 8.51        | 9.65  | 0.335     | 0.380 | 2     |
| D1     | 6.86        | 8.00  | 0.270     | 0.315 | 3     |
| E      | 9.65        | 10.67 | 0.380     | 0.420 | 2, 3  |
| E1     | 7.90        | 8.80  | 0.311     | 0.346 | 3     |
| e      | 2.54 BSC    |       | 0.100 BSC |       |       |
| L      | 13.46       | 14.10 | 0.530     | 0.555 |       |
| L1     | -           | 1.65  | -         | 0.065 | 3     |
| L2     | 3.56        | 3.71  | 0.140     | 0.146 |       |

#### Notes

- (1) Dimensioning and tolerancing as per ASME Y14.5M-1994
- (2) Dimension D and E do not include mold flash. Mold flash shall not exceed 0.127 mm (0.005") per side. These dimensions are measured at the outmost extremes of the plastic body
- (3) Thermal pad contour optional within dimension E, L1, D1 and E1

- (4) Dimension b1 and c1 apply to base metal only

- (5) Controlling dimension: inches

- (6) Outline conform to JEDEC TO-262 except A1 (maximum), b (minimum) and D1 (minimum) where dimensions derived the actual package outline

## TO-262



Example: This is a xxxxxx-1 <sup>(1)</sup> with assembly lot code AC, assembled on WW 19, 2001 in the assembly line "X"

### Note

<sup>(1)</sup> If part number contain "H" as last digit, product is AEC-Q101 qualified

| ENVIRONMENTAL NAMING CODE (Z) | PRODUCT DEFINITION                                          |
|-------------------------------|-------------------------------------------------------------|
| A                             | Termination lead (Pb)-free                                  |
| B                             | Totally lead (Pb)-free                                      |
| E                             | RoHS-compliant and termination lead (Pb)-free               |
| F                             | RoHS-compliant and totally lead (Pb)-free                   |
| M                             | Halogen-free, RoHS-compliant and termination lead (Pb)-free |
| N                             | Halogen-free, RoHS-compliant and totally lead (Pb)-free     |
| G                             | Green                                                       |



## D<sup>2</sup>PAK



Example: This is a xxxxxx <sup>(1)</sup> with assembly lot code AC, assembled on WW 02, 2010

### Note

(1) If part number contain "H" as last digit, product is AEC-Q101 qualified

| ENVIRONMENTAL NAMING CODE (Z) | PRODUCT DEFINITION                                           |
|-------------------------------|--------------------------------------------------------------|
| A                             | Termination lead (Pb)-free                                   |
| B                             | Totally lead (Pb)-free                                       |
| E                             | RoHS-compliant and termination lead (Pb)-free                |
| F                             | RoHS-compliant and totally lead (Pb)-free                    |
| M                             | Halogen-free, RoHS-compliant, and termination lead (Pb)-free |
| N                             | Halogen-free, RoHS-compliant, and totally lead (Pb)-free     |
| G                             | Green                                                        |



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.