

FFA.1S.303.CLAC22

SUMMARY

# Wires		
Low	3	
High	0	
Coax	0	
Triax	0	Download
Quad	0	Request a quote
Fiber	0	Catalog
Fluidic	0	
Series	15	
Termination type	Male solder	
IP rating	50	
Cable Ø	1.40 - 2.20 mm	
Matching parts	ERA.1S.303.CLL	
Status	active	
Alternative part		

Image is for illustrative purpose only

TECHNICAL DETAILS

Mechanics

Shell Style/Model	FFA*: Straight plug, cable collet		
Keying	Hermaphroditic keying ("half moon" insert), plug has male pin 1		
Housing Material	Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces		
Cable Fixing	C22: 1.4 - 2.2 mm		
Variant			
Weight	17.89 g		
Performance			
Configuration	15.303 : 3 Low Voltage		
Insulator	L: PEEK (UL 94 / V-0/3.2, depends on material thickness)		
Rated Current	10 Amps		

Specifications

Contact Type: Solder Max. Matings: 5000 Contact Dia.: 0.9 mm (0.0354in)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.


Bucket Dia.: 0.8 mm (0.031in) Max. Solid Conductor: 0.34 mm^2 (AWG 22) R (max): 4.8 mOhm Vtest: 1200 V (AC), 1800 V (DC)

Others

Endurance (Shell): 5000 mating cycles Temp (min / max): -55°C / +250°C Humidity (max): <=95% [at 60 deg C /140 F] Vibration: 15 g [10 Hz - 2000 Hz] Shock Resistance: 100 g [6 ms] Salt Spray Corrosion: >144 hr Climatical Category: 50/175/21 Shielding (min): 75 dB (10 MHz) Shielding (min): 40 dB (1 GHz) IP Rating: 50

DRAWINGS

Draws





Dimensions

	А	L	м	S2
mm.	12	42.5	31.5	8.5
in.	0,47	1,67	1,24	0,33

RECOMMENDED BY LEMO

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Tools

Spanner wrench: DCD.1S.015.PA085

Cables

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.