

0050MD-1-004 Information

Heisener.com

Part Number 0050MD-1-004 Manufacturer Talema Group LLC Category

Transformers **Power Transformers**

Description XFMR TOROIDAL 50VA THRM PROTCT

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0050MD-1-004 Specifications

Manufacturer Part Number0050MD-1-004ManufacturerTalema Group LLCCategoryTransformersPackage-SeriesMDTypeToroidalVoltage - Primary100V, 120V, 200V, 240VVoltage - Secondary (Full Load)Parallel 120V, Series 240VCurrent - Output (Max)Parallel 420mA, Series 210mAPrimary Winding(s)Dual, Multiple TapsSecondary Winding(s)Single, Multiple TapsCenter TapNoPower - Max50 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension81.00mm Dia x 38.00mm WHeight - Seated (Max)-Voltage - Isolation5000VrmsWeight1.8 lbs (816.5g)		
Category Transformers Package - Series MD Type Toroidal Voltage - Primary 100V, 120V, 200V, 240V Voltage - Secondary (Full Load) Parallel 120V, Series 240V Current - Output (Max) Parallel 420mA, Series 210mA Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max 50 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension 81.00mm Dia x 38.00mm W Height - Seated (Max) - Voltage - Isolation 5000Vrms Weight 1.8 lbs (816.5g)	Manufacturer Part Number	0050MD-1-004
Package Power Transformers Package Power Transformers Frinary Power Transformers MD Type Toroidal Voltage - Primary 100V, 120V, 200V, 240V Voltage - Secondary (Full Load) Parallel 120V, Series 240V Current - Output (Max) Parallel 420mA, Series 210mA Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max So VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension 81.00mm Dia x 38.00mm W Height - Seated (Max) Voltage - Isolation Weight 1.8 lbs (816.5g)	Manufacturer	Talema Group LLC
Package-SeriesMDTypeToroidalVoltage - Primary100V, 120V, 200V, 240VVoltage - Secondary (Full Load)Parallel 120V, Series 240VCurrent - Output (Max)Parallel 420mA, Series 210mAPrimary Winding(s)Dual, Multiple TapsSecondary Winding(s)Single, Multiple TapsCenter TapNoPower - Max50 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension81.00mm Dia x 38.00mm WHeight - Seated (Max)-Voltage - Isolation5000VrmsWeight1.8 lbs (816.5g)	Category	Transformers
Series MD Type Toroidal Voltage - Primary 100V, 120V, 200V, 240V Voltage - Secondary (Full Load) Parallel 120V, Series 240V Current - Output (Max) Parallel 420mA, Series 210mA Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max 50 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension 81.00mm Dia x 38.00mm W Height - Seated (Max) Voltage - Isolation 5000Vrms Weight 1.8 lbs (816.5g)		Power Transformers
Type Toroidal Voltage - Primary 100V, 120V, 200V, 240V Voltage - Secondary (Full Load) Parallel 120V, Series 240V Current - Output (Max) Parallel 420mA, Series 210mA Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max 50 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension 81.00mm Dia x 38.00mm W Height - Seated (Max) - Voltage - Isolation 5000Vrms Weight 1.8 lbs (816.5g)	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 120V, Series 240V Current - Output (Max) Parallel 420mA, Series 210mA Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max 50 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension 81.00mm Dia x 38.00mm W Height - Seated (Max) Voltage - Isolation Weight 1.8 lbs (816.5g)	Series	MD
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 420mA, Series 210mA Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max 50 VA Mounting Type Chassis Mount Termination Style Size / Dimension 81.00mm Dia x 38.00mm W Height - Seated (Max) Voltage - Isolation Weight Parallel 120V, Series 240V Single, Multiple Taps No Chassis Mount 50 VA Wire Leads \$1.00mm Dia x 38.00mm W 1.8 lbs (816.5g)	Туре	Toroidal
Current - Output (Max) Primary Winding(s) Dual, Multiple Taps Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max So VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension 81.00mm Dia x 38.00mm W Height - Seated (Max) Voltage - Isolation Source Wire Leads Size / S	Voltage - Primary	100V, 120V, 200V, 240V
Primary Winding(s) Secondary Winding(s) Center Tap No Power - Max Mounting Type Chassis Mount Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Weight Dual, Multiple Taps Single, Multiple Taps No Chassis Mount Chassis Mount Wire Leads 81.00mm Dia x 38.00mm W - Voltage - Isolation 5000Vrms 1.8 lbs (816.5g)	Voltage - Secondary (Full Load)	Parallel 120V, Series 240V
Secondary Winding(s)Single, Multiple TapsCenter TapNoPower - Max50 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension81.00mm Dia x 38.00mm WHeight - Seated (Max)-Voltage - Isolation5000VrmsWeight1.8 lbs (816.5g)	Current - Output (Max)	Parallel 420mA, Series 210mA
Center Tap No Power - Max 50 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension 81.00mm Dia x 38.00mm W Height - Seated (Max) - Voltage - Isolation 5000Vrms Weight 1.8 lbs (816.5g)	Primary Winding(s)	Dual, Multiple Taps
Power - Max 50 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension 81.00mm Dia x 38.00mm W Height - Seated (Max) - Voltage - Isolation 5000Vrms Weight 1.8 lbs (816.5g)	Secondary Winding(s)	Single, Multiple Taps
Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension 81.00mm Dia x 38.00mm W Height - Seated (Max) - Voltage - Isolation 5000Vrms Weight 1.8 lbs (816.5g)	Center Tap	No
Termination Style Wire Leads Size / Dimension 81.00mm Dia x 38.00mm W Height - Seated (Max) - Voltage - Isolation 5000Vrms Weight 1.8 lbs (816.5g)	Power - Max	50 VA
Size / Dimension 81.00mm Dia x 38.00mm W Height - Seated (Max) - Voltage - Isolation 5000Vrms Weight 1.8 lbs (816.5g)	Mounting Type	Chassis Mount
Height - Seated (Max) Voltage - Isolation Source Veight 1.8 lbs (816.5g)	Termination Style	Wire Leads
Voltage - Isolation 5000Vrms Weight 1.8 lbs (816.5g)	Size / Dimension	81.00mm Dia x 38.00mm W
Weight 1.8 lbs (816.5g)	Height - Seated (Max)	-
	Voltage - Isolation	5000Vrms
Report errors?	Weight	1.8 lbs (816.5g)
		Report errors?

0050MD-1-004 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0050MD-1-004 Payment Methods



















0050MD-1-004 Shipping Methods













If you have any question about 0050MD-1-004, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com