



### 0224007.MXUP Information



For Reference Only

Part Number 0224007.MXUP
Manufacturer Littelfuse Inc.
Category Circuit Protection

Fuses

**Description** FUSE GLASS 7A 125VAC 2AG **Package** 2AG, 5mm x 15mm (Axial)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 0224007.MXUP Specifications

Manufacturer Part Number0224007.MXUPManufacturerLittelfuse Inc.CategoryCircuit ProtectionPackage2AG, 5mm x 15mm (Axial)Series224Fuse TypeCartridge, GlassCurrent Rating7AVoltage Rating - AC125VVoltage Rating - DC-Response TimeFastPackage / Case2AG, 5mm x 15mm (Axial)Mounting TypeThrough HoleBreaking Capacity @ Rated Voltage500AMelting 12t40ApprovalsCE, CSA, PSE, ULOperating Temperature-55°C ~ 125°CColor-Size / Dimension0.185" Dia x 0.570" L (4.70mm x 14.48mm)Report errors?	•	
Category         Circuit Protection           Fuses           Package         2AG, 5mm x 15mm (Axial)           Series         224           Fuse Type         Cartridge, Glass           Current Rating         7A           Voltage Rating - AC         125V           Voltage Rating - DC         -           Response Time         Fast           Package / Case         2AG, 5mm x 15mm (Axial)           Mounting Type         Through Hole           Breaking Capacity @ Rated Voltage         500A           Melting I2t         40           Approvals         CE, CSA, PSE, UL           Operating Temperature         -55°C ~ 125°C           Color         -           Size / Dimension         0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Manufacturer Part Number	0224007.MXUP
Fuses           Package         2AG, 5mm x 15mm (Axial)           Series         224           Fuse Type         Cartridge, Glass           Current Rating         7A           Voltage Rating - AC         125V           Voltage Rating - DC         -           Response Time         Fast           Package / Case         2AG, 5mm x 15mm (Axial)           Mounting Type         Through Hole           Breaking Capacity @ Rated Voltage         500A           Melting 12t         40           Approvals         CE, CSA, PSE, UL           Operating Temperature         -55°C ~ 125°C           Color         -           Size / Dimension         0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Manufacturer	Littelfuse Inc.
Package       2AG, 5mm x 15mm (Axial)         Series       224         Fuse Type       Cartridge, Glass         Current Rating       7A         Voltage Rating - AC       125V         Voltage Rating - DC       -         Response Time       Fast         Package / Case       2AG, 5mm x 15mm (Axial)         Mounting Type       Through Hole         Breaking Capacity @ Rated Voltage       500A         Melting I2t       40         Approvals       CE, CSA, PSE, UL         Operating Temperature       -55°C ~ 125°C         Color       -         Size / Dimension       0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Category	Circuit Protection
Series       224         Fuse Type       Cartridge, Glass         Current Rating       7A         Voltage Rating - AC       125V         Voltage Rating - DC       -         Response Time       Fast         Package / Case       2AG, 5mm x 15mm (Axial)         Mounting Type       Through Hole         Breaking Capacity @ Rated Voltage       500A         Melting I2t       40         Approvals       CE, CSA, PSE, UL         Operating Temperature       -55°C ~ 125°C         Color       -         Size / Dimension       0.185" Dia x 0.570" L (4.70mm x 14.48mm)		Fuses
Fuse Type Current Rating 7A Voltage Rating - AC 125V Voltage Rating - DC Response Time Fast Package / Case 2AG, 5mm x 15mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t 40 Approvals CE, CSA, PSE, UL Operating Temperature -55°C ~ 125°C Color Size / Dimension Cartridge, Glass 7A Cartridge, Glass 7A 7A 125V 7A 125V Cetable Cartridge, Glass 7A 125V Cetable Cartridge, Glass 7A 125V Cetable Cartridge, Glass 7A 125V 125V Cetable Cartridge, Glass 7A 125V 125V Cetable Cartridge, Glass 7A 125V 125V 125V 125V 126V 126V 126V 126V 126V 126V 126V 126	Package	2AG, 5mm x 15mm (Axial)
Current Rating  Voltage Rating - AC  125V  Voltage Rating - DC  Response Time  Package / Case  Package / Case  Through Hole  Breaking Capacity @ Rated Voltage  Melting I2t  Approvals  Operating Temperature  CE, CSA, PSE, UL  Operating Temperature  -55°C ~ 125°C  Color  Size / Dimension  7A  125V  12	Series	224
Voltage Rating - AC  Voltage Rating - DC  Response Time  Fast  Package / Case  2AG, 5mm x 15mm (Axial)  Mounting Type  Through Hole  Breaking Capacity @ Rated Voltage  Melting I2t  Approvals  CE, CSA, PSE, UL  Operating Temperature  -55°C ~ 125°C  Color  Size / Dimension  125V  -  125V	Fuse Type	Cartridge, Glass
Voltage Rating - DC  Response Time Fast  Package / Case 2AG, 5mm x 15mm (Axial)  Mounting Type Through Hole  Breaking Capacity @ Rated Voltage 500A  Melting I2t 40  Approvals CE, CSA, PSE, UL  Operating Temperature -55°C ~ 125°C  Color -  Size / Dimension  -  0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Current Rating	7A
Response Time Fast  Package / Case 2AG, 5mm x 15mm (Axial)  Mounting Type Through Hole  Breaking Capacity @ Rated Voltage 500A  Melting I2t 40  Approvals CE, CSA, PSE, UL  Operating Temperature -55°C ~ 125°C  Color -  Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Voltage Rating - AC	125V
Package / Case 2AG, 5mm x 15mm (Axial)  Mounting Type Through Hole  Breaking Capacity @ Rated Voltage 500A  Melting I2t 40  Approvals CE, CSA, PSE, UL  Operating Temperature -55°C ~ 125°C  Color -  Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Voltage Rating - DC	-
Mounting Type  Breaking Capacity @ Rated Voltage  Melting I2t  Approvals  CE, CSA, PSE, UL  Operating Temperature  -55°C ~ 125°C  Color  Size / Dimension  Through Hole  500A  40  -55°C ~ 125°C  -125°C  -125°C  -125°C  -125°C  -125°C  -125°C  -125°C	Response Time	Fast
Breaking Capacity @ Rated Voltage 500A  Melting I2t 40  Approvals CE, CSA, PSE, UL  Operating Temperature -55°C ~ 125°C  Color -  Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Package / Case	2AG, 5mm x 15mm (Axial)
Melting I2t40ApprovalsCE, CSA, PSE, ULOperating Temperature $-55^{\circ}$ C ~ $125^{\circ}$ CColor-Size / Dimension $0.185''$ Dia x $0.570''$ L $(4.70 \text{mm x } 14.48 \text{mm})$	Mounting Type	Through Hole
Approvals  CE, CSA, PSE, UL  Operating Temperature  -55°C ~ 125°C  Color  Size / Dimension  CE, CSA, PSE, UL  -55°C ~ 125°C  0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Breaking Capacity @ Rated Voltage	500A
Operating Temperature         -55°C ~ 125°C           Color         -           Size / Dimension         0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Melting I2t	40
Color - Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Approvals	CE, CSA, PSE, UL
Size / Dimension 0.185" Dia x 0.570" L (4.70mm x 14.48mm)	Operating Temperature	-55°C ~ 125°C
, and the second se	Color	-
Report errors?	Size / Dimension	0.185" Dia x 0.570" L (4.70mm x 14.48mm)
		Report errors?

### 0224007.MXUP Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# 0224007.MXUP Payment Methods



















### 0224007.MXUP Shipping Methods













If you have any question about 0224007.MXUP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com