

02CO050.Z Information

Manufacturer Littelfuse Inc. Category Circuit Protection Heisener.com

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 50A 600VAC/250VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

Part Number 02CO050.Z

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









02CO050.Z Specifications

Manufacturer Part Number 02C0050.Z Manufacturer Littelfuse Inc. Category Circuit Protection Package Cylindrical, Blade Terminal (Bolt) Series HRCII-C Fuse Type Cartridge Current Rating 50A Voltage Rating - AC 600V Voltage Rating - DC 250V Response Time Slow Applications Motor Protection Features - Class - Approvals CSA Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 80kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.024" Dia x 2.244" L (26.00mm x 57.00mm)		
Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series HRCII-C Fuse Type Cartridge Current Rating 50A Voltage Rating - AC 600V Voltage Rating - DC 250V Response Time Slow Applications Motor Protection Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) 1.024" Dia x 2.244" L (26.00mm x 57.00mm)	Manufacturer Part Number	02CO050.Z
Package Cylindrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series HRCII-C Fuse Type Cartridge Current Rating 50A Voltage Rating - AC 600V Voltage Rating - DC 250V Response Time Slow Applications Motor Protection Features - Class - Approvals CSA Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 80kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.024" Dia x 2.244" L (26.00mm x 57.00mm)	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesHRCII-CFuse TypeCartridgeCurrent Rating50AVoltage Rating - AC600VVoltage Rating - DC250VResponse TimeSlowApplicationsMotor ProtectionFeatures-Class-ApprovalsCSAOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 80kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.024" Dia x 2.244" L (26.00mm x 57.00mm)	Category	Circuit Protection
SeriesHRCII-CFuse TypeCartridgeCurrent Rating50AVoltage Rating - AC600VVoltage Rating - DC250VResponse TimeSlowApplicationsMotor ProtectionFeatures-Class-ApprovalsCSAOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 80kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.024" Dia x 2.244" L (26.00mm x 57.00mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 50A Voltage Rating - AC 600V Voltage Rating - DC 250V Response Time Slow Applications Motor Protection Features - Class - Approvals CSA Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Current Rating 600V Cartridge 600V Approvals CSOV Response Time Slow Motor Protection CSA CSA CSA Cyerating Temperature Bolt Mount CSA Cylindrical, Blade Terminal (Bolt) Size / Dimension Cartridge 600V Approvals CSOV Costanting Capacity @ Rated Voltage Cylindrical, Blade Terminal (Bolt) Size / Dimension Cartridge Size / Dimension Cartridge Size / Dimension	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 600V Voltage Rating - DC 250V Response Time Slow Applications Motor Protection Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 500V Mounting Tyne 500A 600V	Series	HRCII-C
Voltage Rating - AC Voltage Rating - DC 250V Response Time Slow Applications Motor Protection Features - Class - Approvals CSA Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 600V 6	Fuse Type	Cartridge
Voltage Rating - DC Response Time Slow Applications Motor Protection Features - Class - Approvals CSA Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 250V Mounting Type Slow Mount (Solv) 250W 260W 2	Current Rating	50A
Response Time Applications Motor Protection Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Slow Motor Protection Motor Protection CSA CSA CSA CSA CSA DC Bolt Mount Bolt Mount Cylindrical, Blade Terminal (Bolt) 1.024" Dia x 2.244" L (26.00mm x 57.00mm)	Voltage Rating - AC	600V
Applications Motor Protection Features - Class - Approvals CSA Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 80kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.024" Dia x 2.244" L (26.00mm x 57.00mm)	Voltage Rating - DC	250V
Features - Class - CSA Approvals CSA Operating Temperature - CSA Breaking Capacity @ Rated Voltage 200kA AC, 80kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.024" Dia x 2.244" L (26.00mm x 57.00mm)	Response Time	Slow
Class - CSA Operating Temperature - Constant Con	Applications	Motor Protection
Approvals CSA Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension CSA CUSA CUSA	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 80kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.024" Dia x 2.244" L (26.00mm x 57.00mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA AC, 80kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.024" Dia x 2.244" L (26.00mm x 57.00mm)	Approvals	CSA
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.024" Dia x 2.244" L (26.00mm x 57.00mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.024" Dia x 2.244" L (26.00mm x 57.00mm)	Breaking Capacity @ Rated Voltage	200kA AC, 80kA DC
Size / Dimension 1.024" Dia x 2.244" L (26.00mm x 57.00mm)	Mounting Type	Bolt Mount
· · · · · ·	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	1.024" Dia x 2.244" L (26.00mm x 57.00mm)
		Report errors?

02CO050.Z Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

02CO050.Z Payment Methods



















02CO050.Z Shipping Methods













If you have any question about 02CO050.Z, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com