

0466.125NR

0466.125NR Information

facturer Littelfuse Inc. ory Circuit Protection Fuses FUSE BOARD MNT 125MA 125VAC/VDC ge 1206 (3216 Metric) For the pricing/inventory/lead time, please contact	
us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote
	facturer Littelfuse Inc. Dry Circuit Protection Fuses ption FUSE BOARD MNT 125MA 125VAC/VDC ge 1206 (3216 Metric) For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



0466.125NR Specifications

ManufacturerLittlefuse Inc.CategoryCircuit ProtectionFusesPackage1206 (3216 Metric)SeriesSlimLine? 466Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating125mAVoltage Rating - AC125VVoltage Rating - DC125VResponse TimeFastPackage / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMetting 12t0004ApprovalsCSA, ULOperating Temperature-55°C ~ 90°CColor-Size / Dimension125" L x 0.060" W x 0.023" H (3.18mm x 1.52mm x 0.58mm)			
CategoryCircuit ProtectionFusesPackage1206 (3216 Metric)SeriesSlimLine? 466Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating125mAVoltage Rating - AC125VVoltage Rating - DC125VResponse TimeFastPackage / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AApprovalsCSA, ULOperating Temperature-55°C ~ 90°CColor-Size / Dimension0.125" L x 0.060" W x 0.023" H (3.18mm x 1.52mm x 0.58mm)	Manufacturer Part Number	0466.125NR	
Fuses Package 1206 (3216 Metric) Series SlimLine? 466 Fuse Type Board Mount (Cartridge Style Excluded) Current Rating 125mA Voltage Rating - AC 125V Voltage Rating - DC 125V Response Time Fast Package / Case 1206 (3216 Metric) Mounting Type Surface Mount Breaking Capacity @ Rated Voltage 50A Approvals CSA, UL Operating Temperature -55°C ~ 90°C Color - Size / Dimension 0.125" L x 0.060" W x 0.023" H (3.18mm x 1.52mm x 0.58mm)	Manufacturer	Littelfuse Inc.	
Package1206 (3216 Metric)SeriesSlimLine? 466Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating125mAVoltage Rating - AC125VVoltage Rating - DC125VResponse TimeFastPackage / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMetring 12t0.0004ApprovalsCSA, ULOperating Temperature-55°C ~ 90°CColor-Size / Dimension0.125" L x 0.060" W x 0.023" H (3.18mm x 1.52mm x 0.58mm)	Category	Circuit Protection	
Series SlimLine? 466 Fuse Type Board Mount (Cartridge Style Excluded) Current Rating 125mA Voltage Rating - AC 125V Voltage Rating - DC 125V Response Time Fast Rackage / Case 1206 (3216 Metric) Mounting Type Surface Mount Breaking Capacity @ Rated Voltage 50A Approvals CSA, UL Operating Temperature -55°C ~ 90°C Color - Size / Dimension 0.125" L x 0.060" W x 0.023" H (3.18mm x 1.52mm x 0.58mm)		Fuses	
Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating125mAVoltage Rating - AC125VVoltage Rating - DC125VResponse TimeFastPackage / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMetting I2t0.0004ApprovalsCSA, ULOperating Temperature-55°C ~ 90°CColor-Size / Dimension0.125" L x 0.060" W x 0.023" H (3.18mm x 1.52mm x 0.58mm)	Package	1206 (3216 Metric)	
Current Rating 125mA Voltage Rating - AC 125V Voltage Rating - DC 125V Response Time Fast Package / Case 1206 (3216 Metric) Mounting Type Surface Mount Breaking Capacity @ Rated Voltage 50A Approvals CSA, UL Operating Temperature -55°C ~ 90°C Color - Size / Dimension 0.125" L x 0.060" W x 0.023" H (3.18mm x 1.52mm x 0.58mm)	Series	SlimLine? 466	
Notice Notice Voltage Rating - AC 125V Voltage Rating - DC 125V Response Time Fast Package / Case 1206 (3216 Metric) Mounting Type Surface Mount Breaking Capacity @ Rated Voltage 50A Melting I2t 0.0004 Operating Temperature cSA, UL Operating Temperature -55°C ~ 90°C Color - Size / Dimension 0.125" L x 0.060" W x 0.023" H (3.18mm x 1.52mm x 0.58mm)	Fuse Type	Board Mount (Cartridge Style Excluded)	
Voltage Rating - DC125VResponse TimeFastPackage / Case1206 (3216 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.0004ApprovalsCSA, ULOperating Temperature-55°C ~ 90°CColor-Size / Dimension0.125" L x 0.060" W x 0.023" H (3.18mm x 1.52mm x 0.58mm)	Current Rating	125mA	
Response Time Fast Package / Case 1206 (3216 Metric) Mounting Type Surface Mount Breaking Capacity @ Rated Voltage 50A Melting I2t 0.0004 Approvals CSA, UL Operating Temperature -55°C ~ 90°C Color - Size / Dimension 0.125" L x 0.060" W x 0.023" H (3.18mm x 1.52mm x 0.58mm)	Voltage Rating - AC	125V	
Package / Case 1206 (3216 Metric) Mounting Type Surface Mount Breaking Capacity @ Rated Voltage 50A Melting I2t 0.0004 Approvals CSA, UL Operating Temperature -55°C ~ 90°C Color - Size / Dimension 0.125" L x 0.060" W x 0.023" H (3.18mm x 1.52mm x 0.58mm)	Voltage Rating - DC	125V	
Mounting Type Surface Mount Breaking Capacity @ Rated Voltage 50A Melting I2t 0.0004 Approvals CSA, UL Operating Temperature -55°C ~ 90°C Color - Size / Dimension 0.125" L x 0.060" W x 0.023" H (3.18mm x 1.52mm x 0.58mm)	Response Time	Fast	
Breaking Capacity @ Rated Voltage 50A Melting I2t 0.0004 Approvals CSA, UL Operating Temperature -55°C ~ 90°C Color - Size / Dimension 0.125" L x 0.060" W x 0.023" H (3.18mm x 1.52mm x 0.58mm)	Package / Case	1206 (3216 Metric)	
Melting I2t 0.0004 Approvals CSA, UL Operating Temperature -55°C ~ 90°C Color - Size / Dimension 0.125" L x 0.060" W x 0.023" H (3.18mm x 1.52mm x 0.58mm)	Mounting Type	Surface Mount	
Approvals CSA, UL Operating Temperature -55°C ~ 90°C Color - Size / Dimension 0.125" L x 0.060" W x 0.023" H (3.18mm x 1.52mm x 0.58mm)	Breaking Capacity @ Rated Voltage	50A	
Operating Temperature -55°C ~ 90°C Color - Size / Dimension 0.125" L x 0.060" W x 0.023" H (3.18mm x 1.52mm x 0.58mm)	Melting I2t	0.0004	
Color - Size / Dimension 0.125" L x 0.060" W x 0.023" H (3.18mm x 1.52mm x 0.58mm)	Approvals	CSA, UL	
Size / Dimension 0.125" L x 0.060" W x 0.023" H (3.18mm x 1.52mm x 0.58mm)	Operating Temperature	-55°C ~ 90°C	
	Color	-	
Report errors?	Size / Dimension	0.125" L x 0.060" W x 0.023" H (3.18mm x 1.52mm x 0.58mm)	
Report chois:			Report errors?

0466.125NR Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE SUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

If you have any question about 0466.125NR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com