

0467001.NR

0467001.NR Information



0467001.NR
Littelfuse Inc.
Circuit Protection Fuses
FUSE BOARD MNT 1A 32VAC/VDC 0603
0603 (1608 Metric)
For the pricing/inventory/lead time, please contact us
Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



0467001.NR Specifications

Manufacturer Littelfuse Inc. Category Circuit Protection Fuses Fuses Package 0603 (1608 Metric) Series 467 Fuse Type Board Mount (Catrridge Style Excluded) Current Rating IA Voltage Rating - AC 32V Voltage Rating - DC 32V Response Time Fast Package / Case 0603 (1608 Metric) Mounting Type Surface Mount Mounting Type Surface Mount Mething 12t 0.0212 Approvals CSA, UL Operating Temperature -55°C ~ 90°C Color -			
CategoryCircuit ProtectionFusesPackage6603 (1608 Metric)Series467Fuse TypeBoard Mount (Catridge Style Excluded)Fuse TypeBoard Mount (Catridge Style Excluded)Current Rating1AVoltage Rating - AC32VVoltage Rating - DC32VResponse TimeFastPackage / Case6003 (1608 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting 12t0.0212ApprovalsCSA, ULOperating Temperature-55°C ~ 90°CColor-Size / Dimension0.063" L x 0.032" W x 0.012" H (1.60mm x 0.81mm x 0.31mm)	Manufacturer Part Number	0467001.NR	
Fuses Package 0603 (1608 Metric) Series 467 Fuse Type Board Mount (Cartridge Style Excluded) Current Rating 1A Voltage Rating - AC 32V Voltage Rating - DC 32V Response Time Fast Package / Case 0603 (1608 Metric) Mounting Type Surface Mount Breaking Capacity @ Rated Voltage 50A Melting 12t 0.0212 Approvals CSA, UL Operating Temperature -55°C ~ 90°C Color - Size / Dimension 0.063" L x 0.032" W x 0.012" H (1.60mm x 0.81mm x 0.31mm)	Manufacturer	Littelfuse Inc.	
Package0603 (1608 Metric)Series467Fuse TypeBoard Mount (Cartridge Style Excluded)Fuse TypeIACurrent Rating1AVoltage Rating - AC32VVoltage Rating - DC32VResponse TimeFastPackage / Case0603 (1608 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.0212ApprovalsCSA, ULOperating Temperature-55°C ~ 90°CColor-Size / Dimension0.063" L x 0.032" W x 0.012" H (1.60mm x 0.81mm x 0.31mm)	Category	Circuit Protection	
Series 467 Fuse Type Board Mount (Cartridge Style Excluded) Current Rating 1A Voltage Rating - AC 32V Voltage Rating - DC 32V Response Time Fast Package / Case 0603 (1608 Metric) Mounting Type Surface Mount Breaking Capacity @ Rated Voltage 50A Melting I2t 0.0212 Operating Temperature -55°C ~ 90°C Color - Size / Dimension 0.063" L x 0.032" W x 0.012" H (1.60mm x 0.81mm x 0.31mm)		Fuses	
Fuse TypeBoard Mount (Cartridge Style Excluded)Fuse TypeBoard Mount (Cartridge Style Excluded)Current Rating1AVoltage Rating - AC32VVoltage Rating - DC32VResponse TimeFastPackage / Case0603 (1608 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.0212ApprovalsCSA, ULOperating Temperature-55°C ~ 90°CColor-Size / Dimension0.063" L x 0.032" W x 0.012" H (1.60mm x 0.81mm x 0.31mm)	Package	0603 (1608 Metric)	
Current Rating 1A Voltage Rating - AC 32V Voltage Rating - DC 32V Response Time Fast Package / Case 0603 (1608 Metric) Mounting Type Surface Mount Breaking Capacity @ Rated Voltage 50A Melting 12t 0.0212 Approvals CSA, UL Operating Temperature -55°C ~ 90°C Color - Size / Dimension 0.063" L x 0.032" W x 0.012" H (1.60mm x 0.81mm x 0.31mm)	Series	467	
Voltage Rating - AC32VVoltage Rating - DC32VResponse TimeFastPackage / Case0603 (1608 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.0212ApprovalsCSA, ULOperating Temperature-55°C ~ 90°CColor-Size / Dimension0.063" L x 0.032" W x 0.012" H (1.60mm x 0.81mm x 0.31mm)	Fuse Type	Board Mount (Cartridge Style Excluded)	
Voltage Rating - DC32VResponse TimeFastPackage / Case0603 (1608 Metric)Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.0212ApprovalsCSA, ULOperating Temperature-55°C ~ 90°CColor-Size / Dimension0.063" L x 0.032" W x 0.012" H (1.60mm x 0.81mm x 0.31mm)	Current Rating	1A	
Response Time Fast Package / Case 0603 (1608 Metric) Mounting Type Surface Mount Breaking Capacity @ Rated Voltage 50A Melting I2t 0.0212 Approvals CSA, UL Operating Temperature -55°C ~ 90°C Color - Size / Dimension 0.063" L x 0.032" W x 0.012" H (1.60mm x 0.81mm x 0.31mm)	Voltage Rating - AC	32V	
Package / Case 0603 (1608 Metric) Mounting Type Surface Mount Breaking Capacity @ Rated Voltage 50A Melting I2t 0.0212 Approvals CSA, UL Operating Temperature -55°C ~ 90°C Color - Size / Dimension 0.063" L x 0.032" W x 0.012" H (1.60mm x 0.81mm x 0.31mm)	Voltage Rating - DC	32V	
Mounting TypeSurface MountBreaking Capacity @ Rated Voltage50AMelting I2t0.0212ApprovalsCSA, ULOperating Temperature-55°C ~ 90°CColor-Size / Dimension0.063" L x 0.032" W x 0.012" H (1.60mm x 0.81mm x 0.31mm)	Response Time	Fast	
Breaking Capacity @ Rated Voltage50AMelting I2t0.0212ApprovalsCSA, ULOperating Temperature-55°C ~ 90°CColor-Size / Dimension0.063" L x 0.032" W x 0.012" H (1.60mm x 0.81mm x 0.31mm)	Package / Case	0603 (1608 Metric)	
Melting I2t 0.0212 Approvals CSA, UL Operating Temperature -55°C ~ 90°C Color - Size / Dimension 0.063" L x 0.032" W x 0.012" H (1.60mm x 0.81mm x 0.31mm)	Mounting Type	Surface Mount	
ApprovalsCSA, ULOperating Temperature-55°C ~ 90°CColor-Size / Dimension0.063" L x 0.032" W x 0.012" H (1.60mm x 0.81mm x 0.31mm)	Breaking Capacity @ Rated Voltage	50A	
Operating Temperature -55°C ~ 90°C Color - Size / Dimension 0.063" L x 0.032" W x 0.012" H (1.60mm x 0.81mm x 0.31mm)	Melting I2t	0.0212	
Color - Size / Dimension 0.063" L x 0.032" W x 0.012" H (1.60mm x 0.81mm x 0.31mm)	Approvals	CSA, UL	
Size / Dimension 0.063" L x 0.032" W x 0.012" H (1.60mm x 0.81mm x 0.31mm)	Operating Temperature	-55°C ~ 90°C	
	Color	-	
Report errors?	Size / Dimension	0.063" L x 0.032" W x 0.012" H (1.60mm x 0.81mm x 0.31mm)	
			Report errors?

0467001.NR Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE GUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

If you have any question about 0467001.NR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com