



0477002.MXEP Information



For Reference Only

Part Number 0477002.MXEP
Manufacturer Littelfuse Inc.
Category Circuit Protection

Fuses

Description FUSE CERM 2A 500VAC 400VDC 5X20

Package 5mm x 20mm (Axial)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0477002.MXEP Specifications

Manufacturer Part Number 0477002.MXEP Manufacturer Littelfuse Inc. Category Circuit Protection Fuses Fuses Package 5mm x 20mm (Axial) Series 477 Fuse Type Cartridge, Ceramic Current Rating 2A Voltage Rating - AC 500V Voltage Rating - DC 400V Response Time Slow Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A AC, 1.5kA DC Melting 12t 9.12 Approvals cULus, PSE, SEMKO Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.228" Dia x 0.886" L (5.80mm x 22.50mm)	•	
Category Circuit Protection Fuses Package 5mm x 20mm (Axial) Series 477 Fuse Type Cartridge, Ceramic Current Rating 2A Voltage Rating - AC 500V Voltage Rating - DC 400V Response Time Slow Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A AC, 1.5kA DC Melting I2t 9.12 Approvals cULus, PSE, SEMKO Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.228" Dia x 0.886" L (5.80mm x 22.50mm)	Manufacturer Part Number	0477002.MXEP
Fuses Package 5mm x 20mm (Axial) Series 477 Fuse Type Cartridge, Ceramic Current Rating 2A Voltage Rating - AC 500V Voltage Rating - DC 400V Response Time Slow Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A AC, 1.5kA DC Melting I2t 9.12 Approvals cULus, PSE, SEMKO Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.228" Dia x 0.886" L (5.80mm x 22.50mm)	Manufacturer	Littelfuse Inc.
Package 5mm x 20mm (Axial) Series 477 Fuse Type Cartridge, Ceramic Current Rating 2A Voltage Rating - AC 500V Voltage Rating - DC 400V Response Time Slow Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A AC, 1.5kA DC Melting I2t 9.12 Approvals cULus, PSE, SEMKO Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.228" Dia x 0.886" L (5.80mm x 22.50mm)	Category	Circuit Protection
Series 477 Fuse Type Cartridge, Ceramic Current Rating 2A Voltage Rating - AC 500V Voltage Rating - DC 400V Response Time Slow Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A AC, 1.5kA DC Melting I2t 9.12 Approvals cULus, PSE, SEMKO Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.228" Dia x 0.886" L (5.80mm x 22.50mm)		Fuses
Fuse Type Current Rating 2A Voltage Rating - AC 500V Voltage Rating - DC 400V Response Time Slow Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t Approvals Operating Temperature -55°C ~ 125°C Color Size / Dimension Cartridge, Ceramic 2A Cartridge, Ceramic 2A Current Rating 2A 5m0V 400V 400V Figure 1000 400V 5low 5mx 20mm (Axial) 400V 6vitale Avitale 6vitale 6vitale Avitale 6vitale 6vitale Avitale 6vitale	Package	5mm x 20mm (Axial)
Current Rating Voltage Rating - AC 500V Voltage Rating - DC 400V Response Time Slow Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage Melting I2t Approvals Operating Temperature -55°C ~ 125°C Color Size / Dimension 2A 400V	Series	477
Voltage Rating - AC Voltage Rating - DC 400V Response Time Slow Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A AC, 1.5kA DC Melting I2t Approvals culus, PSE, SEMKO Operating Temperature -55°C ~ 125°C Color Size / Dimension 500V 400V 400V 400V 400V 400V 5low 5mm x 20mm (Axial) 7hrough Hole 100A AC, 1.5kA DC 9.12 9.12 9.12 600 Culus, PSE, SEMKO Operating Temperature -55°C ~ 125°C -55°C ~ 125°C	Fuse Type	Cartridge, Ceramic
Voltage Rating - DC Response Time Slow Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A AC, 1.5kA DC Melting I2t Approvals culus, PSE, SEMKO Operating Temperature -55°C ~ 125°C Color - Size / Dimension 400V 400V 400V 400V 400V 400V 400V 400V 5low 5mm x 20mm (Axial) 7hrough Hole 100A AC, 1.5kA DC 100A AC, 1.5kA DC 9.12 9.12 400V 5mm x 20mm (Axial) 7hrough Hole 100A AC, 1.5kA DC 9.12 6ulting I2t 9.12 6ulting I2t 100A AC, 1.5kA DC 9.12 6ulting I2t 100A AC, 1.5kA DC	Current Rating	2A
Response Time Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A AC, 1.5kA DC Melting I2t Approvals cULus, PSE, SEMKO Operating Temperature -55°C ~ 125°C Color Size / Dimension Slow 5mm x 20mm (Axial) Culus, PSE, SEMKO 0.228" Dia x 0.886" L (5.80mm x 22.50mm)	Voltage Rating - AC	500V
Package / Case 5mm x 20mm (Axial) Mounting Type Through Hole Breaking Capacity @ Rated Voltage 100A AC, 1.5kA DC Melting I2t 9.12 Approvals cULus, PSE, SEMKO Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.228" Dia x 0.886" L (5.80mm x 22.50mm)	Voltage Rating - DC	400V
Mounting Type Breaking Capacity @ Rated Voltage 100A AC, 1.5kA DC Melting I2t Approvals CULus, PSE, SEMKO Operating Temperature -55°C ~ 125°C Color Size / Dimension Through Hole 100A AC, 1.5kA DC 9.12 CULus, PSE, SEMKO -55°C ~ 125°C -55°C ~ 125°C	Response Time	Slow
Breaking Capacity @ Rated Voltage 100A AC, 1.5kA DC Melting I2t 9.12 Approvals cULus, PSE, SEMKO Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.228" Dia x 0.886" L (5.80mm x 22.50mm)	Package / Case	5mm x 20mm (Axial)
Melting I2t9.12ApprovalscULus, PSE, SEMKOOperating Temperature -55° C ~ 125° CColor-Size / Dimension0.228" Dia x 0.886" L (5.80mm x 22.50mm)	Mounting Type	Through Hole
Approvals cULus, PSE, SEMKO Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.228" Dia x 0.886" L (5.80mm x 22.50mm)	Breaking Capacity @ Rated Voltage	100A AC, 1.5kA DC
Operating Temperature -55°C ~ 125°C Color - Size / Dimension 0.228" Dia x 0.886" L (5.80mm x 22.50mm)	Melting I2t	9.12
Color - Size / Dimension 0.228" Dia x 0.886" L (5.80mm x 22.50mm)	Approvals	cULus, PSE, SEMKO
Size / Dimension 0.228" Dia x 0.886" L (5.80mm x 22.50mm)	Operating Temperature	-55°C ~ 125°C
, and the second se	Color	-
Report errors?	Size / Dimension	0.228" Dia x 0.886" L (5.80mm x 22.50mm)
		Report errors?

0477002.MXEP Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0477002.MXEP Payment Methods



















0477002.MXEP Shipping Methods













If you have any question about 0477002.MXEP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com