

# 0743232012

#### 0743232012 Information

Heisener.com	Part Number Manufacturer Category Description Package	0743232012 Molex, LLC Connectors, Interconnects USB, DVI, HDMI Connectors DVI-A PLUG CONN SUB-ASSY 30 U - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## 0743232012 Specifications

ManufacturerMolex, LLCCategoryConnectors, InterconnectsBackage-SeriesGoncorss? 74323Connector TypeDVI-ANumber of Contacts17GenderPlugSperifications-Mounting TypeFree Hanging (In-Line)Mounting FeatureSolderFeatures-Romes Protection-Operating Temperature-Operating Temperature1Current Rating3 per ContactVoltage - Rated40VACMaing Cycles100		
CategoryConnectors, InterconnectsUSB, DVI, HDMI ConnectorsPackage-SeriesMicroCross? 74323Connector TypeDVI-ANumber of ContactsI7GenderPlugSpecifications-Mounting TypeFree Hanging (In-Line)Mounting FeatureSolderFeatures-Ingress Protection-Operating Temperature-Ourent Rating3A per ContactVoltage - Rated40VACMaing Cycles100ShieldingShieldenShieldingShielden	Manufacturer Part Number	0743232012
USB, DVI, HDMI ConnectorsPackage-SeriesMicroCross? 74323Connector TypeDVI-ANumber of Contacts17GenderPlugSpecifications-Mounting TypeFree Hanging (In-Line)Mounting FeatureFlangeTerminationSolderFeatures-Operating Temperature-20°C ~ 85°CNumber of Ports1Current Rating3A per ContactVoltage - Rated100Shielding500Shielding<	Manufacturer	Molex, LLC
Package-SeriesMicroCross? 74323Connector TypeDVI-ANumber of Contacts17GenderPlugSpecifications-Mounting TypeFree Hanging (In-Line)Mounting FeatureSolderTerminationSolderFeatures-Number of Ports20°C ~ 85°CNumber of Ports3A per ContactVoltage - Rated40VACMaing Cycles100ShieldingShieldedShieldingShieldedShieldingShielded	Category	Connectors, Interconnects
SeriesMicroCross? 74323Connector TypeDVI-ANumber of Contacts17GenderPlugSpecifications-Mounting TypeFree Hanging (In-Line)Mounting FeatureFlangeTerminationSolderFeatures-Operating Temperature-Operating Temperature20°C ~ 85°CNumber of Ports1Current Rating3A per ContactVoltage - Rated40VACMaing Cycles100ShieldingShielded		USB, DVI, HDMI Connectors
Connector TypeDVI-ANumber of Contacts17GenderPlugSpecifications-Mounting TypeFree Hanging (In-Line)Mounting FeatureFlangeTerminationSolderFeatures-Operating Temperature-Operating Temperature1Number of Ports1Current RatingSAper ContactVoltage - Rated40VACMaing Cycles100ShieldingShielded	Package	-
A17Number of Contacts17GenderPlugSpecifications-Mounting TypeFree Hanging (In-Line)Mounting FeatureFlangeTerminationSolderFeatures-Ingress Protection-Operating Temperature-20°C ~ 85°CNumber of Ports1Current Rating3A per ContactVoltage - Rated100Maing CyclesShieldedShieldingShielded	Series	MicroCross? 74323
GenderPlugSpecifications-Mounting TypeFree Hanging (In-Line)Mounting FeatureFlangeTerminationSolderFeatures-Ingress Protection-Operating Temperature-20°C ~ 85°CNumber of Ports1Current Rating3A per ContactVoltage - Rated40VACMating Cycles100ShieldingShielded	Connector Type	DVI-A
Specifications-Mounting TypeFree Hanging (In-Line)Mounting FeatureFlangeTerminationSolderFeatures-Ingress Protection-Operating Temperature-20°C ~ 85°CNumber of Ports1Current Rating3A per ContactVoltage - Rated40VACMating Cycles100ShieldingShielded	Number of Contacts	17
Mounting TypeFree Hanging (In-Line)Mounting FeatureFlangeTerminationSolderFeatures-Ingress Protection-Operating Temperature-20°C ~ 85°CNumber of Ports1Current Rating3A per ContactVoltage - Rated100Mating CyclesShielded	Gender	Plug
Mounting FeatureFlangeTerminationSolderFeatures-Ingress Protection-Operating Temperature-20°C ~ 85°CNumber of Ports1Current Rating3A per ContactVoltage - Rated40VACMating Cycles100ShieldingShielded	Specifications	-
TerminationSolderFeatures-Ingress Protection-Operating Temperature-20°C ~ 85°CNumber of Ports1Current Rating3A per ContactVoltage - Rated40VACMating Cycles100ShieldingShielded	Mounting Type	Free Hanging (In-Line)
Features-Ingress Protection-Operating Temperature-20°C ~ 85°CNumber of Ports1Current Rating3A per ContactVoltage - Rated40VACMating Cycles100ShieldingShielded	Mounting Feature	Flange
Ingress Protection-Operating Temperature-20°C ~ 85°CNumber of Ports1Current Rating3A per ContactVoltage - Rated40VACMating Cycles100ShieldingShielded	Termination	Solder
Operating Temperature-20°C ~ 85°CNumber of Ports1Current Rating3A per ContactVoltage - Rated40VACMating Cycles100ShieldingShielded	Features	-
Number of Ports1Current Rating3A per ContactVoltage - Rated40VACMating Cycles100ShieldingShielded	Ingress Protection	-
Current Rating3A per ContactVoltage - Rated40VACMating Cycles100ShieldingShielded	Operating Temperature	-20°C ~ 85°C
Voltage - Rated40VACMating Cycles100ShieldingShielded	Number of Ports	1
Mating Cycles100ShieldingShielded	Current Rating	3A per Contact
Shielded Shielded	Voltage - Rated	40VAC
	Mating Cycles	100
Report errors?	Shielding	Shielded
		Report errors?

#### 0743232012 Guarantees



#### Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### 

If you have any question about 0743232012, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com