

09-62-3063 Information

Part Number 09-62-3063

ManufacturerMolex Connector CorporationCategoryConnectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

Description CONN RECEPT 6POS .156 VERT PCB

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









09-62-3063 Specifications

Manufacturer Part Number09-62-3063ManufacturerMolex Connector CorporationCategoryConnectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesKK? 2145Connector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions6Number of Positions LoadedAllPitch - Mating0.156" (3.96mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypeLocking RampContact Finish - MatingGoldContact Finish Thickness - Mating15μin (0.38μm)Insulation ColorWhite		
Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package Series KK? 2145 Connector Type Receptacle Contact Type Female Socket Style Board to Board or Cable Number of Positions 6 Number of Positions Loaded All Pitch - Mating 0.156" (3.96mm) Number of Rows 1 Row Spacing - Mating Type Through Hole Termination Fastening Type Locking Ramp Contact Finish - Mating Gold Contact Finish Thickness - Mating 15µin (0.38µm)	Manufacturer Part Number	09-62-3063
Rectangular Connectors - Headers, Receptacles, Female Sockets Package Series KK? 2145 Connector Type Receptacle Contact Type Female Socket Style Board to Board or Cable Number of Positions 6 Number of Positions Loaded All Pitch - Mating 0.156" (3.96mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Fastening Type Locking Ramp Contact Finish - Mating Gold Contact Finish Thickness - Mating 15µin (0.38µm)	Manufacturer	Molex Connector Corporation
Package-SeriesKK? 2145Connector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions6Number of Positions LoadedAllPitch - Mating0.156" (3.96mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypeLocking RampContact Finish - MatingGoldContact Finish Thickness - Mating15μin (0.38μm)	Category	Connectors, Interconnects
Series KK? 2145 Connector Type Receptacle Contact Type Female Socket Style Board to Board or Cable Number of Positions 6 Number of Positions Loaded All Pitch - Mating 0.156" (3.96mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Locking Ramp Contact Finish - Mating Gold Contact Finish Thickness - Mating 15µin (0.38µm)		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector Type Receptacle Contact Type Female Socket Style Board to Board or Cable Number of Positions 6 Number of Positions Loaded All Pitch - Mating 0.156" (3.96mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Locking Ramp Contact Finish - Mating Gold Contact Finish Thickness - Mating 15µin (0.38µm)	Package	-
Contact Type Female Socket Style Board to Board or Cable Number of Positions 6 Number of Positions Loaded All Pitch - Mating 0.156" (3.96mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Locking Ramp Contact Finish - Mating Gold Contact Finish Thickness - Mating 15µin (0.38µm)	Series	KK? 2145
Style Board to Board or Cable Number of Positions 6 Number of Positions Loaded All Pitch - Mating 0.156" (3.96mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Locking Ramp Contact Finish - Mating Gold Contact Finish Thickness - Mating 15µin (0.38µm)	Connector Type	Receptacle
Number of Positions 6 Number of Positions Loaded All Pitch - Mating 0.156" (3.96mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Locking Ramp Contact Finish - Mating Gold Contact Finish Thickness - Mating 15μin (0.38μm)	Contact Type	Female Socket
Number of Positions Loaded All Pitch - Mating 0.156" (3.96mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Locking Ramp Contact Finish - Mating Gold Contact Finish Thickness - Mating 15μin (0.38μm)	Style	Board to Board or Cable
Pitch - Mating0.156" (3.96mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypeLocking RampContact Finish - MatingGoldContact Finish Thickness - Mating15μin (0.38μm)	Number of Positions	6
Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypeLocking RampContact Finish - MatingGoldContact Finish Thickness - Mating15μin (0.38μm)	Number of Positions Loaded	All
Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypeLocking RampContact Finish - MatingGoldContact Finish Thickness - Mating15μin (0.38μm)	Pitch - Mating	0.156" (3.96mm)
Mounting TypeThrough HoleTerminationSolderFastening TypeLocking RampContact Finish - MatingGoldContact Finish Thickness - Mating15μin (0.38μm)	Number of Rows	1
Termination Solder Fastening Type Locking Ramp Contact Finish - Mating Gold Contact Finish Thickness - Mating 15μin (0.38μm)	Row Spacing - Mating	-
Fastening Type Locking Ramp Contact Finish - Mating Gold Contact Finish Thickness - Mating 15µin (0.38µm)	Mounting Type	Through Hole
Contact Finish - Mating Gold Contact Finish Thickness - Mating 15μin (0.38μm)	Termination	Solder
Contact Finish Thickness - Mating 15µin (0.38µm)	Fastening Type	Locking Ramp
	Contact Finish - Mating	Gold
Insulation Color White	Contact Finish Thickness - Mating	15μin (0.38μm)
	Insulation Color	White
Insulation Height 0.449" (11.40mm)	Insulation Height	0.449" (11.40mm)
Contact Length - Post 0.120" (3.05mm)	Contact Length - Post	0.120" (3.05mm)
Operating Temperature $-40^{\circ}\text{C} \sim 80^{\circ}\text{C}$	Operating Temperature	-40°C ~ 80°C
Material Flammability Rating UL94 V-2	Material Flammability Rating	UL94 V-2

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	Board Hooks
	Report errors?

09-62-3063 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

09-62-3063 Payment Methods



















09-62-3063 Shipping Methods













If you have any question about 09-62-3063, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com