

0CCK160.V Information

Heisener.com

Part NumberOCCK160.VManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 160A 125VDC CYLINDR

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0CCK160.V Specifications

Manufacturer Part Number OCCK 160.V Manufacturer Littelfuse Inc. Category Circuit Protection Backage Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? CCK Fuse Type Cartridge Current Rating 160A Voltage Rating - AC - Voltage Rating - DC 125V Response Time Slow Applications Lift Trucks Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 4.362" L (25.40mm x 110.80mm)		
CategoryCircuit ProtectionElectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? CCKFuse TypeCartridgeCurrent Rating160AVoltage Rating - AC-Voltage Rating - DC125VResponse TimeSlowApplicationsLift TrucksFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 4.362" L (25.40mm x 110.80mm)	Manufacturer Part Number	0CCK160.V
Backage Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? CCK Fuse Type Cartridge Current Rating 160A Voltage Rating - AC - Voltage Rating - DC 125V Response Time Slow Applications Lift Trucks Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 4.362" L (25.40mm x 110.80mm)	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? CCKFuse TypeCartridgeCurrent Rating160AVoltage Rating - AC-Voltage Rating - DC125VResponse TimeSlowApplicationsLift TrucksFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 4.362" L (25.40mm x 110.80mm)	Category	Circuit Protection
SeriesPOWR-GARD? CCKFuse TypeCartridgeCurrent Rating160AVoltage Rating - AC-Voltage Rating - DC125VResponse TimeSlowApplicationsLift TrucksFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 4.362" L (25.40mm x 110.80mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 160A Voltage Rating - AC Voltage Rating - DC 125V Response Time Slow Applications Lift Trucks Features - Class - Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Canaccians Lift Trucks - Cartridge Lift A Approvals - Cultage Cultage Approvals - Cultage Approvals Approvals Approvals - Cultage Approvals Approv	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating 160A Voltage Rating - AC - Voltage Rating - DC 125V Response Time Slow Applications Lift Trucks Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 4.362" L (25.40mm x 110.80mm)	Series	POWR-GARD? CCK
Voltage Rating - AC Voltage Rating - DC 125V Response Time Slow Applications Lift Trucks Features - Class - Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 1.000" Dia x 4.362" L (25.40mm x 110.80mm)	Fuse Type	Cartridge
Voltage Rating - DC Response Time Slow Applications Lift Trucks Features - Class - Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 1.000" Dia x 4.362" L (25.40mm x 110.80mm)	Current Rating	160A
Response Time Applications Lift Trucks Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Slow Lift Trucks - Lift Trucks - Bolt Mount - Class - Cylindrical, Blade Terminal (Bolt) 1.000" Dia x 4.362" L (25.40mm x 110.80mm)	Voltage Rating - AC	-
Applications Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Lift Trucks - Character Nounting Tyue Class Cylindrical, Blade Terminal (Bolt) 1.000" Dia x 4.362" L (25.40mm x 110.80mm)	Voltage Rating - DC	125V
Features - Class - Cla	Response Time	Slow
Class - Approvals - Coperating Temperature - Coperating Capacity @ Rated Voltage 10kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 4.362" L (25.40mm x 110.80mm)	Applications	Lift Trucks
Approvals Operating Temperature	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 10kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 4.362" L (25.40mm x 110.80mm)	Class	-
Breaking Capacity @ Rated Voltage 10kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 4.362" L (25.40mm x 110.80mm)	Approvals	-
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 4.362" L (25.40mm x 110.80mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 4.362" L (25.40mm x 110.80mm)	Breaking Capacity @ Rated Voltage	10kA
Size / Dimension 1.000" Dia x 4.362" L (25.40mm x 110.80mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	1.000" Dia x 4.362" L (25.40mm x 110.80mm)
		Report errors?

0CCK160.V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0CCK160.V Payment Methods



















0CCK160.V Shipping Methods













If you have any question about 0CCK160.V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com