

### **0CCL040.V Information**

Heisener.com

Part Number 0CCL040.V

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE CRTRDGE 40A 125VDC CYLINDR

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **0CCL040.V Specifications**

Manufacturer Part Number         OCCL 040 .V           Manufacturer         Littelfuse Inc.           Category         Circuit Protection           Electrical, Specialty Fuses           Package         Cylindrical, Blade Terminal (Bolt)           Series         POWR-GARD? CCL           Fuse Type         Cartridge           Current Rating         40A           Voltage Rating - AC         -           Voltage Rating - DC         125V           Response Time         Slow           Applications         Lift Trucks           Features         -           Class         -           Approvals         -           Operating Temperature         -           Breaking Capacity @ Rated Voltage         10kA           Mounting Type         Bolt Mount           Package / Case         Cylindrical, Blade Terminal (Bolt)           Size / Dimension         0.750" Dia x 3.629" L (19.05mm x 92.18mm)		
CategoryCircuit ProtectionPackageCylindrical, Specialty FusesPowr-GARD? CCLPowr-GARD? CCLFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC-Voltage Rating - DC125VResponse TimeSlowApplicationsLift TrucksFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.750" Dia x 3.629" L (19.05mm x 92.18mm)	Manufacturer Part Number	0CCL040.V
Beckage Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? CCL Fuse Type Cartridge Current Rating 40A Voltage Rating - AC - Voltage Rating - DC 125V Response Time Slow Applications Lift Trucks Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1000 CCL  Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.750" Dia x 3.629" L (19.05mm x 92.18mm)	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD? CCLFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC-Voltage Rating - DC125VResponse TimeSlowApplicationsLift TrucksFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.750" Dia x 3.629" L (19.05mm x 92.18mm)	Category	Circuit Protection
SeriesPOWR-GARD? CCLFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC-Voltage Rating - DC125VResponse TimeSlowApplicationsLift TrucksFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.750" Dia x 3.629" L (19.05mm x 92.18mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating40AVoltage Rating - AC-Voltage Rating - DC125VResponse TimeSlowApplicationsLift TrucksFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.750" Dia x 3.629" L (19.05mm x 92.18mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating  Voltage Rating - AC  Voltage Rating - DC  Response Time  Slow  Applications  Lift Trucks  Features  - Class  - Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Size / Dimension  40A  125V  - 125V  Response Time  Slow  Lift Trucks  - 106  Lift Trucks  - 106  Lift Trucks  - 106  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  107  108  109  109  109  109  109  109  109	Series	POWR-GARD? CCL
Voltage Rating - AC  Voltage Rating - DC  Response Time  Slow  Applications  Lift Trucks  Features  - Class  - Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  - Class  - Class  C	Fuse Type	Cartridge
Voltage Rating - DC  Response Time  Slow  Applications  Lift Trucks  Features  - Class  - Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  125V  125V  10kA	Current Rating	40A
Response Time  Applications  Lift Trucks  Features  - Class  - Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  Slow  Lift Trucks  - Bolt Mount  Class  - Cylindrical, Blade Terminal (Bolt)  0.750" Dia x 3.629" L (19.05mm x 92.18mm)	Voltage Rating - AC	-
Applications  Features  - Class  - Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  Lift Trucks  - Lift Trucks  Lift Trucks  - Cylindrical, Blade Terminal (Bolt)  0.750" Dia x 3.629" L (19.05mm x 92.18mm)	Voltage Rating - DC	125V
Features - Class - Class - Composition - Class - Composition - Compositi	Response Time	Slow
Class - Approvals - Class - Coperating Temperature - Streaking Capacity @ Rated Voltage 10kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.750" Dia x 3.629" L (19.05mm x 92.18mm)	Applications	Lift Trucks
Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 10kA  Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.750" Dia x 3.629" L (19.05mm x 92.18mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  10kA  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  0.750" Dia x 3.629" L (19.05mm x 92.18mm)	Class	-
Breaking Capacity @ Rated Voltage 10kA  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 0.750" Dia x 3.629" L (19.05mm x 92.18mm)	Approvals	-
Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  0.750" Dia x 3.629" L (19.05mm x 92.18mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.750" Dia x 3.629" L (19.05mm x 92.18mm)	Breaking Capacity @ Rated Voltage	10kA
Size / Dimension 0.750" Dia x 3.629" L (19.05mm x 92.18mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	0.750" Dia x 3.629" L (19.05mm x 92.18mm)
		Report errors?

### **0CCL040.V Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **0CCL040.V Payment Methods**



















### **0CCL040.V Shipping Methods**













If you have any question about OCCL040.V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com