



## **0FLM030.T Information**



For Reference Only

Part Number 0FLM030.T

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE CARTRIDGE 30A 250VAC/125VDC

Package 5AG, 10mm x 38.1mm

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **0FLM030.T Specifications**

Manufacturer         OFLM030.T           Manufacturer         Littelfuse Inc.           Category         Circuit Protection           Electrical, Specialty Fuses           Package         5AG, 10mm x 38.1mm           Series         FLM           Fuse Type         Cartridge           Current Rating         30A           Voltage Rating - AC         250V           Voltage Rating - DC         125V           Response Time         Slow           Applications         Motor Protection           Features         -           Class         -           Approvals         CSA, PSE, QPL, UL           Operating Temperature         -           Breaking Capacity @ Rated Voltage         10kA           Mounting Type         Holder           Package / Case         5AG, 10mm x 38.1mm           Size / Dimension         0.406" Dia x 1.500" L (10.31mm x 38.10mm)		
CategoryCircuit Protection Electrical, Specialty FusesPackage5AG, 10mm x 38.1mmSeriesFLMFuse TypeCartridgeCurrent Rating30AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsMotor ProtectionFeatures-Class-ApprovalsCSA, PSE, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Manufacturer Part Number	0FLM030.T
Flectrical, Specialty Fuses           Package         5AG, 10mm x 38.1mm           Series         FLM           Fuse Type         Cartridge           Current Rating         30A           Voltage Rating - AC         250V           Voltage Rating - DC         125V           Response Time         Slow           Applications         Motor Protection           Features         -           Class         -           Approvals         CSA, PSE, QPL, UL           Operating Temperature         -           Breaking Capacity @ Rated Voltage         10kA           Mounting Type         Holder           Package / Case         5AG, 10mm x 38.1mm           Size / Dimension         0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Manufacturer	Littelfuse Inc.
Package         5AG, 10mm x 38.1mm           Series         FLM           Fuse Type         Cartridge           Current Rating         30A           Voltage Rating - AC         250V           Voltage Rating - DC         125V           Response Time         Slow           Applications         Motor Protection           Features         -           Class         -           Approvals         CSA, PSE, QPL, UL           Operating Temperature         -           Breaking Capacity @ Rated Voltage         10kA           Mounting Type         Holder           Package / Case         5AG, 10mm x 38.1mm           Size / Dimension         0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Category	Circuit Protection
Series         FLM           Fuse Type         Cartridge           Current Rating         30A           Voltage Rating - AC         250V           Voltage Rating - DC         125V           Response Time         Slow           Applications         Motor Protection           Features         -           Class         -           Approvals         CSA, PSE, QPL, UL           Operating Temperature         -           Breaking Capacity @ Rated Voltage         10kA           Mounting Type         Holder           Package / Case         5AG, 10mm x 38.1mm           Size / Dimension         0.406" Dia x 1.500" L (10.31mm x 38.10mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating30AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsMotor ProtectionFeatures-Class-ApprovalsCSA, PSE, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Package	5AG, 10mm x 38.1mm
Current Rating Voltage Rating - AC 250V  Voltage Rating - DC 125V  Response Time Slow Applications Motor Protection  Features - Class - Approvals CSA, PSE, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension  30A 30A 30A 30A 30A 30A 30A 30A 30A 30	Series	FLM
Voltage Rating - AC  Voltage Rating - DC  125V  Response Time  Slow  Applications  Motor Protection  Features  - Class  - Approvals  CSA, PSE, QPL, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  250V  250V  250V  260V  108A  Motor Protection  CSA, PSE, QPL  40L  40L  40L  40L  40L  40L  40L  4	Fuse Type	Cartridge
Voltage Rating - DC  Response Time  Slow  Applications  Motor Protection  Features  - Class  - Approvals  CSA, PSE, QPL, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  125V  125V  106A  106A  107  108A  1	Current Rating	30A
Response Time  Applications  Motor Protection  Features  - Class  - Approvals  CSA, PSE, QPL, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  5AG, 10mm x 38.1mm  Size / Dimension  Slow  Motor Protection  -  Hotor Protection  -  Slow  Motor Protection  -  CSA, PSE, QPL, UL  -  0,406" Dia x 1.500" L (10.31mm x 38.10mm)	Voltage Rating - AC	250V
Applications Motor Protection  Features - Class - Approvals CSA, PSE, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Voltage Rating - DC	125V
Features - Class - Class - CSA, PSE, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Response Time	Slow
Class - Approvals CSA, PSE, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Applications	Motor Protection
Approvals  CSA, PSE, QPL, UL  Operating Temperature  - Breaking Capacity @ Rated Voltage  10kA  Mounting Type  Holder  Package / Case  5AG, 10mm x 38.1mm  Size / Dimension  0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  10kA  Mounting Type  Holder  Package / Case  5AG, 10mm x 38.1mm  Size / Dimension  0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Class	-
Breaking Capacity @ Rated Voltage 10kA  Mounting Type Holder  Package / Case 5AG, 10mm x 38.1mm  Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Approvals	CSA, PSE, QPL, UL
Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Operating Temperature	-
Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Breaking Capacity @ Rated Voltage	10kA
Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Mounting Type	Holder
	Package / Case	5AG, 10mm x 38.1mm
Report errors?	Size / Dimension	0.406" Dia x 1.500" L (10.31mm x 38.10mm)
Tepott offold.		Report errors?

### **0FLM030.T Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **0FLM030.T Payment Methods**





















## **0FLM030.T Shipping Methods**













If you have any question about 0FLM030.T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com