

0KLK03.5T Information



For Reference Only

Part Number 0KLK03.5T

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 3.5A 600VAC/500VDC

Package 5AG, 10mm x 38.1mm

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0KLK03.5T Specifications

Manufacturer Part Number OKLK03.5T Manufacturer Littelfuse Inc. Category Circuit Protection Electrical, Specialty Fuses Package 5AG, 10mm x 38.1mm Series POWR-GARD? KLK Fuse Type Cartridge Current Rating 3.5A Voltage Rating - AC 600V Voltage Rating - DC 500V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 50kA DC Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)		
Category Circuit Protection Electrical, Specialty Fuses Package 5AG, 10mm x 38.1mm Series POWR-GARD? KLK Fuse Type Cartridge Current Rating 3.5A Voltage Rating - AC 600V Voltage Rating - DC 500V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 50kA DC Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Manufacturer Part Number	0KLK03.5T
Package 5AG, 10mm x 38.1mm Series POWR-GARD? KLK Fuse Type Cartridge Current Rating 3.5A Voltage Rating - AC 600V Voltage Rating - DC 500V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 50kA DC Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Manufacturer	Littelfuse Inc.
Package 5AG, 10mm x 38.1mm Series POWR-GARD? KLK Fuse Type Cartridge Current Rating 3.5A Voltage Rating - AC 600V Voltage Rating - DC 500V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 50kA DC Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Category	Circuit Protection
SeriesPOWR-GARD? KLKFuse TypeCartridgeCurrent Rating3.5AVoltage Rating - AC600VVoltage Rating - DC500VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, QPL, ULOperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 50kA DCMounting TypeHolderPackage / Case5AG, 10mm x 38.1mmSize / Dimension0.406" Dia x 1.500" L (10.31mm x 38.10mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 3.5A Voltage Rating - AC 600V Voltage Rating - DC 500V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Cartridge 600V Conv Eartridge 100V Eactor 100V Eact	Package	5AG, 10mm x 38.1mm
Current Rating 3.5A Voltage Rating - AC 600V Voltage Rating - DC 500V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 3.5A 3.5A 3.5A 3.5A 600V CEQV Fast Fast Electrical, Industrial - Lectrical, Industrial - Lectrical, Industrial - Lectrical, Industrial Features - Lectrical, Industrial Features - Lectrical, Industrial Features - Lectrical, Industrial Features - Lectrical, Industrial - Lectrical, Industrial Features - Lectrical, Industrial	Series	POWR-GARD? KLK
Voltage Rating - AC Voltage Rating - DC 500V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 600V 60	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CE, CSA, QPL, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 500V Fast Fast Fast Fast Fast Fast Fast Fas	Current Rating	3.5A
Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension Fast Electrical, Industrial - CE, CSA, QPL, UL - CE, CSA, QPL, UL - Holder - Holder - Holder - SAG, 10mm x 38.1mm 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Voltage Rating - AC	600V
Applications Electrical, Industrial Features - Class - Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 50kA DC Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Voltage Rating - DC	500V
Features - Class - Class - CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 50kA DC Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Response Time	Fast
Class - Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 50kA DC Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Applications	Electrical, Industrial
Approvals CE, CSA, QPL, UL Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 50kA DC Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 100kA AC, 50kA DC Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Class	-
Breaking Capacity @ Rated Voltage 100kA AC, 50kA DC Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Approvals	CE, CSA, QPL, UL
Mounting Type Holder Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Operating Temperature	-
Package / Case 5AG, 10mm x 38.1mm Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Breaking Capacity @ Rated Voltage	100kA AC, 50kA DC
Size / Dimension 0.406" Dia x 1.500" L (10.31mm x 38.10mm)	Mounting Type	Holder
	Package / Case	5AG, 10mm x 38.1mm
Report errors?	Size / Dimension	0.406" Dia x 1.500" L (10.31mm x 38.10mm)
		Report errors?

0KLK03.5T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0KLK03.5T Payment Methods





















0KLK03.5T Shipping Methods













If you have any question about 0KLK03.5T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com