

### **0LKS125.V Information**

heisener.com

Part Number0LKS125.VManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

**Description** FUSE LINK 125A 600VAC CYLINDR

Package Cylindrical, Blade Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **0LKS125.V Specifications**

Manufacturer Part Number         OLKS125.V           Manufacturer         Littelfuse Inc.           Category         Circuit Protection           Electrical, Specialty Fuses           Package         Cylindrical, Blade Terminals           Series         POWR-GARD? LKS           Fuse Type         Fuse Link           Current Rating         125A           Voltage Rating - AC         600V           Voltage Rating - DC         -           Response Time         Fast           Applications         Electrical, Industrial           Features         -           Class         H           Approvals         CE, CSA, UL           Operating Temperature         -           Breaking Capacity @ Rated Voltage         10kA           Mounting Type         Holder           Package / Case         Cylindrical, Blade Terminals           Size / Dimension         1.843" Dia x 6.878" L (46.80mm x 174.70mm)		
CategoryCircuit ProtectionBectrical, Specialty FusesPackageCylindrical, Blade TerminalsSeriesPOWR-GARD? LKSFuse TypeFuse LinkCurrent Rating125AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassHApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.843" Dia x 6.878" L (46.80mm x 174.70mm)	Manufacturer Part Number	0LKS125.V
Electrical, Specialty Fuses  Cylindrical, Blade Terminals  Series  POWR-GARD? LKS  Fuse Type  Fuse Link  Current Rating  125A  Voltage Rating - AC  600V  Voltage Rating - DC  Response Time  Fast  Applications  Electrical, Industrial  Features  - Class  H  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Cylindrical, Blade Terminals  Size / Dimension  Electrical, Fuse Timel  Cylindrical, Blade Terminals  Size / Dimension	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade TerminalsSeriesPOWR-GARD? LKSFuse TypeFuse LinkCurrent Rating125AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassHApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.843" Dia x 6.878" L (46.80mm x 174.70mm)	Category	Circuit Protection
SeriesPOWR-GARD? LKSFuse TypeFuse LinkCurrent Rating125AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassHApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.843" Dia x 6.878" L (46.80mm x 174.70mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 125A Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class H Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Fuse Link Fuse Link Fuse Link Fuse Link Fuse Link Fuse Link Foot  600V - CE, CSA  Fuse Fuse Fuse Fuse Fuse Fuse Fuse Fus	Package	Cylindrical, Blade Terminals
Current Rating 125A Voltage Rating - AC 600V Voltage Rating - DC	Series	POWR-GARD? LKS
Voltage Rating - AC  Voltage Rating - DC  Response Time  Fast  Applications  Electrical, Industrial  Features  - Class  H  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Holder  Package / Case  Size / Dimension  600V  - CR  600V  - 600V  - 600V  - 600V  Fast  Fast  Fast  CE, CSA, UL  CE, CSA, UL  CE, CSA, UL  10kA  Mounting Type  Holder  Cylindrical, Blade Terminals  1.843" Dia x 6.878" L (46.80mm x 174.70mm)	Fuse Type	Fuse Link
Voltage Rating - DC  Response Time Fast  Applications Electrical, Industrial  Features - Class H  Approvals CE, CSA, UL  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder  Package / Case Size / Dimension  - Size / Dimension  Fast CE, CSA, UL  CE, CSA,	Current Rating	125A
Response Time Applications Electrical, Industrial  Features - Class H Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals 1.843" Dia x 6.878" L (46.80mm x 174.70mm)	Voltage Rating - AC	600V
Applications Electrical, Industrial  Features - Class H  Approvals CE, CSA, UL  Operating Temperature - Breaking Capacity @ Rated Voltage 10kA  Mounting Type Holder  Package / Case Cylindrical, Blade Terminals  Size / Dimension 1.843" Dia x 6.878" L (46.80mm x 174.70mm)	Voltage Rating - DC	-
Features - Class H  Approvals CE, CSA, UL  Operating Temperature - I0kA  Breaking Capacity @ Rated Voltage Holder  Mounting Type Holder  Package / Case Cylindrical, Blade Terminals  Size / Dimension 1.843" Dia x 6.878" L (46.80mm x 174.70mm)	Response Time	Fast
Class H Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 10kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.843" Dia x 6.878" L (46.80mm x 174.70mm)	Applications	Electrical, Industrial
Approvals  CE, CSA, UL  Operating Temperature  - Breaking Capacity @ Rated Voltage  10kA  Mounting Type  Holder  Package / Case  Cylindrical, Blade Terminals  Size / Dimension  1.843" Dia x 6.878" L (46.80mm x 174.70mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  10kA  Mounting Type  Holder  Package / Case  Cylindrical, Blade Terminals  Size / Dimension  1.843" Dia x 6.878" L (46.80mm x 174.70mm)	Class	Н
Breaking Capacity @ Rated Voltage 10kA  Mounting Type Holder  Package / Case Cylindrical, Blade Terminals  Size / Dimension 1.843" Dia x 6.878" L (46.80mm x 174.70mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.843" Dia x 6.878" L (46.80mm x 174.70mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminals Size / Dimension 1.843" Dia x 6.878" L (46.80mm x 174.70mm)	Breaking Capacity @ Rated Voltage	10kA
Size / Dimension 1.843" Dia x 6.878" L (46.80mm x 174.70mm)	Mounting Type	Holder
	Package / Case	Cylindrical, Blade Terminals
Report errors?	Size / Dimension	1.843" Dia x 6.878" L (46.80mm x 174.70mm)
		Report errors?

#### **0LKS125.V Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **0LKS125.V Payment Methods**



















### **0LKS125.V Shipping Methods**













If you have any question about 0LKS125.V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com