

# 0LMF1.25H

# **0LMF1.25H Information**



Part Number	0LMF1.25H	
Manufacturer	Littelfuse Inc.	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE CRTRDGE 1.25A 300VAC NONSTD	
Package	Cartridge, Non-Standard	
For the pricing/inventory/lead time, please co us Website: https://www.heisener.com E-mail: salesdept@heisener.com		



Request a Quote

For Reference Only

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **0LMF1.25H Specifications**

ManufacturerLittelfuse Inc.CategoryCircuit ProtectionBeckageCattridge, Non-StandardPackageCartridge, Non-StandardSeriesPOWR-GARD? LMFFuse TypeCartridgeCurrent Rating1.25AVoltage Rating - AC300VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)		
CategoryCircuit ProtectionBeckageElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? LMFFuse TypeCartridgeCurrent Rating1.25AVoltage Rating - AC300VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Manufacturer Part Number	0LMF1.25H
Current RatingElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? LMFFuse TypeCartridgeCurrent Rating1.25AVoltage Rating - AC300VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating TemperatureIokAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD? LMFFuse TypeCartridgeCurrent Rating1.25AVoltage Rating - AC300VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Category	Circuit Protection
SeriesPOWR-GARD? LMFFuse TypeCartridgeCurrent Rating1.25AVoltage Rating - AC300VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating Temperature10kABreaking Capacity @ Rated VoltageHolderAponting TypeGartridge, Non-StandardSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeFuse TypeCartridgeCurrent Rating1.25AVoltage Rating - AC300VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Package	Cartridge, Non-Standard
Current Rating1.25ACurrent Rating - AC300VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Series	POWR-GARD? LMF
Voltage Rating - AC300VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Fuse Type	Cartridge
Voltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Current Rating	1.25A
Response TimeSlowApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Voltage Rating - AC	300V
ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Voltage Rating - DC	-
Features-Features-Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Response Time	Slow
Class-ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Applications	Electrical, Industrial
ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Features	-
A-Operating Temperature-Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Class	-
Breaking Capacity @ Rated Voltage10kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Approvals	CE, CSA, UL
Mounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Operating Temperature	-
Package / CaseCartridge, Non-StandardSize / Dimension0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Breaking Capacity @ Rated Voltage	10kA
Size / Dimension 0.610" Dia x 1.820" L (15.49mm x 46.23mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.610" Dia x 1.820" L (15.49mm x 46.23mm)
		Report errors?

#### **0LMF1.25H Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **0LMF1.25H Payment Methods**



### **0LMF1.25H Shipping Methods**



If you have any question about 0LMF1.25H, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com