

## **0NLN040.T**

## **0NLN040.T Information**

		Part Number	0NLN040.T
	Heisener.com	Manufacturer	Littelfuse Inc.
		Category	Circuit Protection Electrical, Specialty Fuses
		Description	FUSE CARTRIDGE 40A 250VAC/VDC
		Package	Cartridge, Non-Standard
			For the pricing/inventory/lead time, please contact
			us
	For Reference Only		Website: https://www.heisener.com
			E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **0NLN040.T Specifications**

ManufacturerLittelfuse Inc.CategoryCircuit ProtectionElectrical, Specialty FusesPackageCartridge, Non-StandardPackagePOWR-GARD? NLNSteriesPOWR-GARD? NLNFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC250VVoltage Rating - DC250VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature50kA AC, 20kA DCBreaking Capacity @ Rated VoltageSokA AC, 20kA DCPackage / CaseCartridge, Non-Standard		
CategoryCircuit ProtectionElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD? NLNFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC250VVoltage Rating - DC250VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature50kA AC, 20kA DCBreaking Capacity @ Rated VoltageSick AC, 20kA DCPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Manufacturer Part Number	0NLN040.T
Bit of the second sec	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD? NLNFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC250VVoltage Rating - DC250VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Category	Circuit Protection
SeriesPOWR-GARD? NLNFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC250VVoltage Rating - DC250VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.000" L (20.60mm x 76.20mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating40AVoltage Rating - AC250VVoltage Rating - DC250VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kA AC, 20kA DCPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Package	Cartridge, Non-Standard
Current Rating40ACurrent Rating - AC250VVoltage Rating - DC250VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Series	POWR-GARD? NLN
Voltage Rating - AC250VVoltage Rating - DC250VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Fuse Type	Cartridge
Voltage Rating - DC250VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Current Rating	40A
Response TimeFastApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Voltage Rating - AC	250V
ApplicationsElectrical, IndustrialApplications-Features-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Voltage Rating - DC	250V
Fratures-Features-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Response Time	Fast
ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Applications	Electrical, Industrial
ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Features	-
Operating Temperature-Breaking Capacity @ Rated Voltage50kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Class	K5
Breaking Capacity @ Rated Voltage50kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Approvals	CE, CSA, UL
Mounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Operating Temperature	-
Package / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Breaking Capacity @ Rated Voltage	50kA AC, 20kA DC
Size / Dimension 0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.811" Dia x 3.000" L (20.60mm x 76.20mm)
		Report erro

#### **0NLN040.T Guarantees**



#### Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

# 0NLN040.T Payment Methods



### **0NLN040.T Shipping Methods**



If you have any question about 0NLN040.T, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com