



### **0NLN040.T Information**

Man Categ

Part NumberONLN040.TManufacturerLittelfuse Inc.CategoryCircuit Protection

Electrical, Specialty Fuses

**Description** FUSE CARTRIDGE 40A 250VAC/VDC

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **0NLN040.T Specifications**

Manufacturer Part NumberONLN040.TManufacturerLittelfuse Inc.CategoryCircuit ProtectionPackageCartridge, Non-StandardSeriesPOWR-GARD? NLNFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC250VVoltage Rating - DC250VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.000" L (20.60mm x 76.20mm)		
Category  Circuit Protection  Electrical, Specialty Fuses  Package  Cartridge, Non-Standard  Series  POWR-GARD? NLN  Fuse Type  Cartridge  Current Rating  40A  Voltage Rating - AC  250V  Voltage Rating - DC  250V  Response Time  Fast  Applications  Electrical, Industrial  Features  - Class  K5  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  Circuit Protection  Electrical, Specialty Fuses  Electrical, Industrial  Features  - CE, CSA, UL  Operating Temperature  Folka AC, 20kA DC  Holder  Cartridge, Non-Standard  Size / Dimension  O.811" Dia x 3.000" L (20.60mm x 76.20mm)	Manufacturer Part Number	0NLN040.T
Flectrical, Specialty Fuses  Package Cartridge, Non-Standard Series POWR-GARD? NLN  Fuse Type Cartridge Current Rating 40A Voltage Rating - AC Voltage Rating - DC Sesponse Time Fast Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension  Electrical, Specialty Fuses  POWR-GARD? NLN  Cartridge Fourtinge Cartridge, Non-Standard Size / Dimension  Cartridge, Non-Standard Size / Dimension  Cartridge, Non-Standard Size / Dimension	Manufacturer	Littelfuse Inc.
Package Cartridge, Non-Standard  Series POWR-GARD? NLN  Fuse Type Cartridge  Current Rating 40A  Voltage Rating - AC 250V  Voltage Rating - DC 250V  Response Time Fast  Applications Electrical, Industrial  Features -  Class K5  Approvals CE, CSA, UL  Operating Temperature -  Breaking Capacity @ Rated Voltage SokA AC, 20kA DC  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Category	Circuit Protection
SeriesPOWR-GARD? NLNFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC250VVoltage Rating - DC250VResponse TimeFastApplicationsElectrical, IndustrialFeatures-ClassK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage50kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.811" Dia x 3.000" L (20.60mm x 76.20mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 40A Voltage Rating - AC 250V Voltage Rating - DC 250V Response Time Fast Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Casov Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge, Non-Standard Size / Dimension Capacity @ Cartridge, Non-Standard Cartridge,	Package	Cartridge, Non-Standard
Current Rating  Voltage Rating - AC  250V  Voltage Rating - DC  250V  Response Time  Fast  Applications  Electrical, Industrial  Features  - Class  K5  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  40A  40A  40A  40A  40A  40A  40A  40	Series	POWR-GARD? NLN
Voltage Rating - AC  Voltage Rating - DC  250V  Response Time  Fast  Applications  Electrical, Industrial  Features  - Class  K5  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  250V  250V  250V  250V  250V  250V  Electrical, Industrial  - Cletrical, Industrial  - CE, CSA, UL  - CE, CSA, U	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Fast  Applications Electrical, Industrial  Features - Class K5  Approvals CE, CSA, UL  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder  Package / Case Size / Dimension  250V  East 250V  East 360  Electrical, Industrial  - CE, CSA, UL  COPIENT COPIE	Current Rating	40A
Response Time Applications Electrical, Industrial Features - Class K5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Fast Electrical, Industrial  - CE, CSA Holder - CE, CSA, UL - CE, CSA	Voltage Rating - AC	250V
Applications Electrical, Industrial  Features - Class K5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 50kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Voltage Rating - DC	250V
Features - Class K5  Approvals CE, CSA, UL  Operating Temperature - Facking Capacity @ Rated Voltage S0kA AC, 20kA DC  Mounting Type Holder  Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Response Time	Fast
Class K5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 50kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension  CE, CSA, UL  Holder Cartridge, Non-Standard O.811" Dia x 3.000" L (20.60mm x 76.20mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  50kA AC, 20kA DC  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Class	K5
Breaking Capacity @ Rated Voltage 50kA AC, 20kA DC  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Breaking Capacity @ Rated Voltage	50kA AC, 20kA DC
Size / Dimension 0.811" Dia x 3.000" L (20.60mm x 76.20mm)	Mounting Type	Holder
· · · · · ·	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.811" Dia x 3.000" L (20.60mm x 76.20mm)
		Report errors?

### **0NLN040.T Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **0NLN040.T Payment Methods**





















## **0NLN040.T Shipping Methods**













If you have any question about 0NLN040.T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com