



0ZRM0065FF2B Information

Heisener com

Part Number 0ZRM0065FF2B

Manufacturer Bel Fuse Inc.

Category Circuit Protection
PTC Resettable Fuses

Description PTC RESET 0.65A 120VAC/VDC RAD

Package Radial, Disc

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0ZRM0065FF2B Specifications

Manufacturer Part Number OZRM0065FF2B Manufacturer Bel Fuse Inc. Category Circuit Protection PTC Resettable Fuses Package Radial, Disc Series OZRM Type Polymeric Voltage - Max 120V Current - Max 5A Current - Hold (lh) (Max) 650mA Current - Trip (lt) 1.3A Time to Trip 5.7s Resistance - Initial (Ri) (Min) 310 mOhms Resistance - Post Trip (R1) (Max) 720 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.382" Dia x 0.150" W (9.70mm x 3.80mm) Height - Seated (Max) - Lead Spacing 0.201" (5.10mm) Report errors?	•	
Category Circuit Protection Package Radial, Disc Series OZRM Type Polymeric Voltage - Max 120V Current - Max 5A Current - Hold (Ih) (Max) 650mA Current - Trip (It) 1.3A Time to Trip 5.7s Resistance - Initial (Ri) (Min) 310 mOhms Resistance - Post Trip (R1) (Max) 720 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.382" Dia x 0.150" W (9.70mm x 3.80mm) Height - Seated (Max) 0.587" (14.90mm) Thickness (Max) - Lead Spacing 0.201" (5.10mm)	Manufacturer Part Number	0ZRM0065FF2B
Package Radial, Disc Series 0ZRM Type Polymeric Voltage - Max 120V Current - Max 5A Current - Hold (Ih) (Max) 650mA Current - Trip (It) 1.3A Time to Trip 5.7s Resistance - Initial (Ri) (Min) 310 mOhms Resistance - Post Trip (R1) (Max) 720 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.382" Dia x 0.150" W (9.70mm x 3.80mm) Height - Seated (Max) 0.587" (14.90mm) Thickness (Max) - Lead Spacing 0.201" (5.10mm)	Manufacturer	Bel Fuse Inc.
Package Radial, Disc Series OZRM Type Polymeric Voltage - Max 120V Current - Max 5A Current - Hold (Ih) (Max) 650mA Current - Trip (It) 1.3A Time to Trip 5.7s Resistance - Initial (Ri) (Min) 310 mOhms Resistance - Post Trip (R1) (Max) 720 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.382" Dia x 0.150" W (9.70mm x 3.80mm) Height - Seated (Max) 0.587" (14.90mm) Thickness (Max) - Lead Spacing 0.201" (5.10mm)	Category	Circuit Protection
Series 0ZRM Type Polymeric Voltage - Max 120V Current - Max 5A Current - Hold (lh) (Max) 650mA Current - Trip (It) 1.3A Time to Trip 5.7s Resistance - Initial (Ri) (Min) 310 mOhms Resistance - Post Trip (R1) (Max) 720 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.382" Dia x 0.150" W (9.70mm x 3.80mm) Height - Seated (Max) 0.587" (14.90mm) Thickness (Max) - Lead Spacing 0.201" (5.10mm)		PTC Resettable Fuses
Type Polymeric Voltage - Max 120V Current - Max 5A Current - Hold (lh) (Max) 650mA Current - Trip (It) 1.3A Time to Trip 5.7s Resistance - Initial (Ri) (Min) 310 mOhms Resistance - Post Trip (R1) (Max) 720 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.382" Dia x 0.150" W (9.70mm x 3.80mm) Height - Seated (Max) 0.587" (14.90mm) Thickness (Max) - Lead Spacing 0.201" (5.10mm)	Package	Radial, Disc
Voltage - Max 120V Current - Max 5A Current - Hold (lh) (Max) 650mA Current - Trip (It) 1.3A Time to Trip 5.7s Resistance - Initial (Ri) (Min) 310 mOhms Resistance - Post Trip (R1) (Max) 720 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.382" Dia x 0.150" W (9.70mm x 3.80mm) Height - Seated (Max) 0.587" (14.90mm) Thickness (Max) - Lead Spacing 0.201" (5.10mm)	Series	0ZRM
Current - Max 5A Current - Hold (Ih) (Max) 650mA Current - Trip (It) 1.3A Time to Trip 5.7s Resistance - Initial (Ri) (Min) 310 mOhms Resistance - Post Trip (R1) (Max) 720 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.382" Dia x 0.150" W (9.70mm x 3.80mm) Height - Seated (Max) 0.587" (14.90mm) Thickness (Max) - Lead Spacing 0.201" (5.10mm)	Туре	Polymeric
Current - Hold (Ih) (Max) 650mA Current - Trip (It) 1.3A Time to Trip 5.7s Resistance - Initial (Ri) (Min) 310 mOhms Resistance - Post Trip (R1) (Max) 720 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.382" Dia x 0.150" W (9.70mm x 3.80mm) Height - Seated (Max) 0.587" (14.90mm) Thickness (Max) - Lead Spacing 0.201" (5.10mm)	Voltage - Max	120V
Current - Trip (It) 1.3A Time to Trip 5.7s Resistance - Initial (Ri) (Min) 310 mOhms Resistance - Post Trip (R1) (Max) 720 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.382" Dia x 0.150" W (9.70mm x 3.80mm) Height - Seated (Max) 0.587" (14.90mm) Thickness (Max) - Lead Spacing 0.201" (5.10mm)	Current - Max	5A
Time to Trip 5.7s Resistance - Initial (Ri) (Min) 310 mOhms Resistance - Post Trip (R1) (Max) 720 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.382" Dia x 0.150" W (9.70mm x 3.80mm) Height - Seated (Max) 0.587" (14.90mm) Thickness (Max) - Lead Spacing 0.201" (5.10mm)	Current - Hold (Ih) (Max)	650mA
Resistance - Initial (Ri) (Min) Resistance - Post Trip (R1) (Max) Resistance - 25°C (Typ) Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing 310 mOhms 420 mOhms -40°C ~ 85°C Advice As Sive As	Current - Trip (It)	1.3A
Resistance - Post Trip (R1) (Max) Resistance - 25°C (Typ) Operating Temperature -40°C ~ 85°C Ratings Mounting Type Through Hole Package / Case Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing 720 mOhms 720 mOhms 720 mOhms 720 mOhms -40°C ~ 85°C -40°C ~ 85°C Ratings - Where the search of the search o	Time to Trip	5.7s
Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.382" Dia x 0.150" W (9.70mm x 3.80mm) Height - Seated (Max) 0.587" (14.90mm) Thickness (Max) - Lead Spacing 0.201" (5.10mm)	Resistance - Initial (Ri) (Min)	310 mOhms
Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.382" Dia x 0.150" W (9.70mm x 3.80mm) Height - Seated (Max) 0.587" (14.90mm) Thickness (Max) - Lead Spacing 0.201" (5.10mm)	Resistance - Post Trip (R1) (Max)	720 mOhms
Ratings - Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.382" Dia x 0.150" W (9.70mm x 3.80mm) Height - Seated (Max) 0.587" (14.90mm) Thickness (Max) - Lead Spacing 0.201" (5.10mm)	Resistance - 25°C (Typ)	-
Mounting Type Through Hole Package / Case Radial, Disc Size / Dimension 0.382" Dia x 0.150" W (9.70mm x 3.80mm) Height - Seated (Max) 0.587" (14.90mm) Thickness (Max) - Lead Spacing 0.201" (5.10mm)	Operating Temperature	-40°C ~ 85°C
Package / Case Radial, Disc Size / Dimension 0.382" Dia x 0.150" W (9.70mm x 3.80mm) Height - Seated (Max) 0.587" (14.90mm) Thickness (Max) - Lead Spacing 0.201" (5.10mm)	Ratings	-
Size / Dimension 0.382" Dia x 0.150" W (9.70mm x 3.80mm) Height - Seated (Max) 0.587" (14.90mm) Thickness (Max) - Lead Spacing 0.201" (5.10mm)	Mounting Type	Through Hole
Height - Seated (Max) 0.587" (14.90mm) Thickness (Max) - Lead Spacing 0.201" (5.10mm)	Package / Case	Radial, Disc
Thickness (Max) - Lead Spacing 0.201" (5.10mm)	Size / Dimension	0.382" Dia x 0.150" W (9.70mm x 3.80mm)
Lead Spacing 0.201" (5.10mm)	Height - Seated (Max)	0.587" (14.90mm)
	Thickness (Max)	-
Report errors?	Lead Spacing	0.201" (5.10mm)
		Report errors?

0ZRM0065FF2B Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0ZRM0065FF2B Payment Methods



















0ZRM0065FF2B Shipping Methods













If you have any question about 0ZRM0065FF2B, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com