



0ZRM0250FF1A Information



For Reference Only

Part Number 0ZRM0250FF1A

Manufacturer Bel Fuse Inc.

Category Circuit Protection
PTC Resettable Fuses

Description PTC RESET 2.50A 120VAC/VDC RAD

Package Radial, Disc

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









0ZRM0250FF1A Specifications

Manufacturer Part Number OZRM0250FF1A Manufacturer Bel Fuse Inc. Category Circuit Protection Package Radial, Disc Series OZRM Type Polymeric Voltage - Max 120V Current - Max 15A Current - Hold (Ih) (Max) 2.5A Current - Trip (It) 5A Time to Trip 15.6s Resistance - Initial (Ri) (Min) 50 mOhms Resistance - Post Trip (R1) (Max) 130 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Through Hole
Category Circuit Protection PTC Resettable Fuses Package Radial, Disc Series OZRM Type Polymeric Voltage - Max 120V Current - Max 15A Current - Hold (Ih) (Max) 2.5A Current - Trip (It) 5A Time to Trip 15.6s Resistance - Initial (Ri) (Min) 50 mOhms Resistance - Post Trip (R1) (Max) 130 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings -
PTC Resettable Fuses Package Radial, Disc Series OZRM Type Polymeric Voltage - Max 120V Current - Max 15A Current - Hold (Ih) (Max) 2.5A Current - Trip (It) 5A Time to Trip 15.6s Resistance - Initial (Ri) (Min) 50 mOhms Resistance - Post Trip (R1) (Max) 130 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings -
Package Series OZRM Type Polymeric Voltage - Max 120V Current - Max 15A Current - Hold (Ih) (Max) 2.5A Current - Trip (It) 5A Time to Trip 15.6s Resistance - Initial (Ri) (Min) Resistance - Post Trip (R1) (Max) Resistance - 25°C (Typ) Operating Temperature Radial, Disc OZRM Radial, Disc OZRM Polymeric 150 150 SA 150 SA 150 SA 150 SO SO SO SO SO SO SO SO SO S
Series 0ZRM Type Polymeric Voltage - Max 120V Current - Max 15A Current - Hold (Ih) (Max) 2.5A Current - Trip (It) 5A Time to Trip 15.6s Resistance - Initial (Ri) (Min) 50 mOhms Resistance - Post Trip (R1) (Max) 130 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings -
Type Polymeric Voltage - Max 120V Current - Max 15A Current - Hold (Ih) (Max) 2.5A Current - Trip (It) 5A Time to Trip 15.6s Resistance - Initial (Ri) (Min) 50 mOhms Resistance - Post Trip (R1) (Max) 130 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings -
Voltage - Max 120V Current - Max 15A Current - Hold (Ih) (Max) 2.5A Current - Trip (It) 5A Time to Trip 15.6s Resistance - Initial (Ri) (Min) 50 mOhms Resistance - Post Trip (R1) (Max) 130 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings -
Current - Max Current - Hold (Ih) (Max) 2.5A Current - Trip (It) 5A Time to Trip 15.6s Resistance - Initial (Ri) (Min) 50 mOhms Resistance - Post Trip (R1) (Max) Resistance - 25°C (Typ) Operating Temperature -40°C ~ 85°C Ratings - 15A 2.5A 50 mOhms
Current - Hold (Ih) (Max) Current - Trip (It) 5A Time to Trip 15.6s Resistance - Initial (Ri) (Min) 50 mOhms Resistance - Post Trip (R1) (Max) 130 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Company Temperature
Current - Trip (It) 5A Time to Trip 15.6s Resistance - Initial (Ri) (Min) 50 mOhms Resistance - Post Trip (R1) (Max) 130 mOhms Resistance - 25°C (Typ)
Time to Trip 15.6s Resistance - Initial (Ri) (Min) 50 mOhms Resistance - Post Trip (R1) (Max) 130 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings -
Resistance - Initial (Ri) (Min) 50 mOhms Resistance - Post Trip (R1) (Max) 130 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings -
Resistance - Post Trip (R1) (Max) Resistance - 25°C (Typ) Operating Temperature -40°C ~ 85°C Ratings -
Resistance - 25° C (Typ) - -40° C ~ 85° C Ratings -
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Ratings $-$
Ratings -
Mounting Type Through Hole
Package / Case Radial, Disc
Size / Dimension 0.886" Dia x 0.161" W (22.50mm x 4.10mm)
Height - Seated (Max) 1.082" (27.50mm)
Thickness (Max)
Lead Spacing 0.402" (10.20mm)
Report errors?

0ZRM0250FF1A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

0ZRM0250FF1A Payment Methods



















0ZRM0250FF1A Shipping Methods













If you have any question about 0ZRM0250FF1A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com