

Heisener.com

## 1 PSI-GF-PRIME-MINI

### 1 PSI-GF-PRIME-MINI Information

Part Number1 PSI-GF-PRIME-MINIManufacturerAll Sensors CorporationCategorySensors, Transducers

Pressure Sensors, Transducers

**Description** SENSOR 1PSI GF MV MONO

Package 4-SIP Module

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 1 PSI-GF-PRIME-MINI Specifications

Manufacturer Part Number  Manufacturer  All Sensors Corporation  Category  Sensors, Transducers  Pressure Sensors, Transducers  Package  4-SIP Module  Series  ACPC  Pressure Type  Vented Gauge  Operating Pressure  1 PSI (6.89 kPa)  Output Type  Wheatstone Bridge  Output  0 mV ~ 18 mV (12V)  Accuracy  4-0.25%  Voltage - Supply  16V  Port Size  Male - 0.18" (4.57mm) Tube  Port Style  Barbless  Features  Temperature Compensated  Termination Style  Maximum Pressure  10 PSI (68.95 kPa)  Operating Temperature  -25°C ~ 85°C  Package / Case  Supplier Device Package  -  Report errors?		
CategorySensors, TransducersPackage4-SIP ModuleSeriesACPCPressure TypeVented GaugeOperating Pressure1 PSI (6.89 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 18 mV (12V)Accuracy±0.25%Voltage - Supply16VPort SizeMale - 0.18" (4.57mm) TubePort StyleBarblessFeaturesTemperature CompensatedTermination StylePCBMaximum Pressure10 PSI (68.95 kPa)Operating Temperature-25°C ~ 85°CPackage / Case4-SIP ModuleSupplier Device Package-	Manufacturer Part Number	1 PSI-GF-PRIME-MINI
Package 4-SIP Module Series ACPC Pressure Type Vented Gauge Operating Pressure Output Type Wheatstone Bridge Output (12V) Accuracy ±0.25% Voltage - Supply 16V Port Size Male - 0.18" (4.57mm) Tube Port Style Barbless Features Temperature Compensated Termination Style PCB Maximum Pressure 10 PSI (68.95 kPa) Operating Temperature - 25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package	Manufacturer	All Sensors Corporation
Package4-SIP ModuleSeriesACPCPressure TypeVented GaugeOperating Pressure1 PSI (6.89 kPa)Output TypeWheatstone BridgeOutput0 mV ~ 18 mV (12V)Accuracy±0.25%Voltage - Supply16VPort SizeMale - 0.18" (4.57mm) TubePort StyleBarblessFeaturesTemperature CompensatedTermination StylePCBMaximum Pressure10 PSI (68.95 kPa)Operating Temperature-25°C ~ 85°CPackage / Case4-SIP ModuleSupplier Device Package-	Category	Sensors, Transducers
Series ACPC Pressure Type Vented Gauge Operating Pressure Operating Pressure Output Type Wheatstone Bridge Output Output OmV~18 mV (12V) Accuracy ±0.25% Voltage - Supply I6V Port Size Male - 0.18" (4.57mm) Tube Port Style Barbless Features Temperature Compensated Termination Style Maximum Pressure 10 PSI (68.95 kPa) Operating Temperature -25°C ~ 85°C Package / Case Supplier Device Package		Pressure Sensors, Transducers
Pressure Type Operating Pressure 1 PSI (6.89 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 18 mV (12V) Accuracy ±0.25% Voltage - Supply 16V Port Size Male - 0.18" (4.57mm) Tube Port Style Barbless Features Temperature Compensated Termination Style Maximum Pressure 10 PSI (68.95 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package	Package	4-SIP Module
Operating Pressure  1 PSI (6.89 kPa)  Output Type  Wheatstone Bridge  Output  0 mV ~ 18 mV (12V)  Accuracy  ±0.25%  Voltage - Supply  16V  Port Size  Male - 0.18" (4.57mm) Tube  Port Style  Barbless  Features  Temperature Compensated  Termination Style  PCB  Maximum Pressure  10 PSI (68.95 kPa)  Operating Temperature  -25°C ~ 85°C  Package / Case  Supplier Device Package  -	Series	ACPC
Output Type Output Output OmV ~ 18 mV (12V) Accuracy ±0.25% Voltage - Supply I6V Port Size Male - 0.18" (4.57mm) Tube Port Style Barbless Features Temperature Compensated Termination Style Maximum Pressure I0 PSI (68.95 kPa) Operating Temperature -25°C ~ 85°C Package / Case Supplier Device Package -	Pressure Type	Vented Gauge
Output 0 mV ~ 18 mV (12V)  Accuracy ±0.25%  Voltage - Supply 16V  Port Size Male - 0.18" (4.57mm) Tube  Port Style Barbless  Features Temperature Compensated  Termination Style PCB  Maximum Pressure 10 PSI (68.95 kPa)  Operating Temperature -25°C ~ 85°C  Package / Case 4-SIP Module  Supplier Device Package	Operating Pressure	1 PSI (6.89 kPa)
Accuracy ±0.25%  Voltage - Supply 16V  Port Size Male - 0.18" (4.57mm) Tube  Port Style Barbless  Features Temperature Compensated  Termination Style PCB  Maximum Pressure 10 PSI (68.95 kPa)  Operating Temperature -25°C ~ 85°C  Package / Case 4-SIP Module  Supplier Device Package	Output Type	Wheatstone Bridge
Voltage - Supply  Port Size  Male - 0.18" (4.57mm) Tube  Barbless  Features  Temperature Compensated  Termination Style  Maximum Pressure  10 PSI (68.95 kPa)  Operating Temperature  -25°C ~ 85°C  Package / Case  4-SIP Module  Supplier Device Package	Output	$0 \text{ mV} \sim 18 \text{ mV} (12 \text{V})$
Port Size  Port Style  Barbless  Features  Temperature Compensated  Termination Style  PCB  Maximum Pressure  10 PSI (68.95 kPa)  Operating Temperature  -25°C ~ 85°C  Package / Case  4-SIP Module  Supplier Device Package	Accuracy	±0.25%
Port Style  Features  Temperature Compensated  Termination Style  PCB  Maximum Pressure  10 PSI (68.95 kPa)  Operating Temperature  -25°C ~ 85°C  Package / Case  4-SIP Module  Supplier Device Package	Voltage - Supply	16V
Features Temperature Compensated  Termination Style PCB  Maximum Pressure 10 PSI (68.95 kPa)  Operating Temperature -25°C ~ 85°C  Package / Case 4-SIP Module  Supplier Device Package	Port Size	Male - 0.18" (4.57mm) Tube
Termination Style PCB  Maximum Pressure 10 PSI (68.95 kPa)  Operating Temperature -25°C ~ 85°C  Package / Case 4-SIP Module  Supplier Device Package -	Port Style	Barbless
Maximum Pressure10 PSI (68.95 kPa)Operating Temperature-25°C ~ 85°CPackage / Case4-SIP ModuleSupplier Device Package-	Features	Temperature Compensated
Operating Temperature -25°C ~ 85°C  Package / Case 4-SIP Module  Supplier Device Package -	Termination Style	PCB
Package / Case 4-SIP Module Supplier Device Package -	Maximum Pressure	10 PSI (68.95 kPa)
Supplier Device Package -	Operating Temperature	-25°C ~ 85°C
	Package / Case	4-SIP Module
Report errors?	Supplier Device Package	-
		Report errors?

### 1 PSI-GF-PRIME-MINI Guarantees



#### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### 1 PSI-GF-PRIME-MINI Payment Methods



















## 1 PSI-GF-PRIME-MINI Shipping Methods













If you have any question about 1 PSI-GF-PRIME-MINI, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com