



1111J2500621KQT Information

Heisener.com

For Reference Only

1111J2500621KQT

Manufacturer Knowles Syfer Category

Part Number

Capacitors

Ceramic Capacitors

Description

CAP CER 620PF 250V C0G/NP0 1111

Package

1111 (2828 Metric)

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









1111J2500621KQT Specifications

Manufacturer Part Number 1111J2500621KQT Manufacturer Knowles Syfer Category Capacitors Package 1111 (2828 Metric) Series - Capacitance 620pF Tolerance ±10% Voltage - Rated 250V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1111 (2828 Metric) Size / Dimension 0.110" L x 0.110" W (2.79mm x 2.79mm) Height - Seated (Max) - Thickness (Max) 0.070" (1.78mm) Lead Spacing - Lead Spacing - Lead Style -		
Category Capacitors Package 1111 (2828 Metric) Series - Capacitance 620pF Tolerance ±10% Voltage - Rated 250V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1111 (2828 Metric) Size / Dimension 0.110" L x 0.110" W (2.79mm x 2.79mm) Height - Seated (Max) - Thickness (Max) 0.070" (1.78mm) Lead Spacing - Lead Style -	Manufacturer Part Number	1111J2500621KQT
Package 1111 (2828 Metric) Series - Capacitance 620pF Tolerance ±10% Voltage - Rated 250V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1111 (2828 Metric) Size / Dimension 0.110" L x 0.110" W (2.79mm x 2.79mm) Height - Seated (Max) - Thickness (Max) 0.070" (1.78mm) Lead Spacing - Lead Style -	Manufacturer	Knowles Syfer
Package 1111 (2828 Metric) Series - Capacitance 620pF Tolerance ±10% Voltage - Rated 250V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1111 (2828 Metric) Size / Dimension 0.110" L x 0.110" W (2.79mm x 2.79mm) Height - Seated (Max) - Thickness (Max) 0.070" (1.78mm) Lead Spacing - Lead Style -	Category	Capacitors
Series - Capacitance 620pF Tolerance ±10% Voltage - Rated 250V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1111 (2828 Metric) Size / Dimension 0.110" L x 0.110" W (2.79mm x 2.79mm) Height - Seated (Max) - Thickness (Max) 0.070" (1.78mm) Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 620pF Tolerance ±10% Voltage - Rated 250V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1111 (2828 Metric) Size / Dimension 0.110" L x 0.110" W (2.79mm x 2.79mm) Height - Seated (Max) - Thickness (Max) 0.070" (1.78mm) Lead Spacing - Lead Style -	Package	1111 (2828 Metric)
Tolerance ±10% Voltage - Rated 250V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1111 (2828 Metric) Size / Dimension 0.110" L x 0.110" W (2.79mm x 2.79mm) Height - Seated (Max) - Thickness (Max) 0.070" (1.78mm) Lead Spacing - Lead Style -	Series	-
Voltage - Rated250VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh Q, Low LossRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1111 (2828 Metric)Size / Dimension0.110" L x 0.110" W (2.79mm x 2.79mm)Height - Seated (Max)-Thickness (Max)0.070" (1.78mm)Lead Spacing-Lead Style-	Capacitance	620pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1111 (2828 Metric) Size / Dimension 0.110" L x 0.110" W (2.79mm x 2.79mm) Height - Seated (Max) Thickness (Max) 0.070" (1.78mm) Lead Spacing - Lead Style	Tolerance	±10%
Operating Temperature-55°C ~ 125°CFeaturesHigh Q, Low LossRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1111 (2828 Metric)Size / Dimension0.110" L x 0.110" W (2.79mm x 2.79mm)Height - Seated (Max)-Thickness (Max)0.070" (1.78mm)Lead Spacing-Lead Style-	Voltage - Rated	250V
Features High Q, Low Loss Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1111 (2828 Metric) Size / Dimension 0.110" L x 0.110" W (2.79mm x 2.79mm) Height - Seated (Max) - Thickness (Max) 0.070" (1.78mm) Lead Spacing - Lead Style -	Temperature Coefficient	C0G, NP0
Ratings - General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1111 (2828 Metric) Size / Dimension 0.110" L x 0.110" W (2.79mm x 2.79mm) Height - Seated (Max) - Thickness (Max) 0.070" (1.78mm) Lead Spacing - Lead Style	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1111 (2828 Metric) Size / Dimension 0.110" L x 0.110" W (2.79mm x 2.79mm) Height - Seated (Max) - Thickness (Max) 0.070" (1.78mm) Lead Spacing - Lead Style -	Features	High Q, Low Loss
Failure Rate Mounting Type Surface Mount, MLCC Package / Case 1111 (2828 Metric) Size / Dimension 0.110" L x 0.110" W (2.79mm x 2.79mm) Height - Seated (Max) - Thickness (Max) 0.070" (1.78mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 1111 (2828 Metric) Size / Dimension 0.110" L x 0.110" W (2.79mm x 2.79mm) Height - Seated (Max) - Thickness (Max) 0.070" (1.78mm) Lead Spacing - Lead Style -	Applications	General Purpose
Package / Case 1111 (2828 Metric) Size / Dimension 0.110" L x 0.110" W (2.79mm x 2.79mm) Height - Seated (Max) - Thickness (Max) 0.070" (1.78mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.110" L x 0.110" W (2.79mm x 2.79mm) Height - Seated (Max) - Thickness (Max) 0.070" (1.78mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - - - - - - - - - - - - -	Package / Case	1111 (2828 Metric)
Thickness (Max) 0.070" (1.78mm) Lead Spacing - Lead Style -	Size / Dimension	0.110" L x 0.110" W (2.79mm x 2.79mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.070" (1.78mm)
·	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

1111J2500621KQT Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

1111J2500621KQT Payment Methods



















1111J2500621KQT Shipping Methods













If you have any question about 1111J2500621KQT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com