

125E1CL5.5

Request a Quote

125E1CL5.5 Information

Heisener.com	Part Number	125E1CL5.5
	Manufacturer	Littelfuse Inc.
	Category	Circuit Protection Electrical, Specialty Fuses
	Description	FUSE CARTRIDGE 125A 5.5KVAC CYL
	Package	Cylindrical, Blade Terminal (Bolt)
		For the pricing/inventory/lead time, please contact
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



125E1CL5.5 Specifications

ManufacturerLittlefuse Inc.CategoryCircuit ProtectionElectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating125AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Package Manufacture60kAMounting Type60t MountPackage / CaseCircuinal, Blade Terminal (Bolt)			
CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating125AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Applications7ansformer ProtectionFasturesIndicatingClassEApprovals-Operating Temperature80kAMounting TypeBolt MountPackage / CaseSci MountSize / Dimension5.130" K x 3.000" W x 4.310" H (384.30mm x 76.20mm x 109.47mm)	Manufacturer Part Number	125E1CL5.5	
Bit ControlPackageElectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating125AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating TemperatureS0kABreaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension15.130" L x 3.000" W x 4.310" H (384.30mm x 76.20mm x 109.47mm)	Manufacturer	Littelfuse Inc.	
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating125AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension15.130" L x 3.000" W x 4.310" H (384.30mm x 76.20mm x 109.47mm)	Category	Circuit Protection	
SeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating125AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClass-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80AAMounting TypeBol MountPackage / CaseSin Sun Carting Handle MountSize / Dimension15.130" L x 3.000" W x 4.310" H (384.30mm x 76.0mm x 109.47mm)		Electrical, Specialty Fuses	
Fuse TypeCartridgeFuse TypeCartridgeCurrent Rating125AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension5.130" L x 3.000" W x 4.310" H (384.30mm x 76.20mm x 109.47mm)	Package	Cylindrical, Blade Terminal (Bolt)	
Current Rating125AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.5130" L x 3.000" W x 4.310" H (384.30mm x 76.20mm x 109.47mm)	Series	POWR-GARD?	
Voltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension15.130" L x 3.000" W x 4.310" H (384.30mm x 76.20mm x 109.47mm)	Fuse Type	Cartridge	
Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension15.130" L x 3.000" W x 4.310" H (384.30mm x 76.20mm x 109.47mm)	Current Rating	125A	
Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension15.130" L x 3.000" W x 4.310" H (384.30mm x 76.20mm x 109.47mm)	Voltage Rating - AC	5500V (5.5kV)	
ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension15.130" L x 3.000" W x 4.310" H (384.30mm x 76.20mm x 109.47mm)	Voltage Rating - DC	-	
IndicatingFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension15.130" L x 3.000" W x 4.310" H (384.30mm x 76.20mm x 109.47mm)	Response Time	-	
ClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension15.130" L x 3.000" W x 4.310" H (384.30mm x 76.20mm x 109.47mm)	Applications	Transformer Protection	
Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension15.130" L x 3.000" W x 4.310" H (384.30mm x 76.20mm x 109.47mm)	Features	Indicating	
Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension15.130" L x 3.000" W x 4.310" H (384.30mm x 76.20mm x 109.47mm)	Class	Ε	
Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension15.130" L x 3.000" W x 4.310" H (384.30mm x 76.20mm x 109.47mm)	Approvals	-	
Mounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension15.130" L x 3.000" W x 4.310" H (384.30mm x 76.20mm x 109.47mm)	Operating Temperature	-	
Package / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension15.130" L x 3.000" W x 4.310" H (384.30mm x 76.20mm x 109.47mm)	Breaking Capacity @ Rated Voltage	80kA	
Size / Dimension 15.130" L x 3.000" W x 4.310" H (384.30mm x 76.20mm x 109.47mm)	Mounting Type	Bolt Mount	
	Package / Case	Cylindrical, Blade Terminal (Bolt)	
Report errors?	Size / Dimension	15.130" L x 3.000" W x 4.310" H (384.30mm x 76.20mm x 109.47mm)	
		Report errors?	

125E1CL5.5 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE SUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 125E1CL5.5, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com