

#### 14A-5.0-20B20 Information

Heisener.com

**Part Number** 14A-5.0-20B20

Manufacturer Pulse Electronics Power

**Category** Transformers

**Power Transformers** 

**Description** XFRMR LAMINATED 5VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### 14A-5.0-20B20 Specifications

Manufacturer Part Number       14A-5.0-20B20         Manufacturer       Pulse Electronics Power         Category       Transformers         Power Transformers       Power Transformers         Package       -         Series       International PC Plug-In         Type       Laminated Core         Voltage - Primary       115V, 230V         Voltage - Secondary (Full Load)       Parallel 10V, Series 20V         Current - Output (Max)       Parallel 500mA, Series 250mA         Primary Winding(s)       Dual         Secondary Winding(s)       Single, Multiple Taps         Center Tap       No         Power - Max       5 VA         Mounting Type       Through Hole         Termination Style       PC Pin         Size / Dimension       41.28mm L x 33.32mm W         Height - Seated (Max)       34.93mm         Voltage - Isolation       -         Weight       0.37 lb (167.83g)		
Category         Transformers           Power Transformers           Package         -           Series         International PC Plug-In           Type         Laminated Core           Voltage - Primary         115V, 230V           Voltage - Secondary (Full Load)         Parallel 10V, Series 20V           Current - Output (Max)         Parallel 500mA, Series 250mA           Primary Winding(s)         Dual           Secondary Winding(s)         Single, Multiple Taps           Center Tap         No           Power - Max         5 VA           Mounting Type         Through Hole           Termination Style         PC Pin           Size / Dimension         41.28mm L x 33.32mm W           Height - Seated (Max)         34.93mm           Voltage - Isolation         -           Weight         0.37 lb (167.83g)	Manufacturer Part Number	14A-5.0-20B20
Package - Series International PC Plug-In Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 10V, Series 20V Current - Output (Max) Parallel 500mA, Series 250mA Primary Winding(s) Dual Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max 5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) 34.93mm Voltage - Isolation - Weight 0.37 lb (167.83g)	Manufacturer	Pulse Electronics Power
Package-SeriesInternational PC Plug-InTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 10V, Series 20VCurrent - Output (Max)Parallel 500mA, Series 250mAPrimary Winding(s)DualSecondary Winding(s)Single, Multiple TapsCenter TapNoPower - Max5 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 33.32mm WHeight - Seated (Max)34.93mmVoltage - Isolation-Weight0.37 lb (167.83g)	Category	Transformers
SeriesInternational PC Plug-InTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 10V, Series 20VCurrent - Output (Max)Parallel 500mA, Series 250mAPrimary Winding(s)DualSecondary Winding(s)Single, Multiple TapsCenter TapNoPower - Max5 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 33.32mm WHeight - Seated (Max)34.93mmVoltage - Isolation-Weight0.37 lb (167.83g)		Power Transformers
Type Laminated Core  Voltage - Primary 115V, 230V  Voltage - Secondary (Full Load) Parallel 10V, Series 20V  Current - Output (Max) Parallel 500mA, Series 250mA  Primary Winding(s) Dual  Secondary Winding(s) Single, Multiple Taps  Center Tap No  Power - Max 5 VA  Mounting Type Through Hole  Termination Style PC Pin  Size / Dimension 41.28mm L x 33.32mm W  Height - Seated (Max) 34.93mm  Voltage - Isolation -  Weight 0.37 lb (167.83g)	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 10V, Series 20V Current - Output (Max) Parallel 500mA, Series 250mA Primary Winding(s) Dual Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max 5 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) Voltage - Isolation Voltage - Isolation Voltage - Isolation  0.37 lb (167.83g)	Series	International PC Plug-In
Voltage - Secondary (Full Load)  Current - Output (Max)  Parallel 500mA, Series 250mA  Primary Winding(s)  Dual  Secondary Winding(s)  Single, Multiple Taps  Center Tap  No  Power - Max  5 VA  Mounting Type  Through Hole  Termination Style  Size / Dimension  41.28mm L x 33.32mm W  Height - Seated (Max)  Voltage - Isolation  Voltage - Isolation  -  Weight  Parallel 10V, Series 20V  Parallel 10V, Series 20V  Parallel 10V, Series 20V  Parallel 500mA, Series 250mA  Parallel 500mA, Series 250mA  Parallel 500mA, Series 250mA  Parallel 500mA, Series 250mA  Parallel 10V, Series 20V  Parallel 500mA, Series 250mA  Dual  Single, Multiple Taps  No  0 00000000000000000000000000000000	Туре	Laminated Core
Current - Output (Max) Primary Winding(s) Dual Secondary Winding(s) Single, Multiple Taps Center Tap No Power - Max S VA Mounting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Voltage - Isolation Parallel 500mA, Series 250mA Dual  Single, Multiple Taps No Power - Max S VA  No Power - Max S VA  41.28mm L x 33.32mm W	Voltage - Primary	115V, 230V
Primary Winding(s)  Secondary Winding(s)  Center Tap  No  Power - Max  5 VA  Mounting Type  Through Hole  Termination Style  Size / Dimension  Height - Seated (Max)  Voltage - Isolation  Veight  Dual  Single, Multiple Taps  No  PO  140  140  140  140  140  140  140  14	Voltage - Secondary (Full Load)	Parallel 10V, Series 20V
Secondary Winding(s)Single, Multiple TapsCenter TapNoPower - Max5 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 33.32mm WHeight - Seated (Max)34.93mmVoltage - Isolation-Weight0.37 lb (167.83g)	Current - Output (Max)	Parallel 500mA, Series 250mA
Center TapNoPower - Max5 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension41.28mm L x 33.32mm WHeight - Seated (Max)34.93mmVoltage - Isolation-Weight0.37 lb (167.83g)	Primary Winding(s)	Dual
Power - Max  Mounting Type  Through Hole  Termination Style  PC Pin  Size / Dimension  41.28mm L x 33.32mm W  Height - Seated (Max)  Voltage - Isolation  Veight  5 VA  Through Hole  PC Pin  41.28mm L x 33.32mm W  34.93mm  0.37 lb (167.83g)	Secondary Winding(s)	Single, Multiple Taps
Mounting Type Through Hole PC Pin Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) Voltage - Isolation Veight 0.37 lb (167.83g)	Center Tap	No
Termination Style PC Pin Size / Dimension 41.28mm L x 33.32mm W Height - Seated (Max) 34.93mm Voltage - Isolation - Weight 0.37 lb (167.83g)	Power - Max	5 VA
Size / Dimension 41.28mm L x 33.32mm W  Height - Seated (Max) 34.93mm  Voltage - Isolation -  Weight 0.37 lb (167.83g)	Mounting Type	Through Hole
Height - Seated (Max)  Voltage - Isolation  Weight  34.93mm  -  0.37 lb (167.83g)	Termination Style	PC Pin
Voltage - Isolation - Weight 0.37 lb (167.83g)	Size / Dimension	41.28mm L x 33.32mm W
Weight 0.37 lb (167.83g)	Height - Seated (Max)	34.93mm
	Voltage - Isolation	-
	Weight	0.37 lb (167.83g)
Report errors?		Report errors?

#### 14A-5.0-20B20 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# 14A-5.0-20B20 Payment Methods





















### 14A-5.0-20B20 Shipping Methods













If you have any question about 14A-5.0-20B20, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com