

170M2620

170M2620 Information



Part Number	170M2620	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE SQ 350A 700VAC RECTANGULAR	
Package	Rectangular, Blade	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



170M2620 Specifications

Manufacturer Part NumberI70M2620ManufacturerEatonCategoryCircuit ProtectionBelctrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent RatingStoAVoltage Rating - DC-Voltage Rating - DC-ApplicationsElectrical, IndustrialApplicationsElectrical, IndustrialClass-ApprovalsCirc SA, UROperating Temperature-Applorating TypeBit MountMouning TypeBit MountPackage / CaseSci Sa, USA, USA, USA, USA, USA, USA, USA, USA		
CategoryCircuit Protection Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareFuse TypeSobACurrent Rating350AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFaturesIndicatingApprovalsCE, CSA, UROperating Temperature000APreaking Capacity @ Rating Policy-ApprovalsCE, CSA, UROperating Temperature000AMounting TypeBid MountPackage / CaseRectangular, BladeSize / Dimension1.26" L x 1.181" W x 2.008" H (54.00mm x 30.00mm x 51.00mm)	Manufacturer Part Number	170M2620
Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating350AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature200kABreaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2126" L x 1.181" W x 2.008" H (54.00mm x 30.00mm x 51.00mm)	Manufacturer	Eaton
PackageRectangular, BladeSeries-Fuse TypeSquareCurrent RatingSobAVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating TemperatureSobAMounting TypeBolt MountPackage / CaseRetangular, BladeSize / Dimension2.126" L x 1.181" W x 2.008" H (54.00mm x 51.00mm)	Category	Circuit Protection
Series-Fuse TypeSquareCurrent Rating350AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature900ABreaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRcangular, BladeSize / Dimension1.216" L x 1.181" W x 2.008" H (54.00mm x 51.00mm)		Electrical, Specialty Fuses
Fuse TypeSquareFuse TypeSquareCurrent RatingStoAVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature200KAHounting TypeBol MountPackage / CaseRectangual BalaSize / Dimension2.126" L x 1.181" W x 2.008" H (54.00mm x 51.00mm)	Package	Rectangular, Blade
Current Rating350AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Beaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangulandeSize / Dimension2.126" L x 1.181" W x 2.008" H (54.00mm x 50.00mm x 51.00mm)	Series	-
Voltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated VoltageBolt MountMounting TypeBolt MountPackage / Case.Size / Dimension2.126" L x 1.181" W x 2.008" H (54.00mm x 51.00mm)	Fuse Type	Square
Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.126" L x 1.181" W x 2.008" H (54.00mm x 50.00mm x 51.00mm)	Current Rating	350A
Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.126" L x 1.181" W x 2.008" H (54.00mm x 51.00mm)	Voltage Rating - AC	700V
ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.126" L x 1.181" W x 2.008" H (54.00mm x 30.00mm x 51.00mm)	Voltage Rating - DC	-
FeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangulare BladeSize / Dimension2.126" L x 1.181" W x 2.008" H (54.00mm x 51.00mm x 51.00	Response Time	-
Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.126" L x 1.181" W x 2.008" H (54.00mm x 51.00mm)	Applications	Electrical, Industrial
ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.126" L x 1.181" W x 2.008" H (54.00mm x 51.00mm)	Features	Indicating
Operating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.126" L x 1.181" W x 2.008" H (54.00mm x 30.00mm x 51.00mm)	Class	-
Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.126" L x 1.181" W x 2.008" H (54.00mm x 30.00mm x 51.00mm)	Approvals	CE, CSA, UR
Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.126" L x 1.181" W x 2.008" H (54.00mm x 30.00mm x 51.00mm)	Operating Temperature	-
Package / CaseRectangular, BladeSize / Dimension2.126" L x 1.181" W x 2.008" H (54.00mm x 30.00mm x 51.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 2.126" L x 1.181" W x 2.008" H (54.00mm x 30.00mm x 51.00mm)	Mounting Type	Bolt Mount
	Package / Case	Rectangular, Blade
Report errors?	Size / Dimension	2.126" L x 1.181" W x 2.008" H (54.00mm x 30.00mm x 51.00mm)
		Report errors?

170M2620 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 170M2620, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com