

170M4240

170M4240 Information



Part Number	170M4240	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE SQ 250A 1.3KVAC RECTANGULAR	
Package	Rectangular, Blade	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



170M4240 Specifications

Manufacturer Part Number170M4240ManufacturerEatonCategoryCircuit ProtectionBeletrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent RatingStoAVoltage Rating - DC-Voltage Rating - DC-Applications-FacturesIdicatingClass-Approvals-Operating TypeSA, UROperating Type-Applications-Approvals-Operating Type-Mouning TypeBid MountPackage / CaseSito MountSize / DimensionSito Sito Sito Sito Sito Sito Sito Sito		
CategoryCircuit ProtectionBectrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent RatingStoAVoltage Rating - AC300V (1.3kV)Voltage Rating - DC-ApplicationsElectrical, IndustrialFeaturesIdicatingClass-ApprovalsCSA, UROperating Temperature-ApprovalsStoAApprovals-Approvals-Approvals-Aparting Temperature-Autoning Type-Autoning Type-Autoning Type-Stae / Case-Stae / Case-Stae / Dimension-Stae / Dimens	Manufacturer Part Number	170M4240
InstructionElectrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating250AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature100kABreaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseSctangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Manufacturer	Eaton
PackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating250AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature00kABreaking Capacity @ Rated VoltageBolt MountiMounting TypeBolt MountFackage / CaseSctangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 55.00mm)	Category	Circuit Protection
Series.Fuse TypeSquareFuse TypeSquareCurrent Rating250AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC.Response Time.ApplicationsElectrical, IndustrialFeaturesIndicatingClass.ApprovalsCSA, UROperating Temperature.Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangulan, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)		Electrical, Specialty Fuses
Fuse TypeSquareFuser TypeSquareCurrent RatingStoAVoltage Rating - AC300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Anonting TypeBiol MountPackage / CaseRectangulandeFeaturesSto MuntStor L s 2.087" W x 2.598" H (80.00mm x 56.00mm)	Package	Rectangular, Blade
Current Rating250AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangulan BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Series	-
Voltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated VoltageBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Fuse Type	Square
Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature100kABreaking Capacity @ Rated VoltageBolt MountMounting TypeBolt MountPackage / Case3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Current Rating	250A
Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Voltage Rating - AC	1300V (1.3kV)
ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Voltage Rating - DC	-
FeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Response Time	-
Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Applications	Electrical, Industrial
ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Features	Indicating
Operating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Class	-
Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Approvals	CSA, UR
Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Operating Temperature	-
Package / Case Rectangular, Blade Size / Dimension 3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Breaking Capacity @ Rated Voltage	100kA
Size / Dimension 3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)	Mounting Type	Bolt Mount
	Package / Case	Rectangular, Blade
Report errors?	Size / Dimension	3.150" L x 2.087" W x 2.598" H (80.00mm x 53.00mm x 66.00mm)
		Report errors?

170M4240 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 170M4240, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com