

170M4364

170M4364 Information



For Reference Only

Part Number	170M4364	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE SQ 500A 700VAC RECTANGULAR	
Package	Rectangular, Blade	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



Request a Quote

170M4364 Specifications

Manufacturer Part Number170M4364ManufacturerEatonCategoryCircuit ProtectionBelectrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent RatingS00AVoltage Rating + DC-Voltage Rating + DC-Specialty Fuses-Stories-Voltage Rating + DC-Voltage Rating + DC-Specialty Fuses-Specialty Fus		
CategoryCircuit ProtectionBectrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating500AVoltage Rating - AC700VVoltage Rating - DC-ApplicationsElectrical, IndustrialApplicationsElectrical, IndustrialFeaturesIndicatingApprovalsSAURAOperating TemperatureSOAApprovalsSOAApprovalsSOAApprovalsSOAApprovalsSOAApprovalsSOAApprovalsSOAApprovalsSOAApprovalsSOAApprovalsSOAApprovalsSOAApplicationsSOAApprovalsSOAApplicationsSOAApprovalsSOAApprovalsSOAApprovalsSOAApprovalsSOAApplicationsSOAApplicationsSOAApplicationsSOAApplicationsSOAApplicationsSOAApplicationsSOAApplicationsSOAApplicationsSOAApplicationsSOAApplicationsSOAApplicationsSOAApplicationsSOAApplicationsSOAApplicationsSOAApplicationsSOAApplicationsSOAApplicationsSOAApplications	Manufacturer Part Number	170M4364
FieldElectrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating500AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969° L x 2,087° W x 2,717° H (50.00mm x 53.00mm x 69.00mm)	Manufacturer	Eaton
PackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating500AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating TemperatureSolokAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 59.00mm)	Category	Circuit Protection
Series-Fuse TypeSquareCurrent Rating500AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature200kAMounting TypeBolt MountPackage / CaseRectangula BaldeSize / Dimension1,609" L x 2,087" W x 2,717" H (50.00mm x 59.00mm)		Electrical, Specialty Fuses
Fuse TypeSquareFuse TypeSolACurrent RatingSolAVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated VoltageSolAMounting TypeBol MountPackage / CaseRectangulandSize / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 50.00mm)	Package	Rectangular, Blade
Current RatingSOAVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Beaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / Case.Size / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)	Series	-
Voltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated VoltageBolt MountPackage / CaseRectangularedSize / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)	Fuse Type	Square
Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage00kAMounting TypeBolt MountPackage / CaseRectangulandeSize / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 50.00mm x 50.00m	Current Rating	500A
Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)	Voltage Rating - AC	700V
ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 2,087" W x 2,717" H (50,00mm x 53,00mm x 69,00mm)	Voltage Rating - DC	-
FeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)	Response Time	-
Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 2,087" W x 2,717" H (50,00mm x 53,00mm x 69,00mm)	Applications	Electrical, Industrial
ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)	Features	Indicating
Operating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)	Class	-
Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)	Approvals	CSA, UR
Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)	Operating Temperature	-
Package / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 1.969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)	Mounting Type	Bolt Mount
	Package / Case	Rectangular, Blade
Report errors?	Size / Dimension	1.969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)
		Report errors?

170M4364 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 170M4364, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com