

170M6561

170M6561 Information



Part Number	170M6561	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE SQUARE 700A 700VAC	
Package	Rectangular, Blade	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



170M6561 Specifications

Manufacturer Part Number170M6561ManufacturerEatonCategoryCircuit ProtectionElectrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating700AVoltage Rating - ACC-Voltage Rating - DC-ApplicationsElectrical, IndustrialSeries-Approvals-Approvals-Approvals-Ourgent Rating - DC-ApplicationsElectrical, IndustrialCursent Rating-Approvals-Approvals-Approvals-Approvals-Approvals-Approvals-Approvals-Applications Pacteurer-Approvals-Approvals-Approvals-Approvals-Applications Pacteurer-Approvals-Approvals-Approvals-Approvals-Approvals-Approvals-Approvals-Approvals-Approvals-Approvals-Approvals-Approvals-Approvals-Approvals-Approvals-Approvals-Approvals-Approvals-Approvals- <tr< th=""><th></th><th></th></tr<>		
CategoryCircuit Protection Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareFuse Type700AVoltage Rating - AC700VVoltage Rating - DC-ApplicationsElectrical, IndustrialApplicationsElectrical, IndustrialClass-ApprovalsCSA, UROperating Temperature000ABreaking Capacity @ Rated Voltage200AAApprovalsElectrical, IndustrialOperating Temperature-ApticationsElectrical, IndustrialOperating Temperature-AprovalsCSA, URMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension200% L x 2.992" W x 3.622" H (51.00mm x 76.00mm x 92.00mm)	Manufacturer Part Number	170M6561
Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating700AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.622" H (51.00mm x 76.00mm x 92.00mm)	Manufacturer	Eaton
PackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating700AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.622" H (51.00mm x 76.00mm)	Category	Circuit Protection
Series-Fuse TypeSquareCurrent Rating700AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature200KABreaking Capacity @ Rated Voltage200KAMounting TypeHolderPackage / CaseScons" La Sugal, BladeSize / Dimension2008" L x 2.992" W x 3.622" H (51.00mm x 92.00mm)		Electrical, Specialty Fuses
Fuse TypeSquareFuse TypeSquareCurrent Rating700AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature200ABreaking Capacity @ Rated Voltage200AAMounting TypeHolderPackage / CaseRectanguland, BladeSize / Dimension2008" L x 2.992" W x 3.622" H (51.00mm x 92.00mm)	Package	Rectangular, Blade
Current Rating700AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated VoltageOlokAMounting TypeHolderPackage / CaseRectangulandSize / Dimension2,008" L x 2,992" W x 3,652" H (51,00mm x 9,00mm)	Series	-
Voltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature200kABreaking Capacity @ Rated VoltageHolderMounting TypeHolderPackage / CaseScose L x 2.992" W x 3.622" H (51.00mm x 92.00mm)	Fuse Type	Square
Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage00kAMounting TypeHolderPackage / CaseRectangulandeSize / Dimension2.008" L x 2.992" W x 3.622" H (51.00mm x 90.00mm x	Current Rating	700A
Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2,008" L x 2,992" W x 3,622" H (51,00mm x 92,00mm)	Voltage Rating - AC	700V
ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.622" H (51.00mm x 76.00mm x 92.00mm)	Voltage Rating - DC	-
FeaturesIndicatingFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2,008" L x 2.992" W x 3.622" H (51.00mm x 76.00mm x 92.00mm)	Response Time	-
Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2,008" L x 2.992" W x 3.622" H (51.00mm x 92.00mm)	Applications	Electrical, Industrial
ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.622" H (51.00mm x 76.00mm x 92.00mm)	Features	Indicating
Operating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.622" H (51.00mm x 76.00mm x 92.00mm)	Class	-
Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.622" H (51.00mm x 76.00mm x 92.00mm)	Approvals	CSA, UR
Mounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.622" H (51.00mm x 76.00mm x 92.00mm)	Operating Temperature	-
Package / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.622" H (51.00mm x 76.00mm x 92.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 2.008" L x 2.992" W x 3.622" H (51.00mm x 76.00mm x 92.00mm)	Mounting Type	Holder
	Package / Case	Rectangular, Blade
Report errors?	Size / Dimension	2.008" L x 2.992" W x 3.622" H (51.00mm x 76.00mm x 92.00mm)
		Report errors?

170M6561 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 170M6561, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com