

1865-03G-KDN

1865-03G-KDN Information

| www.helsener.com | Part Number | 1865-03G-KDN |
|--------------------|--------------|---|
| | Manufacturer | Honeywell Sensing and Productivity Solutions |
| | Category | Sensors, Transducers Pressure Sensors, Transducers |
| | Description | SENSOR FORCE/PRES 0-15PSIG 10VDC |
| | Package | 8-DIP Module |
| · · · | | For the pricing/inventory/lead time, please contact |
| For Reference Only | | us Website: https://www.heisener.com E-mail: salesdept@heisener.com |



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



1865-03G-KDN Specifications

| Manufacturer Part Number1865-03G-KDNManufacturerHoneywell Sensing and Productivity SolutionsCategorySensors, TransducersPressure Sensors, TransducersPressure Sensors, TransducersPackage8-DIP ModuleSeries1865Pressure TypeVented GaugeOutput TypeVented GaugeOutput TypeVented Sensors, TransducersOutput Sensors0 V ~ 7.5 VAccuracy±0.25%Voltage - Supply0 V ~ 15 VPort Size-Port SizeTemperature CompensatedTermination Style45 PSI (310.26 kPa)Operating Tenperature-28°C ~ 54°CPackage / Case-BIP ModulePort Super Sensore-28°C ~ 54°CPackage / Case-28°C ~ 54°CPackage / Cas | | | |
|---|--------------------------|---|--|
| CategorySensors, TransducersPackagePressure Sensors, TransducersPackage8-DIP ModuleSeries1865Pressure TypeVented GaugeOperating Pressure15 PSI (103.42 kPa)Output TypeWheatstone BridgeOutput Type0 V ~ 7.5 VAccuracy±0.25%Voltage - Supply0 V ~ 15 VPort Size-Port SyleTemperature CompensatedTermination Style45 PSI (310.26 kPa)Operating Temperature-8%°C ~ 54°CPackage / Case8-DIP ModuleSupplier Device Package- | Manufacturer Part Number | 1865-03G-KDN | |
| Pressure Sensors, TransducersPackage8-DIP ModuleSeries1865Pressure TypeVented GaugeOperating Pressure15 PSI (103.42 kPa)Output TypeWheatstone BridgeOutput0 V ~ 7.5 VAccuracy±0.25%Voltage - Supply0 V ~ 15 VPort Size-Port StyleMo PortFeaturesTemperature CompensatedTermination Style45 PSI (310.26 kPa)Operating Temperature-28°C ~ 54°CPackage / Case8-DIP ModuleSupplier Device Package- | Manufacturer | Honeywell Sensing and Productivity Solutions | |
| Package8-DIP ModuleSeries1865Pressure TypeVented GaugeOperating Pressure15 PSI (103.42 kPa)Output TypeWheatsone BridgeOutput Type0 V ~ 7.5 VAccuracy±0.25%Voltage - Supply0 V ~ 15 VPort Size-Port StyleNo PortFeaturesTemperature CompensatedTermination Style-Operating Temperature45 PSI (310.26 kPa)Operating Temperature-28°C ~ 54°CPackage / Case6. DIP ModuleSupplier Device Package- | Category | Sensors, Transducers | |
| Series1865Pressure TypeVented GaugeOperating Pressure15 PSI (103.42 kPa)Output TypeWheatstone BridgeOutput0 V ~ 7.5 VAccuracy±0.25%Voltage - Supply0 V ~ 15 VPort Size-Port StyleNo PortFeaturesTemperature CompensatedTermination Style-Operating Temperature28°C ~ 54°CPort Size-28°C ~ 54°CPort Size-Operating Temperature-Operating Temperature-Operating Temperature-Supplier Device Package-Supplier Device Package- | | Pressure Sensors, Transducers | |
| Pressure TypeVented GaugeOperating Pressure15 PSI (103.42 kPa)Output TypeWheatstone BridgeOutput Que0 V ~ 7.5 VAccuracy±0.25%Voltage - Supply0 V ~ 15 VPort Size-Port StyleNo PortFeaturesTemperature CompensatedPortanig Temperature45 PSI (310.26 kPa)Operating Temperature-28°C ~ 54°CPackage / Case-Supplier Device Package- | Package | 8-DIP Module | |
| Operating Pressure15 PSI (103.42 kPa)Output TypeWheatsone BridgeOutput0 V ~ 7.5 VAccuracy±0.25%Voltage - Supply0 V ~ 15 VPort Size-Port StyleNo PortFeaturesTemperature CompensatedTermination Style-Operating Temperature-S8°C ~ 54°CPackage / Case8-DIP ModuleSupplier Device Package- | Series | 1865 | |
| Output TypeWheatstone BridgeOutput0 V ~ 7.5 VAccuracy±0.25%Voltage - Supply0 V ~ 15 VPort Size-Port StyleNo PortFeaturesTemperature CompensatedTermination Style-Operating Temperature-28°C ~ 54°CPackage / Case8-DIP ModuleSupplier Device Package- | Pressure Type | Vented Gauge | |
| Output0 V ~ 7.5 VAccuracy±0.25%Voltage - Supply0 V ~ 15 VPort Size-Port StyleNo PortFeaturesTemperature CompensatedTermination Style-Operating Temperature-28°C ~ 54°CPackage / Case8-DIP ModuleSupplier Device Package- | Operating Pressure | 15 PSI (103.42 kPa) | |
| Accuracy±0.25%Voltage - Supply0 V ~ 15 VPort Size-Port StyleNo PortFeaturesTemperature CompensatedTermination Style-Operating Temperature45 PSI (310.26 kPa)Operating Temperature-28°C ~ 54°CPackage / Case8-DIP ModuleSupplier Device Package- | Output Type | Wheatstone Bridge | |
| Voltage - Supply0 V ~ 15 VPort Size-Port StyleNo PortFeaturesTemperature CompensatedTermination Style-Maximum Pressure45 PSI (310.26 kPa)Operating Temperature-28°C ~ 54°CPackage / Case8-DIP ModuleSupplier Device Package- | Output | 0 V ~ 7.5 V | |
| Port Size-Port StyleNo PortFeaturesTemperature CompensatedTermination Style-Maximum Pressure45 PSI (310.26 kPa)Operating Temperature-28°C ~ 54°CPackage / Case8-DIP ModuleSupplier Device Package- | Accuracy | ±0.25% | |
| Port StyleNo PortFeaturesTemperature CompensatedTermination Style-Maximum Pressure45 PSI (310.26 kPa)Operating Temperature-28°C ~ 54°CPackage / Case8-DIP ModuleSupplier Device Package- | Voltage - Supply | 0 V ~ 15 V | |
| FeaturesTemperature CompensatedTermination Style-Maximum Pressure45 PSI (310.26 kPa)Operating Temperature-28°C ~ 54°CPackage / Case8-DIP ModuleSupplier Device Package- | Port Size | - | |
| Termination Style-Maximum Pressure45 PSI (310.26 kPa)Operating Temperature-28°C ~ 54°CPackage / Case8-DIP ModuleSupplier Device Package- | Port Style | No Port | |
| Maximum Pressure45 PSI (310.26 kPa)Operating Temperature-28°C ~ 54°CPackage / Case8-DIP ModuleSupplier Device Package- | Features | Temperature Compensated | |
| Operating Temperature-28°C ~ 54°CPackage / Case8-DIP ModuleSupplier Device Package- | Termination Style | - | |
| Package / Case 8-DIP Module Supplier Device Package - | Maximum Pressure | 45 PSI (310.26 kPa) | |
| Supplier Device Package - | Operating Temperature | $-28^{\circ}\text{C} \sim 54^{\circ}\text{C}$ | |
| | Package / Case | 8-DIP Module | |
| Depart emerge | Supplier Device Package | - | |
| Kepont errors | | Report errors? | |

1865-03G-KDN Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

1865-03G-KDN Payment Methods





If you have any question about 1865-03G-KDN, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com