

18980-5PG-311 Information

Heisener.com

Part Number 18980-5PG-311

Manufacturer Conxall/Switchcraft

Category Connectors, Interconnects
Circular Connectors

Description CONN RCPT 5POS INLINE PIN

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









18980-5PG-311 Specifications

Manufacturer Part Number 18980-5PG-311 Manufacturer Conxall/Switchcraft Category Connectors, Interconnects Package - Series Micro-Con-X? Connector Type Receptacle, Male Pins Number of Positions 5 Shell Size - Insert - Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation B Ingress Protection 1P67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Gold Features Backshell Voltage - Rated 600VAC/DC Current Rating 4A		
CategoryConnectors, InterconnectsPackage-SeriesMicro-Con-X?Connector TypeReceptacle, Male PinsNumber of Positions5Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationBIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeaturesBackshellVoltage - Rated600VAC/DCCurrent Rating4A	Manufacturer Part Number	18980-5PG-311
Package-SeriesMicro-Con-X?Connector TypeReceptacle, Male PinsNumber of Positions5Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationBIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeaturesBackshellVoltage - Rated600VAC/DCCurrent Rating4A	Manufacturer	Conxall/Switchcraft
Package-SeriesMicro-Con-X?Connector TypeReceptacle, Male PinsNumber of Positions5Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationBIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeaturesBackshellVoltage - Rated600VAC/DCCurrent Rating4A	Category	Connectors, Interconnects
SeriesMicro-Con-X?Connector TypeReceptacle, Male PinsNumber of Positions5Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationBIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeaturesBackshellVoltage - Rated600VAC/DCCurrent Rating4A		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions5Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationBIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeaturesBackshellVoltage - Rated600V AC/DCCurrent Rating4A	Package	-
Number of Positions5Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationBIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeaturesBackshellVoltage - Rated600VAC/DCCurrent Rating4A	Series	Micro-Con-X?
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation B Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Gold Features Backshell Voltage - Rated Current Rating 4A	Connector Type	Receptacle, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation B Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Gold Features Backshell Voltage - Rated 600VAC/DC Current Rating	Number of Positions	5
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationBIngress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishThermoplasticContact FinishGoldFeaturesBackshellVoltage - Rated600VAC/DCCurrent Rating4A	Shell Size - Insert	-
Termination Crimp Fastening Type Bayonet Lock Orientation B Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Gold Features Backshell Voltage - Rated 600VAC/DC Current Rating 4A	Shell Size, MIL	-
Fastening Type Orientation B Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Contact Finish Gold Features Backshell Voltage - Rated 600VAC/DC Current Rating	Mounting Type	Free Hanging (In-Line)
Orientation B Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Thermoplastic Contact Finish Gold Features Backshell Voltage - Rated 600VAC/DC Current Rating 4A	Termination	Crimp
Ingress Protection Shell Material, Finish Contact Finish Gold Features Backshell Voltage - Rated Current Rating IP67 - Dust Tight, Waterproof Thermoplastic Gold 600VAC/DC 4A	Fastening Type	Bayonet Lock
Shell Material, FinishThermoplasticContact FinishGoldFeaturesBackshellVoltage - Rated600VAC/DCCurrent Rating4A	Orientation	В
Contact Finish Gold Features Backshell Voltage - Rated 600VAC/DC Current Rating 4A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features Backshell Voltage - Rated 600VAC/DC Current Rating 4A	Shell Material, Finish	Thermoplastic
Voltage - Rated 600VAC/DC Current Rating 4A	Contact Finish	Gold
Current Rating 4A	Features	Backshell
	Voltage - Rated	600VAC/DC
Report errors?	Current Rating	4A
		Report errors?

18980-5PG-311 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

18980-5PG-311 Payment Methods



















18980-5PG-311 Shipping Methods













If you have any question about 18980-5PG-311, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com