



# **1SMB24CAT3G Information**



For Reference Only

Part Number 1SMB24CAT3G
Manufacturer Littelfuse Inc.
Category Circuit Protection
TVS - Diodes

**Description** TVS DIODE 24VWM 38.9VC SMB

Package DO-214AA, SMB

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### **1SMB24CAT3G Specifications**

Manufacturer Part Number1SMB24CAT3GManufacturerLittelfuse Inc.CategoryCircuit ProtectionTVS - DiodesPackageDO-214AA, SMBSeriesAutomotive, AEC-Q101TypeZenerUnidirectional Channels-Bidirectional Channels1Voltage - Reverse Standoff (Typ)24VVoltage - Breakdown (Min)26.7VVoltage - Clamping (Max) @ Ipp38.9VCurrent - Peak Pulse (10/1000μs)15.4A
Category Circuit Protection TVS - Diodes  Package DO-214AA, SMB Series Automotive, AEC-Q101 Type Zener Unidirectional Channels - Bidirectional Channels 1 Voltage - Reverse Standoff (Typ) Voltage - Breakdown (Min) 26.7V Voltage - Clamping (Max) @ Ipp  Circuit Protection TVS - Diodes  DO-214AA, SMB Automotive, AEC-Q101  Zener  Zener  4 Voltage - Clamping (Max) @ Ipp
TVS - Diodes Package DO-214AA, SMB Series Automotive, AEC-Q101 Type Zener Unidirectional Channels Bidirectional Channels 1 Voltage - Reverse Standoff (Typ) 24V Voltage - Breakdown (Min) 26.7V Voltage - Clamping (Max) @ Ipp 38.9V
Package DO-214AA, SMB Series Automotive, AEC-Q101 Type Zener Unidirectional Channels - Bidirectional Channels 1 Voltage - Reverse Standoff (Typ) 24V Voltage - Breakdown (Min) 26.7V Voltage - Clamping (Max) @ Ipp 38.9V
Series Automotive, AEC-Q101 Type Zener Unidirectional Channels - Bidirectional Channels 1 Voltage - Reverse Standoff (Typ) 24V Voltage - Breakdown (Min) 26.7V Voltage - Clamping (Max) @ Ipp 38.9V
Type Zener Unidirectional Channels - Bidirectional Channels 1 Voltage - Reverse Standoff (Typ) 24V Voltage - Breakdown (Min) 26.7V Voltage - Clamping (Max) @ Ipp 38.9V
Unidirectional Channels - Bidirectional Channels 1 Voltage - Reverse Standoff (Typ) 24V Voltage - Breakdown (Min) 26.7V Voltage - Clamping (Max) @ Ipp 38.9V
Bidirectional Channels  Voltage - Reverse Standoff (Typ)  Voltage - Breakdown (Min)  26.7V  Voltage - Clamping (Max) @ Ipp  38.9V
Voltage - Reverse Standoff (Typ)24VVoltage - Breakdown (Min)26.7VVoltage - Clamping (Max) @ Ipp38.9V
Voltage - Breakdown (Min)  26.7V  Voltage - Clamping (Max) @ Ipp  38.9V
Voltage - Clamping (Max) @ Ipp 38.9V
Current - Peak Pulse (10/1000µs) 15.4A
Power - Peak Pulse 600W
Power Line Protection No
Applications Automotive
Capacitance @ Frequency 366pF @ 1MHz
Operating Temperature $-65^{\circ}\text{C} \sim 150^{\circ}\text{C} \text{ (TJ)}$
Mounting Type Surface Mount
Package / Case DO-214AA, SMB
Supplier Device Package SMB
Report errors

### **1SMB24CAT3G Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **1SMB24CAT3G Payment Methods**





















### **1SMB24CAT3G Shipping Methods**













If you have any question about 1SMB24CAT3G, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com