

21032412301

21032412301 Information

M Ca V. heterner.com Do	art Number lanufacturer ategory escription ackage	Connectors, Interconnects Circular Connectors CIRCULAR CONN W/HARAX M12 L 3 F - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



21032412301 Specifications

ManufacturerHARTINGCategoryConnectors, InterconnectsCircular ConnectorsPackage-SeriesHarax? M12-LConnector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - InsertM12-3Mounting TypeFree Hanging (In-Line)TerminationIDCFastening TypeThreadedOrientationBIngress ProtectionP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, Finish-Contact Finish32VYotage - Rated32VCurrent Rating4A		
CategoryConnectors, InterconnectsCircular ConnectorsPackage-SeriesHarax? M12-LConnector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - InsertM12-3Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationIDCFastening TypeThreadedOrientationBIngress ProtectionP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, Finish-Contact FinishStrain ReliefVoltage - Rated32VCurrent Rating4A	Manufacturer Part Number	21032412301
Circular ConnectorsPackage-SeriesHarax? M12-LConnector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - InsertM12-3Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationIDCFastening TypeThreadedOrientationBIngress ProtectionP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, Finish-FeaturesStrain ReliefVoltage - Rated32VCurrent Rating4A	Manufacturer	HARTING
Package-SeriesHara? M12-LConnector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - InsertM12-3Shell Size, MIL-Mouting TypeFree Hanging (In-Line)Mouting TypeIDCFastening TypeThreadedOrientationBIngress ProtectionP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, Finish-Contact FinishStrain ReliefVoltage - Rated32VCurrent Rating4A	Category	Connectors, Interconnects
SeriesHara? M12-LConnector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - InsertM12-3Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationIDCFastening TypeThreadedOrientationBIngress ProtectionP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, Finish-Contact Finish-FeaturesStrain ReliefVoltage - Rated32VCurrent Rating4A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - InsertM12-3Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationIDCFastening TypeThreadedOrientationBIngress ProtectionP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, Finish-Contact FinishStrain ReliefFeaturesStrain ReliefVoltage - Rated4A	Package	-
Number of Positions3Shell Size - InsertM12-3Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationIDCFastening TypeThreadedOrientationBIngress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, Finish-Contact Finish-FeaturesStrain ReliefVoltage - Rated32VCurrent Rating4A	Series	Harax? M12-L
Shell Size - InsertM12-3Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationIDCFastening TypeThreadedOrientationBIngress ProtectionP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, Finish-Contact Finish-FeaturesStrain ReliefVoltage - Rated32VCurrent Rating4A	Connector Type	Receptacle, Female Sockets
And PartShell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationIDCFastening TypeThreadedOrientationBIngress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, Finish-Contact Finish-FeaturesStrain ReliefVoltage - Rated32VCurrent Rating4A	Number of Positions	3
Mounting TypeFree Hanging (In-Line)TerminationIDCFastening TypeThreadedOrientationBIngress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, Finish-Contact Finish-FeaturesStrain ReliefVoltage - Rated32VCurrent Rating4A	Shell Size - Insert	M12-3
TerminationIDCFastening TypeThreadedOrientationBIngress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, Finish-Contact Finish-FeaturesStrain ReliefVoltage - Rated32VCurrent Rating4A	Shell Size, MIL	-
Fastening TypeThreadedOrientationBIngress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, Finish-Contact Finish-FeaturesStrain ReliefVoltage - Rated32VCurrent Rating4A	Mounting Type	Free Hanging (In-Line)
OrientationBIngress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, Finish-Contact Finish-FeaturesStrain ReliefVoltage - Rated32VCurrent Rating4A	Termination	IDC
Ingress ProtectionIP65/67 - Dust Tight, Water Resistant, WaterproofShell Material, Finish-Contact Finish-FeaturesStrain ReliefVoltage - Rated32VCurrent Rating4A	Fastening Type	Threaded
Shell Material, Finish-Contact Finish-FeaturesStrain ReliefVoltage - Rated32VCurrent Rating4A	Orientation	В
Contact Finish-FeaturesStrain ReliefVoltage - Rated32VCurrent Rating4A	Ingress Protection	IP65/67 - Dust Tight, Water Resistant, Waterproof
FeaturesStrain ReliefVoltage - Rated32VCurrent Rating4A	Shell Material, Finish	-
Voltage - Rated32VCurrent Rating4A	Contact Finish	-
Current Rating 4A	Features	Strain Relief
-	Voltage - Rated	32V
Report errors?	Current Rating	4A
		Report errors?

21032412301 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 21032412301, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com