

212045-1 Information



For Reference Only

Part Number 212045-1

Manufacturer TE Connectivity AMP Connectors

Category Connectors, Interconnects

Circular Connectors

Description CONN RECEPT 6POS SHIELD RT/A TIN

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









212045-1 Specifications

Manufacturer Part Number212045-1ManufacturerTE Connectivity AMP ConnectorsCategoryConnectors, InterconnectsPackage-Series-Connector TypeReceptacle, Female SocketsNumber of Positions6Shell Size - InsertDIN (240 Degree)Shell Size, MIL-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullOrientation-Ingress Protection-Shell Material, FinishNylonContact FinishTinFeaturesShieldedVoltage - Rated250VACCurrent Rating7.5A		
Category Connectors, Interconnects Circular Connectors Package - Series - Connector Type Receptacle, Female Sockets Number of Positions 6 Shell Size - Insert DIN (240 Degree) Shell Size, MIL - Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Orientation - Ingress Protection Shell Material, Finish Nylon Contact Finish Tin Features Shielded Voltage - Rated Current Rating 7,5A	Manufacturer Part Number	212045-1
Circular Connectors Package - Series - Connector Type Receptacle, Female Sockets Number of Positions 6 Shell Size - Insert DIN (240 Degree) Shell Size, MIL - Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Orientation - Ingress Protection - Shell Material, Finish Nylon Contact Finish Tin Features Shielded Voltage - Rated 250VAC Current Rating 7.5A	Manufacturer	TE Connectivity AMP Connectors
Package-Series-Connector TypeReceptacle, Female SocketsNumber of Positions6Shell Size - InsertDIN (240 Degree)Shell Size, MIL-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullOrientation-Ingress Protection-Shell Material, FinishNylonContact FinishTinFeaturesShieldedVoltage - Rated250VACCurrent Rating7.5A	Category	Connectors, Interconnects
Series - Connector Type Receptacle, Female Sockets Number of Positions 6 Shell Size - Insert DIN (240 Degree) Shell Size, MIL - Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Orientation - Ingress Protection - Shell Material, Finish Nylon Contact Finish Tin Features Shielded Voltage - Rated 250VAC Current Rating 7.5A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions6Shell Size - InsertDIN (240 Degree)Shell Size, MIL-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullOrientation-Ingress Protection-Shell Material, FinishNylonContact FinishTinFeaturesShieldedVoltage - Rated250VACCurrent Rating7.5A	Package	-
Number of Positions Shell Size - Insert DIN (240 Degree) Shell Size, MIL Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Orientation - Ingress Protection Shell Material, Finish Nylon Contact Finish Tin Features Shielded Voltage - Rated Current Rating 7.5A	Series	-
Shell Size - InsertDIN (240 Degree)Shell Size, MIL-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullOrientation-Ingress Protection-Shell Material, FinishNylonContact FinishTinFeaturesShieldedVoltage - Rated250VACCurrent Rating7.5A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Orientation - Ingress Protection - Shell Material, Finish Nylon Contact Finish Tin Features Shielded Voltage - Rated Current Rating 7.5A	Number of Positions	6
Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Orientation - Ingress Protection - Shell Material, Finish Nylon Contact Finish Tin Features Shielded Voltage - Rated 250VAC Current Rating 7.5A	Shell Size - Insert	DIN (240 Degree)
Termination Solder Fastening Type Push-Pull Orientation - Ingress Protection - Shell Material, Finish Nylon Contact Finish Tin Features Shielded Voltage - Rated 250VAC Current Rating 7.5A	Shell Size, MIL	-
Fastening Type Push-Pull Orientation - Ingress Protection - Shell Material, Finish Nylon Contact Finish Tin Features Shielded Voltage - Rated 250VAC Current Rating 7.5A	Mounting Type	Through Hole, Right Angle
Orientation - Ingress Protection - Shell Material, Finish Nylon Contact Finish Tin Features Shielded Voltage - Rated 250VAC Current Rating 7.5A	Termination	Solder
Ingress Protection - Shell Material, Finish Nylon Contact Finish Tin Features Shielded Voltage - Rated 250VAC Current Rating 7.5A	Fastening Type	Push-Pull
Shell Material, FinishNylonContact FinishTinFeaturesShieldedVoltage - Rated250VACCurrent Rating7.5A	Orientation	-
Contact Finish Tin Features Shielded Voltage - Rated Current Rating 7.5A	Ingress Protection	-
Features Shielded Voltage - Rated 250VAC Current Rating 7.5A	Shell Material, Finish	Nylon
Voltage - Rated 250VAC Current Rating 7.5A	Contact Finish	Tin
Current Rating 7.5A	Features	Shielded
•	Voltage - Rated	250VAC
Report errors?	Current Rating	7.5A
		Report errors?

212045-1 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

212045-1 Payment Methods



















212045-1 Shipping Methods













If you have any question about 212045-1, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com