



226PUM050M Information



For Reference Only

Part Number 226PUM050M Manufacturer Illinois Capacitor

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 22UF 20% 50V THRU HOLE

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









226PUM050M Specifications

Manufacturer Part Number226PUM050MManufacturerIllinois CapacitorCategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesPUMCapacitance22μFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)7.536 Ohm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°C
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series PUM Capacitance 22μF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) 7.536 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C
$\begin{array}{cccccccccccccccccccccccccccccccccccc$
PackageRadial, CanSeriesPUMCapacitance $22μF$ Tolerance $±20%$ Voltage - Rated $50V$ ESR (Equivalent Series Resistance) 7.536 Ohm @ $120Hz$ Lifetime @ Temp. 2000 Hrs @ 85 °C
$\begin{array}{cccccccccccccccccccccccccccccccccccc$
Capacitance $22μF$ Tolerance $±20%$ Voltage - Rated $50V$ ESR (Equivalent Series Resistance) 7.536 Ohm @ $120Hz$ Lifetime @ Temp. 2000 Hrs @ 85 °C
Tolerance $\pm 20\%$ Voltage - Rated $50V$ ESR (Equivalent Series Resistance) $7.536 \text{ Ohm } @ 120\text{Hz}$ Lifetime @ Temp. $2000 \text{ Hrs } @ 85^{\circ}\text{C}$
Voltage - Rated 50V ESR (Equivalent Series Resistance) 7.536 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C
ESR (Equivalent Series Resistance) 7.536 Ohm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C
Lifetime @ Temp. 2000 Hrs @ 85°C
Operating Temperature
Operating Temperature -40 C ~ 65 C
Polarization Polar
Applications General Purpose
Ripple Current - Low Frequency 58mA @ 120Hz
Ripple Current - High Frequency 87mA @ 10kHz
Impedance -
Lead Spacing 0.098" (2.50mm)
Size / Dimension 0.248" Dia (6.30mm)
Height - Seated (Max) 0.315" (8.00mm)
Surface Mount Land Size -
Mounting Type Through Hole
Package / Case Radial, Can
Report errors?

226PUM050M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

226PUM050M Payment Methods



















226PUM050M Shipping Methods













If you have any question about 226PUM050M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com