



251R14S220KV4T Information



For Reference Only

Part Number 251R14S220KV4T

Manufacturer Johanson Technology Inc.

Category Capacitors

Ceramic Capacitors

Description CAP CER 22PF 250V NP0 0603

Package 0603 (1608 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









251R14S220KV4T Specifications

Manufacturer Part Number 251R14S220KV4T Manufacturer Johanson Technology Inc. Category Capacitors Package 0603 (1608 Metric) Series S Capacitance 22pF Tolerance ±10% Voltage - Rated 250V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.062" L x 0.032" W (1.57mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.89mm) Lead Spacing - Lead Style -		
Category Capacitors Package 0603 (1608 Metric) Series S Capacitance 22pF Tolerance ±10% Voltage - Rated 250V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.062" L x 0.032" W (1.57mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.89mm) Lead Spacing - Lead Style -	Manufacturer Part Number	251R14S220KV4T
Package 0603 (1608 Metric) Series S Capacitance 22pF Tolerance ±10% Voltage - Rated 250V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.062" L x 0.032" W (1.57mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.89mm) Lead Spacing - Lead Style -	Manufacturer	Johanson Technology Inc.
Package 0603 (1608 Metric) Series S Capacitance 22pF Tolerance ±10% Voltage - Rated 250V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.062" L x 0.032" W (1.57mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.89mm) Lead Spacing - Lead Style -	Category	Capacitors
Series S Capacitance 22pF Tolerance ±10% Voltage - Rated 250V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.062" L x 0.032" W (1.57mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.89mm) Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 22pF Tolerance ±10% Voltage - Rated 250V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.062" L x 0.032" W (1.57mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.89mm) Lead Spacing - Lead Style -	Package	0603 (1608 Metric)
Tolerance ±10% Voltage - Rated 250V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.062" L x 0.032" W (1.57mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.89mm) Lead Spacing - Lead Style -	Series	S
Voltage - Rated250VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh Q, Low LossRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0603 (1608 Metric)Size / Dimension0.062" L x 0.032" W (1.57mm x 0.81mm)Height - Seated (Max)-Thickness (Max)0.035" (0.89mm)Lead Spacing-Lead Style-	Capacitance	22pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.062" L x 0.032" W (1.57mm x 0.81mm) Height - Seated (Max) Thickness (Max) 0.035" (0.89mm) Lead Spacing - Lead Style -	Tolerance	±10%
Operating Temperature -55°C ~ 125°C Features High Q, Low Loss Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.062" L x 0.032" W (1.57mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.89mm) Lead Spacing - Lead Style -	Voltage - Rated	250V
Features High Q, Low Loss Ratings - RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.062" L x 0.032" W (1.57mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.89mm) Lead Spacing - Lead Style - Company of the state of	Temperature Coefficient	C0G, NP0
Ratings - Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.062" L x 0.032" W (1.57mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.89mm) Lead Spacing - Lead Style -	Operating Temperature	-55°C ~ 125°C
Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.062" L x 0.032" W (1.57mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.89mm) Lead Spacing - Lead Style -	Features	High Q, Low Loss
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.062" L x 0.032" W (1.57mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.89mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 0603 (1608 Metric) Size / Dimension 0.062" L x 0.032" W (1.57mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.89mm) Lead Spacing - Lead Style -	Applications	RF, Microwave, High Frequency
Package / Case 0603 (1608 Metric) Size / Dimension 0.062" L x 0.032" W (1.57mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.89mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.062" L x 0.032" W (1.57mm x 0.81mm) Height - Seated (Max) - Thickness (Max) 0.035" (0.89mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) - Thickness (Max) 0.035" (0.89mm) Lead Spacing - Lead Style -	Package / Case	0603 (1608 Metric)
Thickness (Max) 0.035" (0.89mm) Lead Spacing - Lead Style -	Size / Dimension	0.062" L x 0.032" W (1.57mm x 0.81mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.035" (0.89mm)
·	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

251R14S220KV4T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

251R14S220KV4T Payment Methods



















251R14S220KV4T Shipping Methods













If you have any question about 251R14S220KV4T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com