



26PCGNM6G Information



For Reference Only

Part Number 26PCGNM6G

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR PRESS GAUGE 250PSI

Package 4-SIP Module

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









26PCGNM6G Specifications

Manufacturer Part Number $26PCGNM6G$ ManufacturerHoneywell Sensing and Productivity SolutionsCategorySensors, TransducersPackage4-SIP ModuleSeries $26PC$ Pressure TypeCompoundOperating Pressure ± 250 PSI (± 1723.69 kPa)Output TypeWheatstone BridgeOutput 0 mV ~ 150 mV (10 V)Accuracy $\pm 0.7\%$ Voltage - Supply 2.5 V ~ 16 VPort SizeMale - $1/4$ " (6.35 mm) UNF
Category Sensors, Transducers Pressure Sensors, Transducers Package 4-SIP Module Series 26PC Pressure Type Compound Operating Pressure ±250 PSI (±1723.69 kPa) Output Type Wheatstone Bridge Output O
Pressure Sensors, Transducers Package 4-SIP Module Series 26PC Pressure Type Compound Operating Pressure
Package 4-SIP Module Series 26PC Pressure Type Compound Operating Pressure ±250 PSI (±1723.69 kPa) Output Type Wheatstone Bridge Output 0 mV ~ 150 mV (10V) Accuracy ±0.7% Voltage - Supply 2.5 V ~ 16 V Port Size Male - 1/4" (6.35mm) UNF
Series $26PC$ Pressure TypeCompoundOperating Pressure $\pm 250 \text{ PSI } (\pm 1723.69 \text{ kPa})$ Output TypeWheatstone BridgeOutput $0 \text{ mV} \sim 150 \text{ mV } (10\text{V})$ Accuracy $\pm 0.7\%$ Voltage - Supply $2.5 \text{ V} \sim 16 \text{ V}$ Port SizeMale - $1/4$ " (6.35mm) UNF
Pressure Type Compound Operating Pressure $\pm 250 \text{ PSI } (\pm 1723.69 \text{ kPa})$ Output Type Wheatstone Bridge Output $0 \text{ mV} \sim 150 \text{ mV} (10 \text{ V})$ Accuracy $\pm 0.7\%$ Voltage - Supply $\pm 0.7\%$ Port Size Male - 1/4" (6.35mm) UNF
Operating Pressure $ \begin{array}{ll} \pm 250 \ \mathrm{PSI} \ (\pm 1723.69 \ \mathrm{kPa}) \\ \\ \mathrm{Output} \ \mathrm{Type} & \mathrm{Wheatstone} \ \mathrm{Bridge} \\ \\ \mathrm{Output} & 0 \ \mathrm{mV} \sim 150 \ \mathrm{mV} \ (10\mathrm{V}) \\ \\ \mathrm{Accuracy} & \pm 0.7\% \\ \\ \mathrm{Voltage} \ - \ \mathrm{Supply} & 2.5 \ \mathrm{V} \sim 16 \ \mathrm{V} \\ \\ \mathrm{Port} \ \mathrm{Size} & \mathrm{Male} \ - \ 1/4'' \ (6.35\mathrm{mm}) \ \mathrm{UNF} \\ \end{array} $
Output TypeWheatstone BridgeOutput $0 \text{ mV} \sim 150 \text{ mV} (10\text{V})$ Accuracy $\pm 0.7\%$ Voltage - Supply $2.5 \text{ V} \sim 16 \text{ V}$ Port SizeMale - $1/4$ " (6.35mm) UNF
Output $0 \text{ mV} \sim 150 \text{ mV} (10\text{V})$ Accuracy $\pm 0.7\%$ Voltage - Supply $2.5 \text{ V} \sim 16 \text{ V}$ Port Size Male - 1/4" (6.35mm) UNF
Accuracy $\pm 0.7\%$ Voltage - Supply $2.5 \text{ V} \sim 16 \text{ V}$ Port Size Male - 1/4" (6.35mm) UNF
Voltage - Supply $2.5 \text{ V} \sim 16 \text{ V}$ Port Size $\text{Male - 1/4" (6.35 \text{mm}) UNF}$
Port Size Male - 1/4" (6.35mm) UNF
Port Style Threaded
Features Temperature Compensated
Termination Style PC Pin
Maximum Pressure ±500 PSI (±3447.38 kPa)
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$
Package / Case 4-SIP Module
Supplier Device Package -
Report errors 2

26PCGNM6G Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

26PCGNM6G Payment Methods



















26PCGNM6G Shipping Methods













If you have any question about 26PCGNM6G, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com