

## 3-1393818-3 Information

Heisener.com

**Part Number** 3-1393818-3

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Signal Relays, Up to 2 Amps

**Description** RELAY GEN PURPOSE DPDT 2A 20V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## 3-1393818-3 Specifications

Manufacturer Part Number     3-1393818-3       Manufacturer     TE Connectivity Potter & Brumfield Relays       Category     Relays       Package     -       Series     V23162, AXICOM       Relay Type     General Purpose       Coil Type     Non Latching       Coil Current     36.3mA       Coil Voltage     20VDC       Contact Form     DPDT (2 Form C)       Contact Rating (Current)     2A       Switching Voltage     125VAC, 150VDC - Max       Turn On Voltage (Max)     8.9 VDC       Turn Off Voltage (Min)     -       Operate Time     7.5ms       Release Time     3ms       Features     Sealed - Hermetically       Mounting Type     Socketable       Termination Style     Plug In		
CategoryRelaysPackage-SeriesV23162, AXICOMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current36.3mACoil Voltage20VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 150VDC - MaxTurn On Voltage (Max)8.9 VDCTurn Off Voltage (Min)-Operate Time7.5msRelease Time3msFeaturesSealed - HermeticallyMounting TypeSocketableTermination StylePlug In	Manufacturer Part Number	3-1393818-3
Package-SeriesV23162, AXICOMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current36.3mACoil Voltage20VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 150VDC - MaxTurn On Voltage (Max)8.9 VDCTurn Off Voltage (Min)-Operate Time7.5msRelease Time3msFeaturesSealed - HermeticallyMounting TypeSocketableTermination StylePlug In	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package         -           Series         V23162, AXICOM           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         36.3mA           Coil Voltage         20VDC           Contact Form         DPDT (2 Form C)           Contact Rating (Current)         2A           Switching Voltage         125VAC, 150VDC - Max           Turn On Voltage (Max)         8.9 VDC           Turn Off Voltage (Min)         -           Operate Time         7.5ms           Release Time         3ms           Features         Sealed - Hermetically           Mounting Type         Socketable           Termination Style         Plug In	Category	Relays
SeriesV23162, AXICOMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current36.3mACoil Voltage20VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 150VDC - MaxTurn On Voltage (Max)8.9 VDCTurn Off Voltage (Min)-Operate Time7.5msRelease Time3msFeaturesSealed - HermeticallyMounting TypeSocketableTermination StylePlug In		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current36.3mACoil Voltage20VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 150VDC - MaxTurn On Voltage (Max)8.9 VDCTurn Off Voltage (Min)-Operate Time7.5msRelease Time3msFeaturesSealed - HermeticallyMounting TypeSocketableTermination StylePlug In	Package	-
Coil Type Non Latching Coil Current 36.3mA Coil Voltage 20VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 150VDC - Max Turn On Voltage (Max) 8.9 VDC Turn Off Voltage (Min) - Operate Time 7.5ms Release Time 3ms Features Sealed - Hermetically Mounting Type Socketable Termination Style Plug In	Series	V23162, AXICOM
Coil Current36.3mACoil Voltage20VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 150VDC - MaxTurn On Voltage (Max)8.9 VDCTurn Off Voltage (Min)-Operate Time7.5msRelease Time3msFeaturesSealed - HermeticallyMounting TypeSocketableTermination StylePlug In	Relay Type	General Purpose
Coil Voltage 20VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 150VDC - Max Turn On Voltage (Max) 8.9 VDC Turn Off Voltage (Min) - Operate Time 7.5ms Release Time 3ms Features Sealed - Hermetically Mounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form DPDT (2 Form C)  Contact Rating (Current)  Switching Voltage  125VAC, 150VDC - Max  Turn On Voltage (Max)  8.9 VDC  Turn Off Voltage (Min)  Operate Time  7.5ms  Release Time  3ms  Features  Sealed - Hermetically  Mounting Type  Socketable  Termination Style	Coil Current	36.3mA
Contact Rating (Current)  Switching Voltage  125VAC, 150VDC - Max  Turn On Voltage (Max)  8.9 VDC  Turn Off Voltage (Min)  Operate Time  7.5ms  Release Time  3ms  Features  Sealed - Hermetically  Mounting Type  Socketable  Termination Style  Plug In	Coil Voltage	20VDC
Switching Voltage 125VAC, 150VDC - Max  Turn On Voltage (Max) 8.9 VDC  Turn Off Voltage (Min) - Operate Time 7.5ms  Release Time 3ms  Features Sealed - Hermetically  Mounting Type Socketable  Termination Style Plug In	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  7.5ms  Release Time  3ms  Features  Sealed - Hermetically  Mounting Type  Socketable  Termination Style  8.9 VDC	Contact Rating (Current)	2A
Turn Off Voltage (Min)  Operate Time  7.5ms  Release Time  3ms  Features  Sealed - Hermetically  Mounting Type  Socketable  Termination Style  Plug In	Switching Voltage	125VAC, 150VDC - Max
Operate Time 7.5ms  Release Time 3ms  Features Sealed - Hermetically  Mounting Type Socketable  Termination Style Plug In	Turn On Voltage (Max)	8.9 VDC
Release Time 3ms Features Sealed - Hermetically Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	-
Features Sealed - Hermetically  Mounting Type Socketable  Termination Style Plug In	Operate Time	7.5ms
Mounting Type Socketable Termination Style Plug In	Release Time	3ms
Termination Style Plug In	Features	Sealed - Hermetically
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
Top or on one		Report errors?

#### 3-1393818-3 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **3-1393818-3 Payment Methods**





















## **3-1393818-3 Shipping Methods**













If you have any question about 3-1393818-3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com