

346-87-138-41-036101

346-87-138-41-036101 Information



E-mail: salesdept@heisener.com

Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



346-87-138-41-036101 Specifications

Manufacturer Part Number346-87-138-41-036101ManufacturerPreci-DipCategoryConnectors, InterconnectsPackage-Package346Connector TypeSocketContact TypeSocketContact TypeBoard to BoardNumber of Positions LoadedAllPitch - Mating0.100° (2.54mm)Number of Rows1Row Spacing - MatingProse-Fit, SolderMounting TypeDrough HoleContact Finish - MatingGoldNumber of PositionsAllPitch - Mating0.100° (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeBrough HoleContact Finish - MatingOddFastening TypeInfough HoleContact Finish - MatingGoldInsulation ColorBlackInsulation Finish - MatingInfouContact Finish PostJino' (2.79mm)Contact Length - Post0.110° (2.79mm)Contact Length - Post0.110° (2.79mm)Contact Finish TypeSolderInsulation ColorBlackContact Finish TypeSolderContact Finish TypeSolderSolderSolderContact Finish TypeSolderContact Finish TypeSolderContact Finish TypeSolderContact Finish TypeSolderContact Finish TypeSolderContact Finish TypeSolderContact Length - PostSolderCont		
CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-Series346Connector TypeSocketContact TypeBoard to BoardNumber of Positions38Number of Positions LoadedAllNumber of Rows1Number of Rows1Number of Rows1Number of Rows9Number of Rows1Number of Rows9Stating TypePress-Fit, SolderNounting TypeSoldContact Finish - MatingGoldContact Finish - MatingGoldInsulation ColorBackInsulation FieldsN173" (4.40mm)Insulation Height0.110" (2.79mm)Operating Temperature55°C ~ 125°C	Manufacturer Part Number	346-87-138-41-036101
AckageRectangular Connectors - Headers, Receptacles, Female SocketsPackage-Series346Connector TypeSocketContact TypeFemale SocketStyleBoard to BoardNumber of Positions38Number of Positions LoadedAllPitch - Mating0.100° (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationPress-Fit, SolderFastening TypeQuidContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.110° (2.79mm)Contact Length - Post0.110° (2.79mm)	Manufacturer	Preci-Dip
Package.Series346Connector TypeSocketContact TypeFemale SocketStyleBoard to BoardNumber of Positions38Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationPress-Fit, SolderGotact Finish - MatingGoldContact Finish - MatingGoldContact Finish - MatingHashInsulation ColorBlackInsulation Height0.173" (4.40mm)Contact Length - Post0.110" (2.79mm)Operating Temperature-55°C ~ 125°C	Category	Connectors, Interconnects
Series346Connector TypeSocketContact TypeFemale SocketStyleBoard to BoardNumber of Positions38Number of Positions LoadedAllPitch - Mating0.100° (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationPress-Fit, SolderContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.107° (2.79mm)Operating Temperature55°C ~ 125°C		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeSocketContact TypeFemale SocketStyleBoard to BoardNumber of Positions38Number of Positions LoadedAllPitch - Mating0.100° (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationPress-Fit, SolderContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.10° (2.79mm)Operating Temperature55°C ~ 125°C	Package	-
Contact TypeFemale SocketStyleBoard to BoardNumber of Positions38Number of Positions LoadedAllPitch - Mating0.100° (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationPress-Fit, SolderFastening TypeSoldContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.173° (4.40mm)Contact Length - Post0.110° (2.79mm)Operating Temperature-55°C ~ 125°C	Series	346
StyleBoard to BoardStyleBoard to BoardNumber of Positions38Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationPress-Fit, SolderFastening Type9ush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.173" (4.40mm)Contact Length - Post0.110" (2.79mm)Operating Temperature-55°C ~ 125°C	Connector Type	Socket
Number of Positions38Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationPress-Fit, SolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.173" (4.40mm)Contact Length - Post0.110" (2.79mm)Operating Temperature-55°C ~125°C	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationPress-Fit, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.110" (2.79mm)Operating Temperature-55°C ~ 125°C	Style	Board to Board
Pitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationPress-Fit, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingBlackInsulation Color0.173" (4.40mm)Contact Length - Post0.110" (2.79mm)Operating Temperature-55°C ~ 125°C	Number of Positions	38
Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationPress-Fit, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.113" (4.40mm)Contact Length - Post55°C ~ 125°C	Number of Positions Loaded	All
Row Spacing - Mating-Mounting TypeThrough HoleTerminationPress-Fit, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.173" (4.40mm)Contact Length - Post0.110" (2.79mm)Operating Temperature-55°C ~ 125°C	Pitch - Mating	0.100" (2.54mm)
Mounting TypeThrough HoleTerminationPress-Fit, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.173" (4.40mm)Contact Length - Post0.110" (2.79mm)Operating Temperature-55°C ~ 125°C	Number of Rows	1
TerminationPress-Fit, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.173" (4.40mm)Contact Length - Post0.110" (2.79mm)Operating Temperature-55°C ~ 125°C	Row Spacing - Mating	-
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.173" (4.40mm)Contact Length - Post0.110" (2.79mm)Operating Temperature-55°C ~ 125°C	Mounting Type	Through Hole
Contact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.173" (4.40mm)Contact Length - Post0.110" (2.79mm)Operating Temperature-55°C ~ 125°C	Termination	Press-Fit, Solder
Contact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.173" (4.40mm)Contact Length - Post0.110" (2.79mm)Operating Temperature-55°C ~ 125°C	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height0.173" (4.40mm)Contact Length - Post0.110" (2.79mm)Operating Temperature-55°C ~ 125°C	Contact Finish - Mating	Gold
Insulation Height0.173" (4.40mm)Contact Length - Post0.110" (2.79mm)Operating Temperature-55°C ~ 125°C	Contact Finish Thickness - Mating	Flash
Contact Length - Post0.110" (2.79mm)Operating Temperature-55°C ~ 125°C	Insulation Color	Black
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Insulation Height	0.173" (4.40mm)
	Contact Length - Post	0.110" (2.79mm)
	Operating Temperature	-55°C ~ 125°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?





Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 346-87-138-41-036101, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com