

357-015-532-102

357-015-532-102 Information

Heisener.com	Part Number Manufacturer Category Description Package	357-015-532-102 EDAC Inc. Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN FEMALE 15POS 0.156 GOLD - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



357-015-532-102 Specifications

ManufacturerEDAC Inc.Cardecors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Package357Card Type-GenderFemaleNumber of Positions/Bay/Row15Number of Positions0.062" (1.57mm)Number of Rows-Pactares0.062" (1.57mm)Features0.156" (3.96mm)Features-Mounting Type-Contact MaterialCoppen, Nickel, Tin AlloyContact Finish Thickness-Contact Finish Thickness-Contact Type-Contact Type-Contact Type-Contact Finish Thickness-Contact Type-Contact Typ			
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Package357Card Type-GenderFemaleNumber of Positions/Bay/Row15Card Thickness0.062" (1.57mm)Number of Rows-Pitch0.156" (3.96mm)Features-Mounting Type-Contact MaterialCopper, Nickel, Tin AlloyContact Finish Thickness-Contact Finish Thickness-Contact Type-Contact Type- <td>Manufacturer Part Number</td> <td>357-015-532-102</td> <td></td>	Manufacturer Part Number	357-015-532-102	
Indext and the second	Manufacturer	EDAC Inc.	
Package-Series357Card Type-GenderFemaleNumber of Positions/Bay/Row15Card Thickness0.062" (1.57mm)Number of Rows-Pitch0.156" (3.96mm)Features-Mounting Type-Contact MaterialCoper, Nickel, Tin AlloyContact Finish Thickness-Contact Finish Thickness-Contact Type-Contact Type- <t< td=""><td>Category</td><td>Connectors, Interconnects</td><td></td></t<>	Category	Connectors, Interconnects	
Series357Card Type-GenderFemaleNumber of Positions/Bay/Row15Number of Positions-Card Thickness0.062" (1.57mm)Number of Rows-Pitch0.156" (3.96mm)Features-Mounting Type-Contact FinishCopper, Nickel, Tin AlloyContact Finish Thickness-Contact Finish Thickness-Contact Type-Contact Type-Contact Type-Contact Type-Contact Type-Contact Type-Contact Type-ColorBlackFlange Feature-u0°C ~ 105°C		Card Edge Connectors - Edgeboard Connectors	
Card Type.GenderFemaleNumber of Positions/Bay/Row15Number of Positions.Card Thickness0.062" (1.57mm)Number of Rows.Number of Rows.Pitch0.156" (3.96mm)Features.Mounting Type.Contact MaterialCopper, Nickel, Tin AlloyContact Finish Thickness.Contact Finish Thickness.Contact Type.Pitage FeatureBlackFunge Features.Operating Temperature.40°C ~ 105°C	Package	-	
GenderFemaleNumber of Positions/Bay/Row15Number of Positions-Card Thickness0.062" (1.57mm)Number of Rows-Number of Rows0.156" (3.96mm)Pitch0.156" (3.96mm)Features-Mounting Type-Otanta Type-Contact FinishCoper, Nickel, Tin AlloyContact Finish-Contact Finish Thickness-Contact Type-Pinape FeatureBiakFinape FeatureHow Mount, Top Opening, Untergeat, O.128" (3.25mm) DiaOperating Temperature440° < 105°C	Series	357	
Number of Positions/Bay/Row15Number of Positions-Card Thickness0.062" (1.57mm)Number of Rows-Pitch0.156" (3.96mm)Features-Mounting Type-Contact MaterialCopper, Nickel, Tin AlloyContact Finish Thickness-Contact Finish Thickness-Contact Spee-Contact Finish Thickness-Contact Finish Thickness-ColorBlackFlange Feature-40°C ~ 105°C	Card Type	-	
Number of Positions - Card Thickness 0.062" (1.57mm) Number of Rows - Number of Rows - Pitch 0.156" (3.96mm) Features - Mounting Type - Mounting Type - Contact Material Copper, Nickel, Tin Alloy Contact Finish Gold Contact Type - Color Black Flange Feature Hush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) Dia Operating Temperature -40°C ~ 015°C	Gender	Female	
Card Thickness0.062" (1.57mm)Number of Rows-Pitch0.156" (3.96mm)Features-Mounting Type-Termination-Contact MaterialCopper, Nickel, Tin AlloyContact Finish Thickness-Contact Type-ColorBlackFlange Feature-Operating Temperature-40°C ~ 105°C	Number of Positions/Bay/Row	15	
Number of Rows-Pitch0.156" (3.96mm)Features-Mounting Type-Mounting Type-Contact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Finish Thickness-Contact Type-ColorBlackFlange Feature-Operating Temperature-40°C ~ 105°C	Number of Positions	-	
Pitch0.156" (3.96mm)Features-Mounting Type-Termination-Contact MaterialCoper, Nickel, Tin AlloyContact Finish ThicknessGoldContact Finish Thickness-Contact Type-ColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-40°C ~ 105°C	Card Thickness	0.062" (1.57mm)	
Features-Mounting Type-Mounting Type-Termination-Contact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Finish Thickness-Contact Type-ColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-40°C ~ 105°C	Number of Rows	-	
Mounting Type-Termination-Contact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Finish Thickness-Contact Type-ColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-40°C ~ 105°C	Pitch	0.156" (3.96mm)	
Termination-Contact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Finish Thickness-Contact Type-ColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-40°C ~ 105°C	Features	-	
Contact MaterialCopper, Nickel, Tin AlloyContact FinishGoldContact Finish Thickness-Contact Type-ColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-40°C ~ 105°C	Mounting Type	-	
Contact FinishGoldContact Finish Thickness-Contact Type-ColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-40°C ~ 105°C	Termination	-	
Contact Finish Thickness-Contact Type-ColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-40°C ~ 105°C	Contact Material	Copper, Nickel, Tin Alloy	
Contact Type-ColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-40°C ~ 105°C	Contact Finish	Gold	
ColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-40°C ~ 105°C	Contact Finish Thickness	-	
Flange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-40°C ~ 105°C	Contact Type	-	
Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Color	Black	
	Flange Feature	Flush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) Dia	
Report errors?	Operating Temperature	$-40^{\circ}C \sim 105^{\circ}C$	
			Report errors?

357-015-532-102 Guarantees



Quality Guarantees


We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

357-015-532-102 Payment Methods





If you have any question about 357-015-532-102, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com