



3640AA103JATBE Information



For Reference Only

Part Number 3640AA103JATBE
Manufacturer AVX Corporation
Category Capacitors

Capacitors
Ceramic Capacitors

Description CAP CER 10000PF 1KV NP0 3640

Package 3640 (9110 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









3640AA103JATBE Specifications

Category Capacitors Package 3640 (9110 Metric) Series - Capacitance 10000pF Tolerance ±5% Voltage - Rated 1000V (1kV) Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 3640 (9110 Metric) Size / Dimension 0.360" L x 0.402" W (9.14mm x 10.20mm) Height - Seated (Max) - Thickness (Max) 0.100" (2.54mm) Lead Spacing -		
Category Capacitors Package 3640 (9110 Metric) Series - Capacitance 10000pF Tolerance ±5% Voltage - Rated 1000V (1kV) Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 3640 (9110 Metric) Size / Dimension 0.360" L x 0.402" W (9.14mm x 10.20mm) Height - Seated (Max) - Thickness (Max) 0.100" (2.54mm) Lead Spacing - Lead Style -	Manufacturer Part Number	3640AA103JATBE
Package 3640 (9110 Metric) Series - Capacitance 10000pF Tolerance ±5% Voltage - Rated 1000V (1kV) Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 3640 (9110 Metric) Size / Dimension 0.360" L x 0.402" W (9.14mm x 10.20mm) Height - Seated (Max) - Thickness (Max) 0.100" (2.54mm) Lead Spacing - Lead Style -	Manufacturer	AVX Corporation
Package 3640 (9110 Metric) Series - Capacitance 10000pF Tolerance ±5% Voltage - Rated 1000V (1kV) Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 3640 (9110 Metric) Size / Dimension 0.360" L x 0.402" W (9.14mm x 10.20mm) Height - Seated (Max) - Thickness (Max) 0.100" (2.54mm) Lead Spacing - Lead Style -	Category	Capacitors
Series - Capacitance 10000pF Tolerance ±5% Voltage - Rated 1000V (1kV) Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 3640 (9110 Metric) Size / Dimension 0.360" L x 0.402" W (9.14mm x 10.20mm) Height - Seated (Max) - Thickness (Max) 0.100" (2.54mm) Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 10000pF Tolerance ±5% Voltage - Rated 1000V (1kV) Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 3640 (9110 Metric) Size / Dimension 0.360" L x 0.402" W (9.14mm x 10.20mm) Height - Seated (Max) - Thickness (Max) 0.100" (2.54mm) Lead Spacing - Lead Style -	Package	3640 (9110 Metric)
Tolerance ±5% Voltage - Rated 1000V (1kV) Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 3640 (9110 Metric) Size / Dimension 0.360" L x 0.402" W (9.14mm x 10.20mm) Height - Seated (Max) - Thickness (Max) 0.100" (2.54mm) Lead Spacing - Lead Style -	Series	-
Voltage - Rated 1000V (1kV) Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 3640 (9110 Metric) Size / Dimension 0.360" L x 0.402" W (9.14mm x 10.20mm) Height - Seated (Max) - Thickness (Max) 0.100" (2.54mm) Lead Spacing - Lead Style - 1000V (1kV) C0G, NP0 C0G, N	Capacitance	10000pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 3640 (9110 Metric) Size / Dimension 0.360" L x 0.402" W (9.14mm x 10.20mm) Height - Seated (Max) Thickness (Max) 0.100" (2.54mm) Lead Spacing - Lead Style	Tolerance	±5%
Operating Temperature -55°C ~ 125°C Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 3640 (9110 Metric) Size / Dimension 0.360" L x 0.402" W (9.14mm x 10.20mm) Height - Seated (Max) - Thickness (Max) 0.100" (2.54mm) Lead Spacing - Lead Style -	Voltage - Rated	1000V (1kV)
Features High Voltage Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 3640 (9110 Metric) Size / Dimension 0.360" L x 0.402" W (9.14mm x 10.20mm) Height - Seated (Max) - Thickness (Max) 0.100" (2.54mm) Lead Spacing - Lead Style -	Temperature Coefficient	C0G, NP0
Ratings - General Purpose Failure Rate - Surface Mount, MLCC Package / Case 3640 (9110 Metric) Size / Dimension 0.360" L x 0.402" W (9.14mm x 10.20mm) Height - Seated (Max) - Thickness (Max) 0.100" (2.54mm) Lead Spacing - Lead Style - Surface Mount, MLCC	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 3640 (9110 Metric) Size / Dimension 0.360" L x 0.402" W (9.14mm x 10.20mm) Height - Seated (Max) - Thickness (Max) 0.100" (2.54mm) Lead Spacing - Lead Style -	Features	High Voltage
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 3640 (9110 Metric) Size / Dimension 0.360" L x 0.402" W (9.14mm x 10.20mm) Height - Seated (Max) - Thickness (Max) 0.100" (2.54mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 3640 (9110 Metric) Size / Dimension 0.360" L x 0.402" W (9.14mm x 10.20mm) Height - Seated (Max) - Thickness (Max) 0.100" (2.54mm) Lead Spacing - Lead Style -	Applications	General Purpose
Package / Case 3640 (9110 Metric) Size / Dimension 0.360" L x 0.402" W (9.14mm x 10.20mm) Height - Seated (Max) - Thickness (Max) 0.100" (2.54mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.360" L x 0.402" W (9.14mm x 10.20mm) Height - Seated (Max) - Thickness (Max) 0.100" (2.54mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - - - - - - - - - - - - -	Package / Case	3640 (9110 Metric)
Thickness (Max) 0.100" (2.54mm) Lead Spacing - Lead Style -	Size / Dimension	0.360" L x 0.402" W (9.14mm x 10.20mm)
Lead Spacing-Lead Style-	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.100" (2.54mm)
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

3640AA103JATBE Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

3640AA103JATBE Payment Methods



















3640AA103JATBE Shipping Methods













If you have any question about 3640AA103JATBE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com