



377LB5C1562T Information



For Reference Only

Part Number 377LB5C1562T

Manufacturer CTS-Frequency Controls

Category Crystals, Oscillators, Resonators

Oscillators

Description OSC VCXO 156.2500MHZ LVDS SMD

Package 6-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









377LB5C1562T Specifications

Manufacturer Part Number 377LB5C1562T Manufacturer CTS-Frequency Controls Category Crystals, Oscillators, Resonators Package 6-SMD, No Lead Series 377 Type VCXO Frequency 156.25MHz Function Enable/Disable Output LVDS Voltage - Supply 3.3V Frequency Stability ±25ppm Operating Temperature -20°C ~ 70°C Current - Supply (Max) 55mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.079" (2.00mm)	•	
Category Crystals, Oscillators, Resonators Package 6-SMD, No Lead Series 377 Type VCXO Frequency 156.25MHz Function Enable/Disable Output LVDS Voltage - Supply 3.3V Frequency Stability ±25ppm Operating Temperature -20°C ~ 70°C Current - Supply (Max) 55mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.079" (2.00mm)	Manufacturer Part Number	377LB5C1562T
Package 6-SMD, No Lead Series 377 Type VCXO Frequency 156.25MHz Function Enable/Disable Output LVDS Voltage - Supply 3.3V Frequency Stability ±25ppm Operating Temperature -20°C ~ 70°C Current - Supply (Max) 55mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.079" (2.00mm)	Manufacturer	CTS-Frequency Controls
Package 6-SMD, No Lead Series 377 Type VCXO Frequency 156.25MHz Function Enable/Disable Output LVDS Voltage - Supply 3.3V Frequency Stability ±25ppm Operating Temperature -20°C ~ 70°C Current - Supply (Max) 55mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.079" (2.00mm)	Category	Crystals, Oscillators, Resonators
Series 377 Type VCXO Frequency 156.25MHz Function Enable/Disable Output LVDS Voltage - Supply 3.3V Frequency Stability ±25ppm Operating Temperature -20°C ~ 70°C Current - Supply (Max) 55mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.079" (2.00mm)		Oscillators
Type VCXO Frequency 156.25MHz Function Enable/Disable Output LVDS Voltage - Supply 3.3V Frequency Stability ±25ppm Operating Temperature -20°C ~ 70°C Current - Supply (Max) 55mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.079" (2.00mm)	Package	6-SMD, No Lead
Frequency 156.25MHz Function Enable/Disable Output LVDS Voltage - Supply 3.3V Frequency Stability ±25ppm Operating Temperature -20°C ~ 70°C Current - Supply (Max) 55mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.079" (2.00mm)	Series	377
Function Enable/Disable Output LVDS Voltage - Supply 3.3V Frequency Stability Deprating Temperature -20°C ~ 70°C Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.079" (2.00mm)	Туре	VCXO
Output LVDS Voltage - Supply 3.3V Frequency Stability ±25ppm Operating Temperature -20°C ~ 70°C Current - Supply (Max) 55mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.079" (2.00mm)	Frequency	156.25MHz
Voltage - Supply 3.3V Frequency Stability ±25ppm Operating Temperature -20°C ~ 70°C Current - Supply (Max) 55mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.079" (2.00mm)	Function	Enable/Disable
Frequency Stability ±25ppm Operating Temperature -20°C ~ 70°C Current - Supply (Max) 55mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.079" (2.00mm)	Output	LVDS
Operating Temperature -20°C ~ 70°C Current - Supply (Max) 55mA Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.079" (2.00mm)	Voltage - Supply	3.3V
Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.079" (2.00mm)	Frequency Stability	±25ppm
Ratings - Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.079" (2.00mm)	Operating Temperature	-20°C ~ 70°C
Mounting Type Surface Mount Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.079" (2.00mm)	Current - Supply (Max)	55mA
Package / Case 6-SMD, No Lead Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.079" (2.00mm)	Ratings	-
Size / Dimension 0.276" L x 0.197" W (7.00mm x 5.00mm) Height - Seated (Max) 0.079" (2.00mm)	Mounting Type	Surface Mount
Height - Seated (Max) 0.079" (2.00mm)	Package / Case	6-SMD, No Lead
	Size / Dimension	0.276" L x 0.197" W (7.00mm x 5.00mm)
Report errors?	Height - Seated (Max)	0.079" (2.00mm)
		Report errors?

377LB5C1562T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

377LB5C1562T Payment Methods



















377LB5C1562T Shipping Methods













If you have any question about 377LB5C1562T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com