

4-1393816-0 Information

Heisener.com

Part Number 4-1393816-0

Manufacturer TE Connectivity Potter & Brumfield Relays

Category

Signal Relays, Up to 2 Amps

RELAY GEN PURPOSE 4PDT 2A 24V **Description**

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









4-1393816-0 Specifications

Manufacturer Part Number 4-1393816-0 Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Signal Relays, Up to 2 Amps Package - Series V23005, AXICOM Relay Type General Purpose Coil Type Non Latching Coil Current 141mA Coil Voltage 24VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 150VDC - Max Turn On Voltage (Max) 19.2 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Socketable Termination Style Plug In		
Category Relays Package - Series V23005, AXICOM Relay Type General Purpose Coil Type Non Latching Coil Current 141mA Coil Voltage 24VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 150VDC - Max Turn On Voltage (Max) 19.2 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Socketable Termination Style Plug In	Manufacturer Part Number	4-1393816-0
Package-SeriesV23005, AXICOMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current141mACoil Voltage24VACContact Form4PDT (4 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 150VDC - MaxTurn On Voltage (Max)19.2 VACTurn Off Voltage (Min)-Operate Time-Release Time-Features-Mounting TypeSocketableTermination StylePlug In	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series V23005, AXICOM Relay Type General Purpose Coil Type Non Latching Coil Current 141mA Coil Voltage 24VAC Contact Form 4PDT (4 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 150VDC - Max Turn On Voltage (Max) 19.2 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Socketable Termination Style Plug In	Category	Relays
SeriesV23005, AXICOMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current141mACoil Voltage24VACContact Form4PDT (4 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 150VDC - MaxTurn On Voltage (Max)19.2 VACTurn Off Voltage (Min)-Operate Time-Release Time-Features-Mounting TypeSocketableTermination StylePlug In		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current141mACoil Voltage24VACContact Form4PDT (4 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 150VDC - MaxTurn On Voltage (Max)19.2 VACTurn Off Voltage (Min)-Operate Time-Release Time-Features-Mounting TypeSocketableTermination StylePlug In	Package	-
Coil TypeNon LatchingCoil Current141mACoil Voltage24VACContact Form4PDT (4 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 150VDC - MaxTurn On Voltage (Max)19.2 VACTurn Off Voltage (Min)-Operate Time-Release Time-Features-Mounting TypeSocketableTermination StylePlug In	Series	V23005, AXICOM
Coil Current141mACoil Voltage24VACContact Form4PDT (4 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 150VDC - MaxTurn On Voltage (Max)19.2 VACTurn Off Voltage (Min)-Operate Time-Release Time-Features-Mounting TypeSocketableTermination StylePlug In	Relay Type	General Purpose
Coil Voltage24VACContact Form4PDT (4 Form C)Contact Rating (Current)2ASwitching Voltage125VAC, 150VDC - MaxTurn On Voltage (Max)19.2 VACTurn Off Voltage (Min)-Operate Time-Release Time-Features-Mounting TypeSocketableTermination StylePlug In	Coil Type	Non Latching
Contact Form 4PDT (4 Form C) Contact Rating (Current) 2A Switching Voltage 125VAC, 150VDC - Max Turn On Voltage (Max) 19.2 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Socketable Termination Style Plug In	Coil Current	141mA
Contact Rating (Current) Switching Voltage 125VAC, 150VDC - Max 19.2 VAC Turn On Voltage (Max) 19.2 VAC Turn Off Voltage (Min) Operate Time - Release Time - Features Mounting Type Socketable Termination Style Plug In	Coil Voltage	24VAC
Switching Voltage 125VAC, 150VDC - Max Turn On Voltage (Max) 19.2 VAC Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Socketable Termination Style Plug In	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max) 19.2 VAC Turn Off Voltage (Min) Operate Time Release Time - Release Time - Mounting Type Socketable Termination Style 19.2 VAC	Contact Rating (Current)	2A
Turn Off Voltage (Min) Operate Time Release Time - Features Mounting Type Socketable Termination Style Plug In	Switching Voltage	125VAC, 150VDC - Max
Operate Time Release Time	Turn On Voltage (Max)	19.2 VAC
Release Time	Turn Off Voltage (Min)	-
Features - Mounting Type Socketable Termination Style Plug In	Operate Time	-
Mounting Type Socketable Termination Style Plug In	Release Time	-
Termination Style Plug In	Features	-
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
		Report errors?

4-1393816-0 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

4-1393816-0 Payment Methods



















4-1393816-0 Shipping Methods













If you have any question about 4-1393816-0, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com