



4000-09E07AE999 Information

Heisener.com

4000-09E07AE999 Part Number

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Transformers

Power Transformers

Description XFRMR LAMINATED 40VA CHAS MOUNT

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









4000-09E07AE999 Specifications

Manufacturer Part Number 4000-09E07AE999 Manufacturer TE Connectivity Potter & Brumfield Relays Category Transformers Power Transformers Power Transformers Package - Series 4000, Products Unlimited Type Laminated Core Voltage - Primary 208V, 240V Voltage - Secondary (Full Load) 24V Current - Output (Max) - Primary Winding(s) Single Secondary Winding(s) Single Center Tap No Power - Max 40 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 90.47mm L x 55.58mm W Height - Seated (Max) - Voltage - Isolation - Weight -		
Category Transformers Package - Series 4000, Products Unlimited Type Laminated Core Voltage - Primary 208V, 240V Voltage - Secondary (Full Load) 24V Current - Output (Max) - Primary Winding(s) Single Secondary Winding(s) Single Center Tap No Power - Max 40 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 90.47mm L x 55.58mm W Height - Seated (Max) - Voltage - Isolation - Weight -	Manufacturer Part Number	4000-09E07AE999
Package - Series 4000, Products Unlimited Type Laminated Core Voltage - Primary 208V, 240V Voltage - Secondary (Full Load) 24V Current - Output (Max) - Primary Winding(s) Single Secondary Winding(s) Single Center Tap No Power - Max 40 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 90.47mm L x 55.58mm W Height - Seated (Max) - Weight - Seated Series Se	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package-Series4000, Products UnlimitedTypeLaminated CoreVoltage - Primary208V, 240VVoltage - Secondary (Full Load)24VCurrent - Output (Max)-Primary Winding(s)SingleSecondary Winding(s)SingleCenter TapNoPower - Max40 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension90.47mm L x 55.58mm WHeight - Seated (Max)-Voltage - Isolation-Weight-	Category	Transformers
Series4000, Products UnlimitedTypeLaminated CoreVoltage - Primary208V, 240VVoltage - Secondary (Full Load)24VCurrent - Output (Max)-Primary Winding(s)SingleSecondary Winding(s)SingleCenter TapNoPower - Max40 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension90.47mm L x 55.58mm WHeight - Seated (Max)-Voltage - Isolation-Weight-		Power Transformers
Type Laminated Core Voltage - Primary 208V, 240V Voltage - Secondary (Full Load) 24V Current - Output (Max) - Primary Winding(s) Single Secondary Winding(s) Single Center Tap No Power - Max 40 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 90.47mm L x 55.58mm W Height - Seated (Max) - Voltage - Isolation - Weight	Package	-
Voltage - Primary Voltage - Secondary (Full Load) 24V Current - Output (Max) Primary Winding(s) Secondary Winding(s) Secondary Winding(s) Secondary Winding(s) Center Tap No Power - Max 40 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 90.47mm L x 55.58mm W Height - Seated (Max) Voltage - Isolation Voltage - Isolation - Weight	Series	4000, Products Unlimited
Voltage - Secondary (Full Load) Current - Output (Max) - Primary Winding(s) Secondary Winding(s) Secondary Winding(s) Center Tap No Power - Max 40 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 90.47mm L x 55.58mm W Height - Seated (Max) Voltage - Isolation Voltage - Isolation Weight - 24V Chassis Mount -	Туре	Laminated Core
Current - Output (Max) Primary Winding(s) Single Secondary Winding(s) Single Center Tap No Power - Max 40 VA Mounting Type Chassis Mount Termination Style Size / Dimension 90.47mm L x 55.58mm W Height - Seated (Max) Voltage - Isolation - Weight - Single Single No - No	Voltage - Primary	208V, 240V
Primary Winding(s) Secondary Winding(s) Single Center Tap No Power - Max 40 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 90.47mm L x 55.58mm W Height - Seated (Max) Voltage - Isolation - Weight - Single No Power	Voltage - Secondary (Full Load)	24V
Secondary Winding(s)SingleCenter TapNoPower - Max40 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension90.47mm L x 55.58mm WHeight - Seated (Max)-Voltage - Isolation-Weight-	Current - Output (Max)	-
Center Tap No Power - Max 40 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 90.47mm L x 55.58mm W Height - Seated (Max) - Voltage - Isolation - Weight -	Primary Winding(s)	Single
Power - Max Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 90.47mm L x 55.58mm W Height - Seated (Max) Voltage - Isolation - Weight -	Secondary Winding(s)	Single
Mounting Type Chassis Mount Termination Style Solder, Quick Connect Size / Dimension 90.47mm L x 55.58mm W Height - Seated (Max) - Voltage - Isolation - Weight -	Center Tap	No
Termination Style Size / Dimension 90.47mm L x 55.58mm W Height - Seated (Max) Voltage - Isolation - Weight Weight	Power - Max	40 VA
Size / Dimension90.47mm L x 55.58mm WHeight - Seated (Max)-Voltage - Isolation-Weight-	Mounting Type	Chassis Mount
Height - Seated (Max) Voltage - Isolation Weight - - - - - - - - - - - - -	Termination Style	Solder, Quick Connect
Voltage - Isolation - Weight -	Size / Dimension	90.47mm L x 55.58mm W
Weight -	Height - Seated (Max)	-
	Voltage - Isolation	-
Report errors?	Weight	-
		Report errors?

4000-09E07AE999 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

4000-09E07AE999 Payment Methods





















4000-09E07AE999 Shipping Methods













If you have any question about 4000-09E07AE999, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com