



402F360XXCJT Information



For Reference Only

Part Number 402F360XXCJT

Manufacturer CTS-Frequency Controls

Category Crystals, Oscillators, Resonators

Crystals

Description CRYSTAL 36.0000MHZ 9PF SMD

Package 4-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









402F360XXCJT Specifications

| Manufacturer Part Number402F360XXCJTManufacturerCTS-Frequency ControlsCategoryCrystals, Oscillators, ResonatorsPackage4-SMD, No LeadSeries402TypeMHz CrystalFrequency36MHzFrequency Stability±15ppmFrequency Tolerance±15ppmLoad Capacitance9pFESR (Equivalent Series Resistance)60 OhmOperating ModeFundamentalOperating Temperature-20°C ~ 70°CRatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.079" L x 0.063" W (2.00mm x 1.60mm)Height - Seated (Max)0.022" (0.55mm) | • | |
|--|------------------------------------|---------------------------------------|
| Category Crystals, Oscillators, Resonators Crystals Package 4-SMD, No Lead Series 402 Type MHz Crystal Frequency 36MHz Frequency Stability ±15ppm Frequency Tolerance ±15ppm Load Capacitance 9pF ESR (Equivalent Series Resistance) 60 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.022" (0.55mm) | Manufacturer Part Number | 402F360XXCJT |
| Package 4-SMD, No Lead Series 402 Type MHz Crystal Frequency 36MHz Frequency Stability ±15ppm Frequency Tolerance ±15ppm Load Capacitance 9pF ESR (Equivalent Series Resistance) 60 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.022" (0.55mm) | Manufacturer | CTS-Frequency Controls |
| Package 4-SMD, No Lead Series 402 Type MHz Crystal Frequency 36MHz Frequency Stability ±15ppm Frequency Tolerance ±15ppm Load Capacitance 9pF ESR (Equivalent Series Resistance) 60 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.022" (0.55mm) | Category | Crystals, Oscillators, Resonators |
| Series 402 Type MHz Crystal Frequency 36MHz Frequency Stability ±15ppm Frequency Tolerance ±15ppm Load Capacitance 9pF ESR (Equivalent Series Resistance) 60 Ohm Operating Mode Fundamental Operating Temperature -20°C ~70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.022" (0.55mm) | | Crystals |
| Type MHz Crystal Frequency 36MHz Frequency Stability ±15ppm Frequency Tolerance ±15ppm Load Capacitance 9pF ESR (Equivalent Series Resistance) 60 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.022" (0.55mm) | Package | 4-SMD, No Lead |
| Frequency Stability ±15ppm Frequency Tolerance ±15ppm Load Capacitance 9pF ESR (Equivalent Series Resistance) 60 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.022" (0.55mm) | Series | 402 |
| Frequency Stability Frequency Tolerance Load Capacitance 9pF ESR (Equivalent Series Resistance) Operating Mode Operating Temperature Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension Height - Seated (Max) \$\frac{1}{2}\$ \text{pm}\$ \$\frac{1}{2}\$ \text{pm}\$ | Туре | MHz Crystal |
| Frequency Tolerance ±15ppm Load Capacitance 9pF ESR (Equivalent Series Resistance) 60 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.022" (0.55mm) | Frequency | 36MHz |
| Load Capacitance 9pF ESR (Equivalent Series Resistance) 60 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.022" (0.55mm) | Frequency Stability | ±15ppm |
| ESR (Equivalent Series Resistance) Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.022" (0.55mm) | Frequency Tolerance | ±15ppm |
| Operating ModeFundamentalOperating Temperature $-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$ Ratings-Mounting TypeSurface MountPackage / Case 4-SMD , No LeadSize / Dimension $0.079^{\circ}\text{L} \times 0.063^{\circ}\text{W} (2.00\text{mm} \times 1.60\text{mm})$ Height - Seated (Max) 0.022° (0.55mm) | Load Capacitance | 9pF |
| Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.022" (0.55mm) | ESR (Equivalent Series Resistance) | 60 Ohm |
| Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.022" (0.55mm) | Operating Mode | Fundamental |
| Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.022" (0.55mm) | Operating Temperature | -20°C ~ 70°C |
| Package / Case 4-SMD, No Lead Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.022" (0.55mm) | Ratings | - |
| Size / Dimension 0.079" L x 0.063" W (2.00mm x 1.60mm) Height - Seated (Max) 0.022" (0.55mm) | Mounting Type | Surface Mount |
| Height - Seated (Max) 0.022" (0.55mm) | Package / Case | 4-SMD, No Lead |
| | Size / Dimension | 0.079" L x 0.063" W (2.00mm x 1.60mm) |
| Report errors? | Height - Seated (Max) | 0.022" (0.55mm) |
| | | Report errors? |

402F360XXCJT Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

402F360XXCJT Payment Methods



















402F360XXCJT Shipping Methods













If you have any question about 402F360XXCJT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com