



40PC150G3A Information

Heisener.com

Part Number 40PC150G3A

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR GAUGE 0-150 PSI

Package 6-DIP Module

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









40PC150G3A Specifications

Manufacturer Part Number40PC150G3AManufacturerHoneywell Sensing and Productivity SolutionsCategorySensors, TransducersPackage6-DIP ModuleSeries40PCPressure TypeVented GaugeOperating Pressure150 PSI (1034.21 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±2.5%Voltage - Supply4.75 V ~ 5.25 VPort SizeMale - 0.18" (4.57mm) TubePort StyleBarblessFeaturesAmplified OutputTermination StylePC PinMaximum Pressure300 PSI (2068.43 kPa)Operating Temperature-45°C ~ 125°C	•	
Category Sensors, Transducers Pressure Sensors, Transducers Package 6-DIP Module Series 40PC Pressure Type Vented Gauge Operating Pressure 150 PSI (1034.21 kPa) Output Type Analog Voltage Output 0.5 V ~ 4.5 V Accuracy ±2.5% Voltage - Supply 4.75 V ~ 5.25 V Port Size Male - 0.18" (4.57mm) Tube Port Style Barbless Features Features Amplified Output Termination Style Maximum Pressure 300 PSI (2068.43 kPa) Operating Temperature -45°C ~ 125°C	Manufacturer Part Number	40PC150G3A
Pressure Sensors, Transducers 6-DIP Module Series 40PC Pressure Type Vented Gauge Operating Pressure 150 PSI (1034.21 kPa) Output Type Analog Voltage Output 0.5 V ~ 4.5 V Accuracy ±2.5% Voltage - Supply 4.75 V ~ 5.25 V Port Size Male - 0.18" (4.57mm) Tube Port Style Barbless Features Amplified Output Termination Style Maximum Pressure 300 PSI (2068.43 kPa) Operating Temperature -45°C ~ 125°C	Manufacturer	Honeywell Sensing and Productivity Solutions
Package 6-DIP Module Series 40PC Pressure Type Vented Gauge Operating Pressure 150 PSI (1034.21 kPa) Output Type Analog Voltage Output 0.5 V ~ 4.5 V Accuracy ±2.5% Voltage - Supply 4.75 V ~ 5.25 V Port Size Male - 0.18" (4.57mm) Tube Port Style Barbless Features Amplified Output Termination Style PC Pin Maximum Pressure 300 PSI (2068.43 kPa) Operating Temperature -45°C ~ 125°C	Category	Sensors, Transducers
Series 40PC Pressure Type Vented Gauge Operating Pressure 150 PSI (1034.21 kPa) Output Type Analog Voltage Output 0.5 V ~ 4.5 V Accuracy ±2.5% Voltage - Supply 4.75 V ~ 5.25 V Port Size Male - 0.18" (4.57mm) Tube Port Style Barbless Features Amplified Output Termination Style PC Pin Maximum Pressure 300 PSI (2068.43 kPa) Operating Temperature -45°C ~ 125°C		Pressure Sensors, Transducers
Pressure Type Vented Gauge Operating Pressure 150 PSI (1034.21 kPa) Output Type Analog Voltage Output 0.5 V ~ 4.5 V Accuracy ±2.5% Voltage - Supply 4.75 V ~ 5.25 V Port Size Male - 0.18" (4.57mm) Tube Port Style Barbless Features Amplified Output Termination Style PC Pin Maximum Pressure 300 PSI (2068.43 kPa) Operating Temperature -45°C ~ 125°C	Package	6-DIP Module
Operating Pressure $150 \text{ PSI } (1034.21 \text{ kPa})$ Output TypeAnalog VoltageOutput $0.5 \text{ V} \sim 4.5 \text{ V}$ Accuracy $\pm 2.5\%$ Voltage - Supply $4.75 \text{ V} \sim 5.25 \text{ V}$ Port SizeMale - 0.18 " (4.57mm) TubePort StyleBarblessFeaturesAmplified OutputTermination StylePC PinMaximum Pressure $300 \text{ PSI } (2068.43 \text{ kPa})$ Operating Temperature $-45^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Series	40PC
Output TypeAnalog VoltageOutput $0.5 \text{ V} \sim 4.5 \text{ V}$ Accuracy $\pm 2.5\%$ Voltage - Supply $4.75 \text{ V} \sim 5.25 \text{ V}$ Port SizeMale - 0.18 " (4.57mm) TubePort StyleBarblessFeaturesAmplified OutputTermination StylePC PinMaximum Pressure $300 \text{ PSI } (2068.43 \text{ kPa})$ Operating Temperature $-45^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Pressure Type	Vented Gauge
Output $0.5 \text{ V} \sim 4.5 \text{ V}$ Accuracy $\pm 2.5\%$ Voltage - Supply $4.75 \text{ V} \sim 5.25 \text{ V}$ Port Size $\text{Male} - 0.18'' (4.57 \text{mm}) \text{ Tube}$ Port Style Barbless Features Amplified Output Termination Style PC Pin Maximum Pressure $300 \text{ PSI } (2068.43 \text{ kPa})$ Operating Temperature $-45^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Operating Pressure	150 PSI (1034.21 kPa)
Accuracy $\pm 2.5\%$ Voltage - Supply $4.75 \text{ V} \sim 5.25 \text{ V}$ Port Size $\text{Male - 0.18" (4.57 mm) Tube}$ Port Style Barbless Features Amplified Output Termination Style PC Pin Maximum Pressure $300 \text{ PSI (2068.43 kPa)}$ Operating Temperature $-45^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Output Type	Analog Voltage
Voltage - Supply $4.75 \text{ V} \sim 5.25 \text{ V}$ Port Size $\text{Male} - 0.18'' (4.57 \text{mm}) \text{ Tube}$ Port Style Barbless Features Amplified Output Termination Style PC Pin Maximum Pressure $300 \text{ PSI } (2068.43 \text{ kPa})$ Operating Temperature $-45^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Output	0.5 V ~ 4.5 V
Port Size Male - 0.18" (4.57mm) Tube Port Style Barbless Features Amplified Output Termination Style PC Pin Maximum Pressure 300 PSI (2068.43 kPa) Operating Temperature -45°C ~ 125°C	Accuracy	±2.5%
Port Style Barbless Features Amplified Output Termination Style PC Pin Maximum Pressure 300 PSI (2068.43 kPa) Operating Temperature -45°C ~ 125°C	Voltage - Supply	4.75 V ~ 5.25 V
Features Amplified Output Termination Style PC Pin Maximum Pressure $300 \text{ PSI } (2068.43 \text{ kPa})$ Operating Temperature $-45^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Port Size	Male - 0.18" (4.57mm) Tube
Termination Style PC Pin Maximum Pressure 300 PSI (2068.43 kPa) Operating Temperature -45°C ~ 125°C	Port Style	Barbless
Maximum Pressure $300 \text{ PSI } (2068.43 \text{ kPa})$ Operating Temperature $-45^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Features	Amplified Output
Operating Temperature $-45^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Termination Style	PC Pin
	Maximum Pressure	300 PSI (2068.43 kPa)
	Operating Temperature	-45°C ~ 125°C
Package / Case 6-DIP Module	Package / Case	6-DIP Module
Supplier Device Package -	Supplier Device Package	-
Report errors?		Report errors?

40PC150G3A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

40PC150G3A Payment Methods



















40PC150G3A Shipping Methods













If you have any question about 40PC150G3A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com