



416F36011ATT Information



For Reference Only

Part Number 416F36011ATT

Manufacturer CTS-Frequency Controls

Category Crystals, Oscillators, Resonators

Crystals

Description CRYSTAL 36.000 MHZ 6PF SMT

Package 4-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









416F36011ATT Specifications

Manufacturer Part Number 416F36011ATT Manufacturer CTS-Frequency Controls Category Crystals, Oscillators, Resonators Crystals Crystals Package 4-SMD, No Lead Series 416 Type MHz Crystal Frequency 36MHz Frequency Stability ±10ppm Frequency Tolerance ±10ppm Load Capacitance 6pF ESR (Equivalent Series Resistance) 200 Ohm Operating Mode Fundamental Operating Temperature -10°C ~ 60°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)		
Category Crystals, Oscillators, Resonators Crystals Package 4-SMD, No Lead Series 416 Type MHz Crystal Frequency 36MHz Frequency Stability Frequency Tolerance ±10ppm Load Capacitance 6pF ESR (Equivalent Series Resistance) Operating Mode Operating Temperature -10°C ~ 60°C Ratings Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Manufacturer Part Number	416F36011ATT
Crystals Package 4-SMD, No Lead Series 416 Type MHz Crystal Frequency 36MHz Frequency Stability ±10ppm Frequency Tolerance ±10ppm Load Capacitance 6pF ESR (Equivalent Series Resistance) 200 Ohm Operating Mode Fundamental Operating Temperature -10°C ~ 60°C Ratings Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Manufacturer	CTS-Frequency Controls
Package 4-SMD, No Lead Series 416 Type MHz Crystal Frequency 36MHz Frequency Stability ±10ppm Frequency Tolerance ±10ppm Load Capacitance 6pF ESR (Equivalent Series Resistance) 200 Ohm Operating Mode Fundamental Operating Temperature -10°C ~ 60°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Category	Crystals, Oscillators, Resonators
Series 416 Type MHz Crystal Frequency 36MHz Frequency Stability ±10ppm Frequency Tolerance ±10ppm Load Capacitance 6pF ESR (Equivalent Series Resistance) 200 Ohm Operating Mode Fundamental Operating Temperature -10°C ~ 60°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead		Crystals
Type MHz Crystal Frequency 36MHz Frequency Stability ±10ppm Frequency Tolerance ±10ppm Load Capacitance 6pF ESR (Equivalent Series Resistance) 200 Ohm Operating Mode Fundamental Operating Temperature -10°C ~ 60°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Package	4-SMD, No Lead
Frequency Stability ±10ppm Frequency Tolerance ±10ppm Load Capacitance 6pF ESR (Equivalent Series Resistance) 200 Ohm Operating Mode Fundamental Operating Temperature -10°C ~ 60°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Series	416
Frequency Stability $\pm 10 \mathrm{ppm}$ Frequency Tolerance $\pm 10 \mathrm{ppm}$ Load Capacitance $6 \mathrm{pF}$ ESR (Equivalent Series Resistance) $200 \mathrm{Ohm}$ Operating Mode Fundamental Operating Temperature $-10^{\circ}\mathrm{C} \sim 60^{\circ}\mathrm{C}$ Ratings $-$ Mounting Type Surface Mount Package / Case 4-SMD , No Lead	Type	MHz Crystal
Frequency Tolerance $\pm 10 \mathrm{ppm}$ Load Capacitance $6 \mathrm{pF}$ ESR (Equivalent Series Resistance) $200 \mathrm{Ohm}$ Operating Mode Fundamental Operating Temperature $-10^{\circ}\mathrm{C} \sim 60^{\circ}\mathrm{C}$ Ratings - Mounting Type Surface Mount Package / Case 4-SMD , No Lead	Frequency	36MHz
Load Capacitance 6pF ESR (Equivalent Series Resistance) 200 Ohm Operating Mode Fundamental Operating Temperature -10°C ~ 60°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Frequency Stability	±10ppm
ESR (Equivalent Series Resistance) Operating Mode Fundamental Operating Temperature -10°C ~ 60°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Frequency Tolerance	± 10 ppm
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	Load Capacitance	6pF
$ \begin{array}{cccc} \text{Operating Temperature} & & -10^{\circ}\text{C} \sim 60^{\circ}\text{C} \\ \text{Ratings} & & - \\ \text{Mounting Type} & & \text{Surface Mount} \\ \text{Package / Case} & & 4\text{-SMD, No Lead} \\ \end{array} $	ESR (Equivalent Series Resistance)	200 Ohm
Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Operating Mode	Fundamental
Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Operating Temperature	-10°C ~ 60°C
Package / Case 4-SMD, No Lead	Ratings	-
-	Mounting Type	Surface Mount
Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)	Package / Case	4-SMD, No Lead
	Size / Dimension	0.063" L x 0.047" W (1.60mm x 1.20mm)
Height - Seated (Max) 0.018" (0.45mm)	Height - Seated (Max)	0.018" (0.45mm)
Report errors?		Report errors?

416F36011ATT Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

416F36011ATT Payment Methods



















416F36011ATT Shipping Methods













If you have any question about 416F36011ATT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com