



416F380XXCDR Information

www.medicale.me

For Reference Only

Part Number 416F380XXCDR

Manufacturer CTS-Frequency Controls

Category Crystals, Oscillators, Resonators

Crystals

Description CRYSTAL 38.000 MHZ 18PF SMT

Package 4-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









416F380XXCDR Specifications

Manufacturer Part Number 416F380XXCDR Manufacturer CTS-Frequency Controls Category Crystals, Oscillators, Resonators Package 4-SMD, No Lead Series 416 Type MHz Crystal Frequency 38MHz Frequency Stability ±15ppm Frequency Tolerance ±15ppm Load Capacitance 18pF ESR (Equivalent Series Resistance) 200 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm) Height - Seated (Max) 0.018" (0.45mm)	*	
Category Crystals Package 4-SMD, No Lead Series 416 Type MHz Crystal Frequency 38MHz Frequency Stability ±15ppm Frequency Tolerance ±15ppm Load Capacitance 18pF ESR (Equivalent Series Resistance) Operating Mode Operating Temperature -20°C ~ 70°C Ratings Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension Ools" (0.45mm) Crystals, Oscillators, Resonators Crystals 4-SMD, No Lead Size / Odom x 1.20mm) Height - Seated (Max) Ools" (0.45mm)	Manufacturer Part Number	416F380XXCDR
Package 4-SMD, No Lead Series 416 Type MHz Crystal Frequency 38MHz Frequency Stability ±15ppm Frequency Tolerance ±15ppm Load Capacitance 18pF ESR (Equivalent Series Resistance) 200 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm) Height - Seated (Max) 0.018" (0.45mm)	Manufacturer	CTS-Frequency Controls
Package 4-SMD, No Lead Series 416 Type MHz Crystal Frequency 38MHz Frequency Stability ±15ppm Frequency Tolerance ±15ppm Load Capacitance 18pF ESR (Equivalent Series Resistance) 200 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm) Height - Seated (Max) 0.018" (0.45mm)	Category	Crystals, Oscillators, Resonators
Series 416 Type MHz Crystal Frequency 38MHz Frequency Stability ±15ppm Frequency Tolerance ±15ppm Load Capacitance 18pF ESR (Equivalent Series Resistance) 200 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm) Height - Seated (Max) 0.018" (0.45mm)		Crystals
Type MHz Crystal Frequency 38MHz Frequency Stability ±15ppm Frequency Tolerance ±15ppm Load Capacitance 18pF ESR (Equivalent Series Resistance) 200 Ohm Operating Mode Fundamental Operating Temperature -20°C ~70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm) Height - Seated (Max) 0.018" (0.45mm)	Package	4-SMD, No Lead
Frequency Stability Frequency Stability Frequency Tolerance Load Capacitance ESR (Equivalent Series Resistance) Operating Mode Operating Temperature Ratings - Mounting Type Surface Mount Package / Case Size / Dimension Height - Seated (Max) 38MHz ±15ppm 18pF 200 Ohm Fundamental -20° C ~ 70° C Surface Mount -20° C ~ 70° C -20° C ~ 70° C	Series	416
Frequency Stability Frequency Tolerance Load Capacitance 18pF ESR (Equivalent Series Resistance) Operating Mode Operating Temperature Fatings - Mounting Type Surface Mount Package / Case Size / Dimension Height - Seated (Max) **Estable pm ±15ppm ±15ppm ±15ppm ±15ppm 200 Ohm Fundamental -20° C ~ 70° C **Surface Mount **Operating Temperature -20° C ~ 70° C **Surface Mount **Out 1.60mm x 1.20mm) **Out 1.60mm x 1.20mm)	Туре	MHz Crystal
Frequency Tolerance ±15ppm Load Capacitance 18pF ESR (Equivalent Series Resistance) 200 Ohm Operating Mode Fundamental Operating Temperature -20°C ~ 70°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm) Height - Seated (Max) 0.018" (0.45mm)	Frequency	38MHz
Load Capacitance18pFESR (Equivalent Series Resistance)200 OhmOperating ModeFundamentalOperating Temperature-20°C ~ 70°CRatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.063" L x 0.047" W (1.60mm x 1.20mm)Height - Seated (Max)0.018" (0.45mm)	Frequency Stability	±15ppm
ESR (Equivalent Series Resistance) 200 Ohm Operating Mode Fundamental Operating Temperature $-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$ Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm) Height - Seated (Max) 0.018" (0.45mm)	Frequency Tolerance	±15ppm
$\begin{array}{llllllllllllllllllllllllllllllllllll$	Load Capacitance	18pF
$ \begin{array}{llllllllllllllllllllllllllllllllllll$	ESR (Equivalent Series Resistance)	200 Ohm
Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm) Height - Seated (Max) 0.018" (0.45mm)	Operating Mode	Fundamental
Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm) Height - Seated (Max) 0.018" (0.45mm)	Operating Temperature	-20°C ~ 70°C
Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm) Height - Seated (Max) 0.018" (0.45mm)	Ratings	-
Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm) Height - Seated (Max) 0.018" (0.45mm)	Mounting Type	Surface Mount
Height - Seated (Max) 0.018" (0.45mm)	Package / Case	4-SMD, No Lead
	Size / Dimension	0.063" L x 0.047" W (1.60mm x 1.20mm)
Report errors?	Height - Seated (Max)	0.018" (0.45mm)
		Report errors?

416F380XXCDR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

416F380XXCDR Payment Methods



















416F380XXCDR Shipping Methods













If you have any question about 416F380XXCDR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com